

2K EPOXY PRIMER

Creation date	22nd September 2022	Version	4.0
Revision date			

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier 2K EPOXY PRIMER
Substance / mixture mixture
Number 1 35291
UFI XCP2-GDRT-2008-7W1V

1.2. Relevant identified uses of the substance or mixture and uses advised against**Mixture's intended use**

Two-component primer.

The use descriptors

SU 22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PROC 7	Industrial spraying
PROC 11	Non industrial spraying

Mixture uses advised against

For professional use only.

1.3. Details of the supplier of the safety data sheet**Supplier**

Name or trade name	RETECH, s.r.o.
Address	Vackova 1541/4, Praha 5 - Stodůlky, 155 00 Czech Republic
Identification number (CRN)	25018205
VAT Reg No	CZ25018205
Phone	+420327596428
E-mail	info@retech.cz
Web address	www.retech.com

Competent person responsible for the safety data sheet

Name	RETECH, s.r.o.
E-mail	info@retech.cz

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification of the mixture in accordance with Regulation (EC) No 1272/2008**

The mixture is classified as dangerous.

Aerosol 1, H222, H229
Skin Irrit. 2, H315
Skin Sens. 1, H317
Eye Irrit. 2, H319
STOT RE 2, H373
Aquatic Chronic 3, H412

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Extremely flammable aerosol. Pressurised container: May burst if heated.

Most serious adverse effects on human health and the environment

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

2K EPOXY PRIMER

Creation date

22nd September 2022

Revision date

Version

4.0

2.2. Label elements**Hazard pictogram****Signal word**

Danger

Hazardous substances

xylene

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight 700-1000)

condensation products of dimerised fatty acids, C18-unsaturated, with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine

Hazard statements

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

H319

Causes serious eye irritation.

H373

May cause damage to organs through prolonged or repeated exposure.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211

Do not spray on an open flame or other ignition source.

P251

Do not pierce or burn, even after use.

P260

Do not breathe spray.

P280

Wear protective gloves.

P284

In case of inadequate ventilation wear respiratory protection.

P302+P352

IF ON SKIN: Wash with plenty of water and soap.

P312

Call a POISON CENTER/doctor if you feel unwell.

P410+P412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501

Dispose of contents/container to in accordance with national regulations.

Supplemental information

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Density

1,0 g/cm³ at 20 °C

VOC

63,3 %

Dry matter

30,7 % volume

VOC limit value

cat. B (e) : 840 g/l

Max. VOC content in the product in its ready to use condition

632,9 g/l

2.3. Other hazards

Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Buildup of explosive mixtures possible without sufficient ventilation.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

2K EPOXY PRIMER

Creation date 22nd September 2022
Revision date Version 4.0

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 603-019-00-8 CAS: 115-10-6 EC: 204-065-8 Registration number: 01-2119472128-37	dimethyl ether	25-<50	Flam. Gas 1A, H220 Press. Gas (compressed gas), H280	4
Index: 601-022-00-9 EC: 905-588-0 Registration number: 01-2119488216-32	xylene	12,5-<20,0	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373	
Index: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 Registration number: 01-2119471330-49	acetone	5-<10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	4
Index: 603-074-00-8 CAS: 25068-38-6 EC: 500-033-5 Registration number: 01-2119456619-26	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight 700-1000)	5-<10	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319	
Index: 603-064-00-3 CAS: 107-98-2 EC: 203-539-1 Registration number: 01-2119457435-35	1-methoxy-2-propanol	2,5-<5,0	Flam. Liq. 3, H226 STOT SE 3, H336	4
EC: 918-668-5 Registration number: 01-2119455851-35	hydrocarbons, C9, aromatics	<2,5	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335, H336 Aquatic Chronic 2, H411	
Index: 606-010-00-7 CAS: 108-94-1 EC: 203-631-1 Registration number: 01-2119453616-35	cyclohexanone	<2,5	Flam. Liq. 3, H226 Acute Tox. 4, H302+H312+H332 Skin Irrit. 2, H315 Eye Dam. 1, H318	4
Index: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9 Registration number: 01-2119475791-29	2-methoxy-1-methylethyl acetate	<2,5	Flam. Liq. 3, H226 STOT SE 3, H336	4
Index: 022-006-00-2 CAS: 13463-67-7 EC: 236-675-5 Registration number: 01-2119489379-17	titanium dioxide	<2,5	Carc. 2, H351 (inhalation)	1, 2, 3
Index: 030-011-00-6 CAS: 7779-90-0 EC: 231-944-3 Registration number: 01-2119485044-40	trizinc bis(orthophosphate)	≤0,5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

2K EPOXY PRIMER

Creation date 22nd September 2022

Revision date Version 4.0

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 162627-17-0 EC: 605-296-0 Registration number: 01-2119970640-38	condensation products of dimerised fatty acids, C18-unsaturated, with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine	≤0,5	Skin Sens. 1, H317	

Notes

- Note V: If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.
- Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

- Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.
- Substance with a Union workplace exposure limit.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

Symptoms of poisoning may manifest after many hours, medical supervision is necessary for 48 hours after the accident.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Provide medical treatment. In case of unconsciousness place patient stably in side position for transportation.

If on skin

Immediately wash with water and soap and rinse thoroughly.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. In the event of issues, find medical advice.

If swallowed

Rinse out the mouth with clean water. Provide medical treatment.

4.2. Most important symptoms and effects, both acute and delayed**If inhaled**

not available

If on skin

May cause an allergic skin reaction. Causes skin irritation.

If in eyes

Causes serious eye irritation.

If swallowed

not available

4.3. Indication of any immediate medical attention and special treatment needed

not available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide, powder, water spray jet. Fight larger fires with water spray or alcohol resistant foam. Accommodate according to the location of the fire.

Unsuitable extinguishing media

not available

5.2. Special hazards arising from the substance or mixture

In the event of fire toxic gases may arise.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

2K EPOXY PRIMER

Creation date 22nd September 2022
Revision date Version 4.0

5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Extremely flammable aerosol. Pressurised container: May burst if heated. Remove all ignition sources. Use personal protective equipment for work. Keep unprotected persons away.

6.2. Environmental precautions

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

6.3. Methods and material for containment and cleaning up

Provide sufficient ventilation. Dispose of the collected material according to the instructions in the section 13.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Use personal protective equipment as per Section 8.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value	Note
1-methoxy-2-propanol (CAS: 107-98-2)	OEL 8 hours	375 mg/m ³	Skin
	OEL 8 hours	100 ppm	
	OEL 15 minutes	568 mg/m ³	
	OEL 15 minutes	150 ppm	

European Union

EU limits

Substance name (component)	Type	Value	Note
dimethyl ether (CAS: 115-10-6)	OEL 8 hours	1920 mg/m ³	
	OEL 8 hours	1000 ppm	
acetone (CAS: 67-64-1)	OEL 8 hours	1210 mg/m ³	
	OEL 8 hours	500 ppm	
cyclohexanone (CAS: 108-94-1)	OEL 8 hours	40,8 mg/m ³	
	OEL 8 hours	10 ppm	
	OEL 15 minutes	81,6 mg/m ³	
	OEL 15 minutes	20 ppm	
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	OEL 8 hours	275 mg/m ³	
	OEL 8 hours	50 ppm	
	OEL 15 minutes	550 mg/m ³	

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

2K EPOXY PRIMER

Creation date 22nd September 2022
Revision date Version 4.0

European Union

EU limits

Substance name (component)	Type	Value	Note
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	OEL 15 minutes	100 ppm	

8.2. Exposure controls

Do not store together with food, drink and animal feed. Immediately remove all soiled and contaminated clothing. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest. Do not inhale aerosols. Prevent contact with skin and eyes.

Eye/face protection

Tightly sealed goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. Material of gloves: Butyl rubber. Recommended thickness of the material: ≥ 0.4 mm. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear.

Respiratory protection

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self contained respiratory protective device. Filter A2/P3.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	gas
Colour	grey
Odour	characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	data not available
Flammability	Extremely flammable aerosol.
Lower and upper explosion limit	
bottom	1,0 %
upper	26,2 %
Flash point	240 °C
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	data not available
Kinematic viscosity	data not available
Solubility in water	almost insoluble
Solubility in fats	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	4000 hPa at 20 °C
Density and/or relative density	
Density	1,0 g/cm ³ at 20 °C
Form	aerosol
data not available	

9.2. Other information

Evaporation rate	data not available
Content of organic solvents (VOC)	63,3 %
Solid content (dry matter)	30,7 % volume
VOC limit value	cat. B (e) : 840 g/l
Max. VOC content in the product in its ready to use condition	632,9 g/l
data not available	

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

2K EPOXY PRIMER

Creation date 22nd September 2022
Revision date Version 4.0

SECTION 10: Stability and reactivity

- 10.1. Reactivity**
not available
- 10.2. Chemical stability**
The product is stable under normal conditions.
- 10.3. Possibility of hazardous reactions**
Unknown.
- 10.4. Conditions to avoid**
not available
- 10.5. Incompatible materials**
not available
- 10.6. Hazardous decomposition products**
Unknown.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	8530 mg/kg		Rat	
Dermal	LD ₅₀	>5000 mg/kg		Rabbit	
Inhalation	LC ₅₀	>10000 mg/m ³	4 hour	Rat	

acetone

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	5800 mg/kg		Rat	
Dermal	LD ₅₀	>15800 mg/kg		Rabbit	
Inhalation	LC ₅₀	76 mg/l	4 hour	Rat	

cyclohexanone

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Inhalation	LC ₅₀	>6.2 mg/l	4 hour	Rat	

hydrocarbons, C9, aromatics

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	3592 mg/kg		Rat	
Dermal	LD ₅₀	3160 mg/kg		Rabbit	

xylene

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	3523 mg/kg		Rat	
Dermal	LD ₅₀	2000 mg/kg		Rabbit	
Inhalation	LC ₅₀	29000 mg/m ³	4 hour	Rat	

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

2K EPOXY PRIMER

Creation date

22nd September 2022

Revision date

Version

4.0

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

Based on available data the classification criteria are not met.

Toxicity for specific target organ - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data the classification criteria are not met.

11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

Harmful to aquatic life with long lasting effects.

2-methoxy-1-methylethyl acetate

Parameter	Value	Exposure time	Species	Environment
EC ₅₀	>500 mg/l	48 hour	Daphnia (Daphnia magna)	
LC ₅₀	100-180 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	

acetone

Parameter	Value	Exposure time	Species	Environment
LC ₅₀	8300 mg/l	96 hour	Fishes	
EC ₅₀	7200 mg/l	96 hour	Algae	
LC ₅₀	8450 mg/l	48 hour	Crustaceans	

dimethyl ether

Parameter	Value	Exposure time	Species	Environment
EC ₅₀	155 mg/l	96 hour	Algae	
LC ₅₀	>4000 mg/l	48 hour	Daphnia (Daphnia magna)	
LC ₅₀	>4000 mg/l	96 hour	Fishes	

hydrocarbons, C9, aromatics

Parameter	Value	Exposure time	Species	Environment
EC ₅₀	3.2 mg/l	48 hour	Daphnia (Daphnia magna)	
EC ₅₀	2.75 mg/l	72 hour	Algae (Pseudokirchneriella subcapitata)	
EC ₅₀	9.2 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	

xylene

Parameter	Value	Exposure time	Species	Environment
EC ₅₀	7.4 mg/l	48 hour	Daphnia (Daphnia magna)	
LC ₅₀	13.5 mg/l	96 hour	Fishes	

12.2. Persistence and degradability

Not available.

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

2K EPOXY PRIMER

Creation date

22nd September 2022

Revision date

Version

4.0

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Ecotoxicological effects: Remark: Toxic for fish

Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water. Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances *

Packaging waste type code

15 01 11 metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers *

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information**14.1. UN number or ID number**

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not relevant

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

2K EPOXY PRIMER

Creation date	22nd September 2022	Version	4.0
Revision date			

Additional information


Stowage Code: SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. Segregation Code: SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

Hazard identification No.

UN number

Classification code

Safety signs



5F

2.1



Road transport - ADR

Limited quantities

Excepted quantities

Transport category

Tunnel restriction code

1L

E0

2

(D)

Railway transport - RID

Marine transport - IMDG

EmS (emergency plan)

Marine Pollutant

F-D, S-U

Yes

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended. Product contains reportable explosives precursors: Reporting of suspicious transactions, disappearances and thefts according to Regulation (EU) 2019/1148, Article 9.

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer if inhaled.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

2K EPOXY PRIMER

Creation date	22nd September 2022	Version	4.0
Revision date			

H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H312+H332	Harmful in contact with skin or if inhaled.
H302+H312+H332	Harmful if swallowed, in contact with skin or if inhaled.

Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P280	Wear protective gloves.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with national regulations.
P284	In case of inadequate ventilation wear respiratory protection.
P312	Call a POISON CENTER/doctor if you feel unwell.

A list of additional standard phrases used in the safety data sheet

EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH066	Repeated exposure may cause skin dryness or cracking.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
ES	Identification code for each substance listed in EINECS
EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
log K _{ow}	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution from Ships
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

2K EPOXY PRIMER

Creation date	22nd September 2022	Version	4.0
Revision date			

UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Acute Tox.	Acute toxicity
Aerosol	Aerosol
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
Carc.	Carcinogenicity
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Press. Gas	Gases under pressure
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 4.0 replaces the SDS version from 05 August 2020. Changes were made in sections 11, 12, 13, 15 and 16.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.