

**2K EPOXY PRIMER**

Creation date	11. April 2018	Version	2.0
Revision date	11. June 2018		

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Substance / mixture	2K EPOXY PRIMER
Number	mixture 1 35291

**1.2. Relevant identified uses of the substance or mixture and uses advised against mixture's intended use**

Two-component primer.

**The use descriptors**

SU 22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

PROC 7 Industrial spraying

PROC 11 Non industrial spraying

Disapproved uses of mixture For professional use only.

**1.3. Details of the supplier of the safety data sheet****Supplier**

Name or trade name	RETECH, s.r.o.
Address	Vackova 1541/4, Praha 5 - Stodůlky, 155 00 Czech Republic
Identification number (ID)	25018205
Phone	+420327596428
E-mail	info@retech.cz
Web address	www.retech.com

**Competent person responsible for the safety data sheet**

Name	RETECH, s.r.o.
E-mail	info@retech.cz

**1.4. Emergency telephone number**

RETECH, Suchdol 212, 285 02 Suchdol u Kutné Hory, Czech Republic; Telephone number: +420 327 596 128 (7.30-16.00 hour)  
Poisoning information centre, Na Bojišti 1, Praha, Czech Republic, Tel.: non-stop +420 224 919 293 or +420 224 915 402, Information on health risks only - acute poisoning of humans and animals.

**SECTION 2: Hazards identification****2.1. Substance or mixture classification****Classification of the mixture in accordance with Regulation (EC) No 1272/2008**

The mixture is classified as dangerous.

Aerosol 1, H222, H229  
Skin Irrit. 2, H315  
Skin Sens. 1, H317  
Eye Irrit. 2, H319  
Aquatic Chronic 3, H412

Full text of all classifications and hazard statements is given in the section 16.

**Most serious adverse physico-chemical effects**

Extremely flammable aerosol. Pressurised container: May burst if heated.

**Most serious adverse effects on human health and the environment**

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

**2K EPOXY PRIMER**

Creation date	11. April 2018	Version	2.0
Revision date	11. June 2018		

**2.2. Label elements****Hazard pictogram****Signal word**

Danger

**Hazardous substances**

epoxy resin (number average molecular weight  $\leq 700$ )  
condensation products of dimerised fatty acids, C18-unsaturated, with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine

**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P280	Wear protective gloves.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to in accordance with national regulations.

**Supplemental information**

Density	0.98 g/cm <sup>3</sup>
VOC	63.7 %
Dry matter	30.5 % volume
VOC limit value	cat. B (e) : 840 g/l
Max. VOC content in the product in its ready to use condition	624.1 g/l

**2.3. Other hazards**

Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Buildup of explosive mixtures possible without sufficient ventilation.

## 2K EPOXY PRIMER

Creation date 11. April 2018  
 Revision date 11. June 2018 Version 2.0

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Mixture of substances and additives specified below.

**Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment**

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note.
Index: 603-019-00-8 CAS: 115-10-6 EC: 204-065-8 Registration number: 01-2119472128-37	dimethyl ether	25-<50	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	1
Index: 603-074-00-8 CAS: 25068-38-6 EC: 500-033-5	epoxy resin (number average molecular weight ≤ 700)	5-<10	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319	
Index: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 Registration number: 01-2119471330-49	acetone	5-<10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	1
Index: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 Registration number: 01-2119488216-32-xxxx	xylene	5-<10	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412	1
Index: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 Registration number: 01-2119488216-32	xylene (mixture of isomers)	5-<10	Flam. Liq. 3, H226 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315	1
Index: 603-064-00-3 CAS: 107-98-2 EC: 203-539-1 Registration number: 01-2119457435-35	1-methoxy-2-propanol	2,5-<5	Flam. Liq. 3, H226 STOT SE 3, H336	1
Index: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 Registration number: 01-2119489370-35	ethylbenzene	2,5-<5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Acute Tox. 4, H332 STOT RE 2, H373 Aquatic Chronic 3, H412	1
EC: 918-668-5 Registration number: 01-2119455851-35	hydrocarbons, C9, aromatics	<2,5	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335, H336 Aquatic Chronic 2, H411	
Index: 606-010-00-7 CAS: 108-94-1 EC: 203-631-1	cyclohexanone	<2,5	Flam. Liq. 3, H226 Acute Tox. 4, H332	1

**2K EPOXY PRIMER**

Creation date 11. April 2018

Revision date 11. June 2018

Version 2.0

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note.
CAS: 108-65-6 EC: 203-603-9 Registration number: 01-2119475791-29	2-methoxy-1-methylethyl acetate	<2,5	Flam. Liq. 3, H226	1
Index: 030-011-00-6 CAS: 7779-90-0 EC: 231-944-3 Registration number: 01-2119485044-40	trizinc bis(orthophosphate)	≤0,5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
CAS: 162627-17-0 EC: 605-296-0 Registration number: 01-2119970640-38	condensation products of dimerised fatty acids, C18-unsaturated, with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine	≤0,5	Skin Sens. 1, H317	

**Notes**

1 Substance for which exposure limits of Community for working environment exist.

Full text of all classifications and hazard statements is given in the section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures**

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

**Inhalation**

Terminate the exposure immediately; move the affected person to fresh air. Provide medical treatment. In case of unconsciousness place patient stably in side position for transportation.

**Skin contact**

Immediately wash with water and soap and rinse thoroughly.

**Eye contact**

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. In the event of issues, find medical advice.

**Ingestion**

Rinse out the mouth with clean water. Provide medical treatment.

**4.2. Most important symptoms and effects, both acute and delayed****Inhalation**

not available

**Skin contact**

May cause an allergic skin reaction.

**Eye contact**

Causes serious eye irritation.

**Ingestion**

not available

**4.3. Indication of any immediate medical attention and special treatment needed**

not available

**2K EPOXY PRIMER**

Creation date 11. April 2018  
Revision date 11. June 2018 Version 2.0

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Carbon dioxide, powder, water spray jet. Fight larger fires with water spray or alcohol resistant foam. Accommodate according to the location of the fire.

**Unsuitable extinguishing media**

not available

**5.2. Special hazards arising from the substance or mixture**

In the event of fire toxic gases may arise.

**5.3. Advice for firefighters**

Use a self-contained breathing apparatus and full-body protective clothing.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Provide sufficient ventilation. Use personal protective equipment for work. Keep unprotected persons away.

**6.2. Environmental precautions**

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

**6.3. Methods and material for containment and cleaning up**

Provide sufficient ventilation. Dispose of the collected material according to the instructions in the section 13.

**6.4. Reference to other sections**

See the Section 7, 8 and 13.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Prevent contact with skin and eyes. Wash hands and exposed parts of the body thoroughly after handling. Use personal protective equipment as per Section 8.

**7.2. Conditions for safe storage, including any incompatibilities**

Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Storage class 2B - Aerosols

**7.3. Specific end use(s)**

not available

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

The mixture contains substances for which occupational exposure limits are set.

**European Union**

Substance name (component)	Type	Time of exposure	Value	Note	Source
dimethyl ether (CAS: 115-10-6)	OEL	8 hours	1920 mg/m <sup>3</sup>		EU limits
	OEL	8 hours	1000 ppm		
acetone (CAS: 67-64-1)	OEL	8 hours	1210 mg/m <sup>3</sup>		EU limits
	OEL	8 hours	500 ppm		
xylene (CAS: 1330-20-7)	OEL	8 hours	221 mg/m <sup>3</sup>		EU limits
	OEL	8 hours	50 ppm		
	OEL	Short-term	442 mg/m <sup>3</sup>		
	OEL	Short-term	100 ppm		

**2K EPOXY PRIMER**

Creation date

11. April 2018

Revision date

11. June 2018

Version

2.0

**European Union**

Substance name (component)	Type	Time of exposure	Value	Note	Source
xylene (mixture of isomers) (CAS: 1330-20-7)	OEL	8 hours	221 mg/m <sup>3</sup>		EU limits
	OEL	8 hours	50 ppm		
	OEL	Short-term	442 mg/m <sup>3</sup>		
	OEL	Short-term	100 ppm		
1-methoxy-2-propanol (CAS: 107-98-2)	OEL	8 hours	375 mg/m <sup>3</sup>		EU limits
	OEL	8 hours	100 ppm		
	OEL	Short-term	568 mg/m <sup>3</sup>		
	OEL	Short-term	150 ppm		
ethylbenzene (CAS: 100-41- 4)	OEL	8 hours	442 mg/m <sup>3</sup>		EU limits
	OEL	8 hours	100 ppm		
	OEL	Short-term	884 mg/m <sup>3</sup>		
	OEL	Short-term	200 ppm		
cyclohexanone (CAS: 108-94- 1)	OEL	8 hours	40,8 mg/m <sup>3</sup>		EU limits
	OEL	8 hours	10 ppm		
	OEL	Short-term	81,6 mg/m <sup>3</sup>		
	OEL	Short-term	20 ppm		
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	OEL	8 hours	275 mg/m <sup>3</sup>		EU limits
	OEL	8 hours	50 ppm		
	OEL	Short-term	550 mg/m <sup>3</sup>		
	OEL	Short-term	100 ppm		

**United Kingdom of Great Britain and Northern Ireland**

Substance name (component)	Type	Time of exposure	Value	Note	Source
dimethyl ether (CAS: 115-10- 6)	WEL	8 hours	766 mg/m <sup>3</sup>		GBR
	WEL	15 minutes	958 mg/m <sup>3</sup>		
	WEL	8 hours	400 ppm		

**2K EPOXY PRIMER**

Creation date 11. April 2018  
Revision date 11. June 2018 Version 2.0

**United Kingdom of Great Britain and Northern Ireland**

Substance name (component)	Type	Time of exposure	Value	Note	Source
dimethyl ether (CAS: 115-10-6)	WEL	15 minutes	500 ppm		GBR
acetone (CAS: 67-64-1)	WEL	8 hours	1210 mg/m <sup>3</sup>		GBR
	WEL	15 minutes	3620 mg/m <sup>3</sup>		
	WEL	8 hours	500 ppm		
	WEL	15 minutes	1500 ppm		
xylene (CAS: 1330-20-7)	WEL	8 hours	220 mg/m <sup>3</sup>	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
	WEL	15 minutes	441 mg/m <sup>3</sup>	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	8 hours	50 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	15 minutes	100 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
xylene (mixture of isomers) (CAS: 1330-20-7)	WEL	8 hours	220 mg/m <sup>3</sup>	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
	WEL	15 minutes	441 mg/m <sup>3</sup>	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	8 hours	50 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	15 minutes	100 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	

**2K EPOXY PRIMER**

Creation date 11. April 2018  
Revision date 11. June 2018 Version 2.0

**United Kingdom of Great Britain and Northern Ireland**

Substance name (component)	Type	Time of exposure	Value	Note	Source
1-methoxy-2-propanol (CAS: 107-98-2)	WEL	8 hours	375 mg/m <sup>3</sup>	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
	WEL	15 minutes	560 mg/m <sup>3</sup>	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	8 hours	100 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	15 minutes	150 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
ethylbenzene (CAS: 100-41-4)	WEL	8 hours	441 mg/m <sup>3</sup>		Gestis
	WEL	Short-term	552 mg/m <sup>3</sup>		
	WEL	8 hours	100 ppm		
	WEL	Short-term	125 ppm		
cyclohexanone (CAS: 108-94-1)	WEL	8 hours	41 mg/m <sup>3</sup>	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
	WEL	15 minutes	82 mg/m <sup>3</sup>	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	8 hours	10 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	



**2K EPOXY PRIMER**

Creation date 11. April 2018  
Revision date 11. June 2018 Version 2.0

**United Kingdom of Great Britain and Northern Ireland**

Substance name (component)	Type	Time of exposure	Value	Note	Source
cyclohexanone (CAS: 108-94-1)	WEL	15 minutes	20 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	WEL	8 hours	274 mg/m <sup>3</sup>	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
	WEL	15 minutes	548 mg/m <sup>3</sup>	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	8 hours	50 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	15 minutes	100 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	

**8.2. Exposure controls**

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

**Eye/face protection**

Tightly sealed goggles.

**Skin protection**

Hand protection: Protective gloves resistant to the product. Material of gloves: Butyl rubber. Recommended thickness of the material: ≥ 0.4 mm. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear.

**Respiratory protection**

Under regular circumstances it is not necessary. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter AX.

**Thermal hazard**

Not available.

**Environmental exposure controls**

Observe usual measures for protection of the environment, see Section 6.2.

**2K EPOXY PRIMER**

Creation date	11. April 2018	Version	2.0
Revision date	11. June 2018		

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	aerosol
Physical state	liquid at 20°C
color	grey
Odour	characteristic
Odour threshold	data not available
pH	data not available
Melting point/freezing point	data not available
Initial boiling point and boiling range	data not available
Flash point	240 °C
Evaporation rate	data not available
Flammability (solid, gas)	Extremely flammable aerosol.
Upper/lower flammability or explosive limits	
flammability limits	data not available
explosive limits	
bottom	3.3 %
upper	26.2 %
Vapour pressure	4000 hPa at 20 °C
Vapour density	data not available
Relative density	data not available
Solubility(ies)	
solubility in water	almost insoluble
solubility in fats	data not available
Partition coefficient: n-octanol/water	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
Viscosity	data not available
Explosive properties	data not available
Oxidising properties	data not available
data not available	

**9.2. Other information**

Density	0.98 g/cm <sup>3</sup> at 20 °C
ignition temperature	data not available
content of organic solvents (VOC)	63.7 %
solid content (dry matter)	30.5 % volume
VOC limit value	cat. B (e) : 840 g/l
Max. VOC content in the product in its ready to use condition	624.1 g/l
Product is not selfigniting.	

**SECTION 10: Stability and reactivity****10.1. Reactivity**

not available

**10.2. Chemical stability**

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

**10.3. Possibility of hazardous reactions**

Unknown.

**2K EPOXY PRIMER**

Creation date 11. April 2018  
Revision date 11. June 2018 Version 2.0

**10.4. Conditions to avoid**

not available

**10.5. Incompatible materials**

not available

**10.6. Hazardous decomposition products**

Unknown.

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

No toxicological data is available for the mixture.

**Acute toxicity**

Based on available data the classification criteria are not met.

2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD <sub>50</sub>	8530 mg/kg		Rat	
Dermal	LD <sub>50</sub>	>5000 mg/kg		Rabbit	
Inhalation	LD <sub>50</sub>	>10000 mg/m <sup>3</sup>	4 hour	Rat	

acetone

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD <sub>50</sub>	5800 mg/kg		Rat	
Dermal	LD <sub>50</sub>	20000 mg/kg		Rabbit	

hydrocarbons, C9, aromatics

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD <sub>50</sub>	3592 mg/kg		Rat	
Dermal	LD <sub>50</sub>	3160 mg/kg		Rabbit	

trizinc bis(orthophosphate)

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD <sub>50</sub>	>5000 mg/kg		Rat	

xylene

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD <sub>50</sub>	3523 mg/kg		Rat	
Dermal	LD <sub>50</sub>	2000 mg/kg		Rabbit	
Inhalation	LC <sub>50</sub>	29000 mg/m <sup>3</sup>	4 hour	Rat	

xylene (mixture of isomers)

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD <sub>50</sub>	3523 mg/kg		Rat	
Dermal	LD <sub>50</sub>	2000 mg/kg		Rabbit	
Inhalation	LC <sub>50</sub>	29000 mg/m <sup>3</sup>	4 hour	Rat	

**Skin corrosion/irritation**

Causes skin irritation.

**2K EPOXY PRIMER**

Creation date	11. April 2018	Version	2.0
Revision date	11. June 2018		

**Serious eye damage/irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**Germ cell mutagenicity**

Based on available data the classification criteria are not met.

**Carcinogenicity**

Based on available data the classification criteria are not met.

**Reproductive toxicity**

Based on available data the classification criteria are not met.

**Toxicity for specific target organ - single exposure**

Based on available data the classification criteria are not met.

**Toxicity for specific target organ - repeated exposure**

Based on available data the classification criteria are not met.

**Aspiration hazard**

Based on available data the classification criteria are not met.

**SECTION 12: Ecological information**

**12.1. Toxicity**

**Acute toxicity**

Harmful to aquatic life with long lasting effects.

2-methoxy-1-methylethyl acetate

Parameter	Value	Time of exposure	Species	Environment
EC <sub>50</sub>	>500 mg/l	48 hour	Daphnia (Daphnia magna)	
LC <sub>50</sub>	100-180 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	

hydrocarbons, C9, aromatics

Parameter	Value	Time of exposure	Species	Environment
EC <sub>50</sub>	3.2 mg/l	48 hour	Daphnia (Daphnia magna)	
EC <sub>50</sub>	2.75 mg/l	72 hour	Algae (Pseudokirchneriella subcapitata)	
EC <sub>50</sub>	9.2 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	

xylene

Parameter	Value	Time of exposure	Species	Environment
EC <sub>50</sub>	7.4 mg/l	48 hour	Daphnia (Daphnia magna)	

**2K EPOXY PRIMER**

Creation date	11. April 2018	Version	2.0
Revision date	11. June 2018		

xylene

Parameter	Value	Time of exposure	Species	Environment
LC <sub>50</sub>	13.5 mg/l	96 hour	Fishes	

xylene (mixture of isomers)

Parameter	Value	Time of exposure	Species	Environment
EC <sub>50</sub>	7.6 mg/l	48 hour	Daphnia (Daphnia magna)	
LC <sub>50</sub>	13.5 mg/l	96 hour	Fishes	

**12.2. Persistence and degradability**

Not available.

**12.3. Bioaccumulative potential**

Not available.

**12.4. Mobility in soil**

Not available.

**12.5. Results of PBT and vPvB assessment**

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

**12.6. Other adverse effects**

Ecotoxicological effects: Remark: Toxic for fish

Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water. Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste.

**Legislation of waste**

Council Directive 75/442/EEC on waste, as amended. Decree No. 383/2001 Coll., on details regarding waste handling as amended. Decree No. 93/2016 Coll., (waste catalogue) as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

**Waste type code**

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

**Packaging waste type code**

15 01 11 metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

**SECTION 14: Transport information**

**14.1. UN number**

UN 1950

**14.2. UN proper shipping name**

AEROSOLS

**14.3. Transport hazard class(es)**

2 Gases

**14.4. Packing group**

not available

**2K EPOXY PRIMER**

Creation date	11. April 2018	Version	2.0
Revision date	11. June 2018		

**14.5. Environmental hazards**

not available

**14.6. Special precautions for user**

Reference in the Sections 4 to 8.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not available

**Additional information**

Stowage Code: SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. Segregation Code: SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

Hazard identification No.		(Kemler Code)
UN number		<b>1950</b>
Classification code	5F	
Safety signs	2.1	

**Road transport ADR**

Limited amount	1L
Extracted amounts	E0
Transport category	2
Tunnel restriction code	(D)

**Marine transport - IMDG**

EmS (emergency plan)	F-D, S-U
Marine pollution	Yes

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended. The Act No. 350/2011 Coll., on Chemical Substances and Chemical Preparations as amended (the Chemical Act). The Act No. 350/2011 Coll., on Chemical Substances and Chemical Preparations as amended. The Act No. 258/2000 Coll., on Protection of Public Health as amended. Decree No. 361/2007 Coll., determining conditions of occupational health protection as amended. Decree No. 415/2012 Coll., on the permissible level of pollution and its determination and implementation of certain other provisions of the Air Protection Act as amended. The Act No. 185/2001 Coll., on Waste and the Amendment of Some Other Acts as amended. The Act No. 201/2012 Coll., on the Protection of Atmosphere – Clean Air Act as amended. Decree No. 432/2003 Coll., laying down conditions for assigning categories to individual jobs, limit values of indices from biological exposure tests, conditions for the sampling of biological materials for biological exposure and the particulars of the reports on work with asbestos and biological agents as amended. REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents, as amended.

**15.2. Chemical safety assessment**

not available

**2K EPOXY PRIMER**

Creation date	11. April 2018	Version	2.0
Revision date	11. June 2018		

**SECTION 16: Other information****A list of standard risk phrases used in the safety data sheet**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H312+H332	Harmful in contact with skin or if inhaled.

**Guidelines for safe handling used in the safety data sheet**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P280	Wear protective gloves.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with national regulations.

**A list of additional standard phrases used in the safety data sheet**

EUH 066	Repeated exposure may cause skin dryness or cracking.
---------	-------------------------------------------------------

**Other important information about human health protection**

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

**Key to abbreviations and acronyms used in the safety data sheet**

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
DNEL	Derived no-effect level
EC	Identification code for each substance listed in EINECS
EC <sub>50</sub>	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
IC <sub>50</sub>	Concentration causing 50% blockade

**2K EPOXY PRIMER**

Creation date	11. April 2018	Version	2.0
Revision date	11. June 2018		

ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC <sub>50</sub>	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD <sub>50</sub>	Lethal dose of a substance in which it can be expected death of 50% of the population
LOAEC	Lowest observed adverse effect concentration
LOAEL	Lowest observed adverse effect level
log K <sub>ow</sub>	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution From Ships
NOAEC	No observed adverse effect concentration
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
NOEL	No observed effect level
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted no-effect concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Acute Tox.	Acute toxicity
Aerosol	Flammable aerosol
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Press. Gas	Gases under pressure
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

**Training guidelines**

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

**Recommended restrictions of use**

not available

**Information about data sources used to compile the Safety Data Sheet**

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. The Act No. 350/2011 Coll., on Chemical Substances and Chemical Preparations as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

**The changes (which information has been added, deleted or modified)**



**2K EPOXY PRIMER**

Creation date	11. April 2018		
Revision date	11. June 2018	Version	2.0

2, 15, 16.

**Statement**

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.