

according to Regulation (EC) No 1907/2006 (REACH) as amended

### **AUTOCLEAN**

Creation date 25th November 2024

Revision date Version 4.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

.1. Product identifier
Substance / mixture
Number
AUTOCLEAN
mixture
R 34707

UFI RS33-9358-H00X-3Q3K

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Mixture's intended use

Cleaning agent. Degreasing agent. For professional use only.

Main intended use

PC-CLN-2 All-purpose (or multi-purpose) non-abrasive cleaners including degreasing

agents (unless otherwise specified in other subcategories of cleaning products)

#### Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

### 1.3. Details of the supplier of the safety data sheet

**Supplier** 

Name or trade name RETECH, s.r.o.

Address Vackova 1541/4, Praha 5 - Stodůlky, 155 00

Czech Republic

Identification number (CRN)25018205VAT Reg NoCZ25018205Phone+420327596428E-mailinfo@retech.czWeb addresswww.retech.com

Competent person responsible for the safety data sheet

Name RETECH, s.r.o. E-mail info@retech.cz

### 1.4. Emergency telephone number

European emergency number: 112

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

### Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Aerosol 1, H222, H229 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 STOT RE 2, H373 Aquatic Chronic 2, H411

#### Most serious adverse physico-chemical effects

Extremely flammable aerosol. Pressurised container: May burst if heated.

# Most serious adverse effects on human health and the environment

Causes skin irritation. May cause drowsiness or dizziness. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **AUTOCLEAN**

Creation date 25th November 2024

Revision date Version 4.0

#### 2.2. Label elements

### **Hazard pictogram**









#### Signal word

Danger

### **Hazardous substances**

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics xylene (contains ethylbenzene - CAS 100-41-4)

#### **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.
P280 Wear protective gloves/eye protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P331 Do NOT induce vomiting.
P403 Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of container to in accordance with national regulations.

#### **Supplemental information**

>=30 % aromatic hydrocarbons, >=30 % aliphatic hydrocarbons

#### 2.3. Other hazards

Buildup of explosive mixtures possible without sufficient ventilation.

Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Does not contain any PMT or vPvM components.



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **AUTOCLEAN**

Creation date 25th November 2024

Revision date Version 4.0

### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Chemical characterization

Mixture.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Registration number: 01-2119473851-33	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	25-<50	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 EUH066	
EC: 905-588-0 Registration number: 01-2119488216-32/- 6136-34*	xylene (contains ethylbenzene - CAS 100 -41-4)	25-<50	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412	
CAS: 74-98-6 EC: 200-827-9 Registration number: 01-2119486944-21	propane	2.5-<10	Flam. Gas 1A, H220 Press. Gas (compressed gas), H280	
CAS: 106-97-8 EC: 203-448-7 Registration number: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8))	1-<2.5	Flam. Gas 1A, H220 Press. Gas (compressed gas), H280	
CAS: 75-28-5 EC: 200-857-2 Registration number: 01-2119485395-27	isobutane	0.1-<1	Flam. Gas 1A, H220 Press. Gas (compressed gas), H280	

Full text of all classifications and hazard statements is given in the section 16.

#### **Additional information**

\*ES: 905-588-0 xylene (contains ethylbenzene - CAS 100-41-4) => Contains: 98-82-8 cumene (<0,1 %); 108-88-3 toluene ( $\leq 2$  %)

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

Symptoms of poisoning may manifest after many hours, medical supervision is necessary for 48 hours after the accident.

### If inhaled

Terminate the exposure immediately; move the affected person to fresh air. If the affected person is not breathing, breathing is irregular or in respiratory arrest provide artificial respiration or oxygen. Keep the affected person warm and at rest. In the event of issues, find medical advice. In case of unconsciousness place patient stably in side position for transportation.

### If on skin

Immediately wash with water and soap and rinse thoroughly.

### If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. In the event of issues, find medical advice.



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **AUTOCLEAN**

Creation date 25th November 2024

Revision date Version 4.0

#### If swallowed

DO NOT INDUCE VOMITING! Provide medical treatment.

### 4.2. Most important symptoms and effects, both acute and delayed

#### If inhaled

May cause respiratory irritation. May cause drowsiness or dizziness.

#### If on skin

Causes skin irritation.

#### If in eyes

Causes serious eye irritation.

#### If swallowed

not available

### 4.3. Indication of any immediate medical attention and special treatment needed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Provide medical treatment considering the frequent need of further observation for at least 24 hours.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

### Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water mist.

### Unsuitable extinguishing media

Water - full jet.

#### 5.2. Special hazards arising from the substance or mixture

not available

### 5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing.

### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Use personal protective equipment for work. Keep unprotected persons away.

#### 6.2. Environmental precautions

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

#### 6.3. Methods and material for containment and cleaning up

Dispose of the collected material according to the instructions in the section 13. Provide sufficient ventilation. Do not flush with water or aqueous cleansing agents.

#### 6.4. Reference to other sections

See the Section 7, 8 and 13.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Do not spray on an open flame or other ignition source. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. No smoking. Take precautionary measures against static discharge. Pressurised container: May burst if heated. Keep away from sources of heating, ignition and direct sunlight. Do not pierce or burn, even after use.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Protect from sunlight. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C.

Content	Packaging type	Material of package
500 ml	aerosol can	



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **AUTOCLEAN**

Creation date 25th November 2024

Revision date Version 4.0

Storage class

2B - Aerosols

### 7.3. Specific end use(s)

not available

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

The mixture contains no substances for which occupational exposure limits are set.

### **DNEL**

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics				
Workers / consumers	Route of exposure	Value	Effect	
Consumers	Oral	699 mg/kg bw/day	Chronic effects systemic	
Consumers	Dermal	699 mg/kg bw/day	Chronic effects systemic	
Workers	Dermal	773 mg/kg bw/day	Chronic effects systemic	
Consumers	Inhalation	608 mg/m <sup>3</sup>	Chronic effects systemic	
Workers	Inhalation	2035 mg/m <sup>3</sup>	Chronic effects systemic	

xylene (contains ethylbenzene - CAS 100-41-4)					
Workers / consumers	Route of exposure	Value	Effect		
Consumers	Oral	1.6 mg/kg bw/day	Chronic effects systemic		
Consumers	Dermal	108 mg/kg bw/day	Chronic effects systemic		
Workers	Dermal	180 mg/kg bw/day	Chronic effects systemic		
Workers	Inhalation	289 mg/m <sup>3</sup>	Acute effects systemic		
Consumers	Inhalation	14.8 mg/m <sup>3</sup>	Chronic effects systemic		
Workers	Inhalation	77 mg/m <sup>3</sup>	Chronic effects systemic		
Consumers	Inhalation	174 mg/m <sup>3</sup>	Acute effects systemic		
Workers	Inhalation	289 mg/m <sup>3</sup>	Acute effects local		
Consumers	Inhalation	174 mg/m³	Chronic effects local		
Workers	Inhalation	221 mg/m <sup>3</sup>	Chronic effects local		

### **PNEC**

xylene (contains ethylbenzene - CAS 100-41-4)				
Route of exposure	Value			
Freshwater environment	0.327 mg/l			
Marine water	0.327 mg/l			
Freshwater sediment	12.46 mg/kg of dry substance of sediment			
Soil (agricultural)	2.31 mg/kg of dry substance of soil			
Microorganisms in sewage treatment	6.58 mg/l			
Sea sediments	12.46 mg/kg of dry substance of sediment			



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **AUTOCLEAN**

Creation date 25th November 2024

Revision date Version 4.0

### 8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. Do not store together with food, drink and animal feed. Remove contaminated clothes immediately. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

### Eye/face protection

Tightly sealed goggles.

### Skin protection

Hand protection: Protective gloves resistant to the product. EN ISO 374-1. Material of gloves: Nitrile rubber, NBR. Recommended thickness of the material:  $\geq 0.5$  mm. Penetration time of glove material:  $\geq 240$  min. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer.

Other protection: protective workwear and footwear. In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

### **Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Filter A2/P2.

#### Thermal hazard

Not available.

### **Environmental exposure controls**

Observe usual measures for protection of the environment, see Section 6.2.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state gas
Colour colourless
Odour characteristic
Melting point/freezing point data not available

Boiling point or initial boiling point and boiling range  $\,$  -44.5  $^{\circ}\text{C}$ 

Flammability Extremely flammable aerosol.

Lower and upper explosion limit

bottom 0.7 % butane (containing < 0,1 % butadiene (203- 1.5 %

450-8)) (CAS: 106-97-8)

upper 10.9 % Flash point -97 °C

Auto-ignition temperature data not available

butane (containing < 0,1 % butadiene (203-450-8) 365 °C

) (CAS: 106-97-8)

Decomposition temperature data not available pH non-polar/aprotic Kinematic viscosity data not available Solubility in water almost insoluble Solubility in fats data not available Partition coefficient n-octanol/water (log value) data not available Vapour pressure 8300 hPa at 20 °C

Density and/or relative density

Density 0.75 g/cm³ at 20 °C Relative vapour density data not available Particle characteristics data not available

Form spray

data not available

### 9.2. Other information

Evaporation rate data not available



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **AUTOCLEAN**

Creation date 25th November 2024

Revision date Version 4.0

Ignition temperature >200 °C

Explosive properties The product does not have explosive properties but

746.0 g/l

can be explosive when blended with air.

Content of organic solvents (VOC)

Max. VOC content in the product in its ready to use

condition

Product is not selfigniting.

### **SECTION 10: Stability and reactivity**

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

not available

10.5. Incompatible materials

not available

10.6. Hazardous decomposition products

Unknown.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological data is available for the mixture.

### **Acute toxicity**

Based on the available data, the criteria for classification of the mixture are not met.

AUTOCLEAN					
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Dermal	ATE	2420 mg/kg			
Inhalation	ATE	24.2 mg/l			

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics					
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD50	>5000 mg/kg		Rat	
Dermal	LD <sub>50</sub>	>3100 mg/kg		Rat	
Inhalation	LC50	>23.3 mg/l	4 hours	Rat	
Oral	LD <sub>50</sub>	>8 ml/kg		Rat	

xylene (contains ethylbenzene - CAS 100-41-4)						
Route of exposure	Parameter	Value	Exposure time	Species	Sex	
Oral	LD50	3523 mg/kg		Rat		
Dermal	LD50	12126 mg/kg		Rabbit		
Inhalation	LC <sub>50</sub>	29000 mg/l	4 hours	Rat		

### Skin corrosion/irritation

Causes skin irritation. Data for the components of the mixture are not available.



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **AUTOCLEAN**

Creation date 25th November 2024

Revision date Version 4.0

### Serious eye damage/irritation

Causes serious eye irritation. Data for the components of the mixture are not available.

### Respiratory or skin sensitisation

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

#### Germ cell mutagenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

#### Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

#### Reproductive toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

### Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness. May cause respiratory irritation. Data for the components of the mixture are not available.

#### Toxicity for specific target organ - repeated exposure

May cause damage to organs through prolonged or repeated exposure. Data for the components of the mixture are not available.

### **Aspiration hazard**

May be fatal if swallowed and enters airways. Data for the components of the mixture are not available.

### 11.2. Information on other hazards

#### **Endocrine disrupting properties**

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

#### Other information

not available

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Toxic to aquatic life with long lasting effects.

### **Acute toxicity**

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics					
Parameter	Value	Exposure time	Species	Environment	
NOELR	10 mg/l	72 hours	Algae (Selenastrum capricornutum)		
LL50	>13.4 mg/l	72 hours	Fish (Oncorhynchus mykiss)		
NOEC	0.17 mg/l	21 days	Invertebrates (Daphnia magna)		
LOEC	0.32 mg/l	21 days	Invertebrates (Daphnia magna)		



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **AUTOCLEAN**

Creation date 25th November 2024

Revision date Version 4.0

Hydrocarbons, C7	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics					
Parameter	Value	Exposure time	Species	Environment		
EC50	3 mg/l	48 hours	Invertebrates (Daphnia magna)			
EL50	10-30 mg/l	72 hours	Algae (Selenastrum capricornutum)			

xylene (contains ethylbenzene - CAS 100-41-4)					
Parameter	Value	Exposure time	Species	Environment	
EC50	3.2-9.5 mg/l	48 hours	Daphnia (Daphnia magna)		
LC50	8.9-16.4 mg/l	96 hours	Fish (Pimephales promelas)		

### **Chronic toxicity**

xylene (contains ethylbenzene - CAS 100-41-4)					
Parameter	Value	Exposure time	Species	Environment	
NOEC	1.3 mg/l		Fish		
NOEC	0.96 mg/l	7 days	Daphnia (Daphnia magna)		
NOEC	0.44 mg/l	72 hours	Algae		
NOEC	16 mg/l	28 days	Bacteria		

### 12.2. Persistence and degradability

The product is not easily biodegradable.

### 12.3. Bioaccumulative potential

Not available.

### 12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

### 12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

### 12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

### 12.7. Other adverse effects

Ecotoxical effects: Remark: Toxic for fish

Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water. Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms.

### **SECTION 13: Disposal considerations**



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **AUTOCLEAN**

Creation date 25th November 2024

Revision date Version 4.0

#### 13.1. Waste treatment methods

Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. HP3 "Flammable".

 ${\sf HP}$  4 'Irritant — skin irritation and eye damage'.

HP 5 'Specific Target Organ Toxicity (STOT)/Aspiration Toxicity'.

HP 6 "Acute Toxicity".

HP 14 'Ecotoxic'.

#### Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

#### Waste type code

16 03 05\* organic wastes containing hazardous substances

#### Packaging waste type code

15 01 11\* metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers

(\*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

### **SECTION 14: Transport information**

#### 14.1. UN number or ID number

UN 1950

#### 14.2. UN proper shipping name

**AEROSOLS** 

### 14.3. Transport hazard class(es)

2 Gases

### 14.4. Packing group

not relevant

### 14.5. Environmental hazards

Yes

### 14.6. Special precautions for user

Reference in the Sections 4 to 8.

### 14.7. Maritime transport in bulk according to IMO instruments

not relevant

#### **Additional information**

Stowage Code: SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code: SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

Hazard identification No.

**UN** number

Classification code

Safety signs



5F

2.1+hazardous for the environment







according to Regulation (EC) No 1907/2006 (REACH) as amended

### **AUTOCLEAN**

Creation date 25th November 2024

Revision date Version 4.0

### Road transport - ADR

Limited quantities 1 L Excepted quantities E0 Transport category 2 Tunnel restriction code (D)

Railway transport - RID

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents, as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

#### More information

Directive 2012/18/EU of the European parliament and of the Council - ANNEX I - Hazard categories: P3a FLAMMABLE AEROSOLS. E2 Hazardous to the Aquatic Environment in Category Chronic 2.

Qualifying quantity (tonnes) of dangerous substances for the application - of lower-tier requirements: 150

Qualifying quantity (tonnes) of dangerous substances for the application of - upper-tier requirements: 500 (net).

Repeated exposure may cause skin dryness or cracking.

#### **SECTION 16: Other information**

**EUH066** 

#### A list of standard risk phrases used in the safety data sheet

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated

exposure.

Toxic to aquatic life with long lasting effects. H411 Harmful to aquatic life with long lasting effects. H412

### Guidelines for safe handling used in the safety data sheet

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **AUTOCLEAN**

Creation date 25th November 2024

Revision date Version 4.0

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.
P280 Wear protective gloves/eye protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P331 Do NOT induce vomiting.
P403 Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of container to in accordance with national regulations.

#### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

### Key to abbreviations and acronyms used in the safety data sheet

Acute Tox. Acute toxicity

ADR European agreement concerning the international carriage of dangerous goods

by road

Aerosol Aerosol

Aquatic Chronic Hazardous to the aquatic environment (chronic)

Asp. Tox. Aspiration hazard
BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substance and mixtures

EC Identification code for each substance listed in EINECS

EC50 Concentration of a substance when it is affected 50 % of the population EINECS European Inventory of Existing Commercial Chemical Substances

EL<sub>50</sub> Effective Loading for 50 % of the tested organisms

EmS Emergency plan EU European Union

EuPCS European Product Categorisation System

Eye Irrit. Eye irritation
Flam. Gas Flammable gas
Flam. Liq. Flammable liquid

IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying

**Dangerous Chemicals** 

ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous Goods
IMO International Maritime Organization

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

LC50 Lethal concentration of a substance in which it can be expected death of 50%

of the population

LD50 Lethal dose of a substance in which it can be expected death of 50% of the

population

LL<sub>50</sub> Lethal Loading for 50 % of tested organisms

log Kow Octanol-water partition coefficient NOEC No observed effect concentration

NOEL No observed effect level

NOELR No Observed Effect Loading Rate
OEL Occupational Exposure Limits



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **AUTOCLEAN**

Creation date 25th November 2024

Revision date Version 4.0

PBT Persistent, bioaccumulative and toxic

PMT Persistent, mobile and toxic

ppm Parts per million
Press. Gas Gases under pressure

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

Skin Irrit. Skin irritation

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

UN Four-figure identification number of the substance or article taken from the UN

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials

VOC Volatile organic compounds

vPvB Very persistent and very bioaccumulative

vPvM Very persistent and very mobile

### **Training guidelines**

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

#### Recommended restrictions of use

not available

### Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

### The changes (which information has been added, deleted or modified)

The version 4.0 replaces the SDS version from Tuesday, 13 December 2022. Changes were made in sections 1, 2, 3, 8, 11, 12, 13, 15 and 16.

#### **Statement**

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.