

BLACK MATT SPRAY

Creation date 09. July 2019
Revision date Version 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture BLACK MATT SPRAY
mixture
Number 1 35156
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use Paint.
Mixture uses advised against For professional use only.
- 1.3. Details of the supplier of the safety data sheet**
Supplier
Name or trade name RETECH, s.r.o.
Address Vackova 1541/4, Praha 5 - Stodůlky, 155 00
Czech Republic
Identification number (CRN) 25018205
Phone +420327596428
E-mail info@retech.cz
Web address www.retech.com
- Competent person responsible for the safety data sheet**
Name RETECH, s.r.o.
E-mail info@retech.cz
- 1.4. Emergency telephone number**
RETECH, Suchdol 212, 285 02 Suchdol u Kutné Hory, Czech Republic; Telephone number: +420 327 596 128 (7.30-16.00 hour)
Poisoning information centre, Na Bojišti 1, Praha, Czech Republic, Tel.: non-stop +420 224 919 293 or +420 224 915 402, Information on health risks only - acute poisoning of humans and animals.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification of the mixture in accordance with Regulation (EC) No 1272/2008**

The mixture is classified as dangerous.

Aerosol 1, H222, H229
Eye Irrit. 2, H319
STOT SE 3, H336

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Extremely flammable aerosol. Pressurised container: May burst if heated.

Most serious adverse effects on human health and the environment

Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements**Hazard pictogram****Signal word**

Danger

Hazardous substances

acetone
n-butyl acetate

BLACK MATT SPRAY

 Creation date 09. July 2019
 Revision date Version 2.0

Hazard statements

 H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P260 Do not breathe spray.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container to in accordance with national regulations.

Supplemental information

 EUH 066 Repeated exposure may cause skin dryness or cracking.
 Density 0.78 g/cm³
 Dry matter 26.1 % volume
 VOC limit value cat. B (e) : 840 g/l
 Max. VOC content in the product in its ready to use condition 645.2 g/l

2.3. Other hazards

Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Buildup of explosive mixtures possible without sufficient ventilation.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note.
Index: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 Registration number: 01-2119471330-49	acetone	25-<50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH 066	1
Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9 Registration number: 01-2119486944-21	propane	12,5- <20,0	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	
Index: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 Registration number: 01-2119485493-29	n-butyl acetate	12,5- <20,0	Flam. Liq. 3, H226 STOT SE 3, H336 EUH 066	1

BLACK MATT SPRAY

Creation date 09. July 2019

Revision date Version 2.0

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note.
Index: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7 Registration number: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8))	10,0- <12,5	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	1
CAS: 9004-70-0 EC: 618-392-2	Nitrocellulose (<12,6 % N)	5-<10	Flam. Sol. 1, H228	
Index: 601-004-00-0 CAS: 75-28-5 EC: 200-857-2 Registration number: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8))	2,5-<5,0	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	
CAS: 64742-94-5 EC: 265-198-5 Registration number: 01-2119510128-50	Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified	<2,5	Asp. Tox. 1, H304	
Index: 603-002-00-5 CAS: 64-17-5 EC: 200-578-6 Registration number: 01-2119457610-43	ethanol	<2,5	Flam. Liq. 2, H225 Specific concentration limit: Eye Irrit. 2, H319: C ≥ 50 %	1
EC: 918-668-5 Registration number: 01-2119455851-35	hydrocarbons	≤0,5	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335, H336 Aquatic Chronic 2, H411	

Notes

1 Substance for which exposure limits of Community for working environment exist.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. In the event of issues, find medical advice.

If on skin

Generally the product does not irritate the skin.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. In the event of issues, find medical advice.

If swallowed

Rinse out the mouth with clean water. Provide medical treatment.

BLACK MATT SPRAY

Creation date	09. July 2019	Version	2.0
Revision date			

4.2. Most important symptoms and effects, both acute and delayed**If inhaled**

May cause drowsiness or dizziness.

If on skin

not available

If in eyes

Causes serious eye irritation.

If swallowed

not available

4.3. Indication of any immediate medical attention and special treatment needed

not available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide, powder, water spray jet. Fight larger fires with water spray or alcohol resistant foam.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

not available

5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide sufficient ventilation. Use personal protective equipment for work. Keep unprotected persons away.

6.2. Environmental precautions

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

6.3. Methods and material for containment and cleaning up

Provide sufficient ventilation. Dispose of the collected material according to the instructions in the section 13. Do not flush with water or aqueous cleansing agents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Do not spray on an open flame or other ignition source. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. No smoking. Take precautionary measures against static discharge. Pressurised container: May burst if heated. Keep away from sources of heating, ignition and direct sunlight. Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Storage class

2B - Aerosols

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

The mixture contains substances for which occupational exposure limits are set.

BLACK MATT SPRAY

Creation date

09. July 2019

Revision date

Version

2.0

European Union

Substance name (component)	Type	Time of exposure	Value	Note	Source
acetone (CAS: 67-64-1)	OEL	8 hours	1210 mg/m ³		EU limits
	OEL	8 hours	500 ppm		

United Kingdom of Great Britain and Northern Ireland

Substance name (component)	Type	Time of exposure	Value	Note	Source
acetone (CAS: 67-64-1)	WEL	8 hours	1210 mg/m ³		GBR
	WEL	15 minutes	3620 mg/m ³		
	WEL	8 hours	500 ppm		
	WEL	15 minutes	1500 ppm		
n-butyl acetate (CAS: 123-86-4)	WEL	8 hours	724 mg/m ³		GBR
	WEL	15 minutes	966 mg/m ³		
	WEL	8 hours	150 ppm		
	WEL	15 minutes	200 ppm		
butane (containing < 0,1 % butadiene (203-450-8)) (CAS: 106-97-8)	WEL	8 hours	600 ppm		GBR
	WEL	8 hours	1450 mg/m ³		
	WEL	15 minutes	1810 mg/m ³		
	WEL	15 minutes	750 ppm		
ethanol (CAS: 64-17-5)	WEL	8 hours	1920 mg/m ³		Gestis
	WEL	8 hours	1000 ppm		

8.2. Exposure controls

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

Eye/face protection

Tightly sealed goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. Material of gloves: Butyl rubber. Penetration time of glove material: The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. Other protection: protective workwear.

BLACK MATT SPRAY

Creation date	09. July 2019	Version	2.0
Revision date			

Respiratory protection

In case of inadequate ventilation wear respiratory protection. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter AX/P2.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	aerosol
Physical state	liquid at 20°C
color	black
Odour	characteristic
Odour threshold	data not available
pH	data not available
Melting point/freezing point	data not available
Initial boiling point and boiling range	data not available
Flash point	data not available
Evaporation rate	data not available
Flammability (solid, gas)	Extremely flammable aerosol.
Upper/lower flammability or explosive limits	
flammability limits	data not available
explosive limits	
bottom	1.2 %
upper	13.0 %
Vapour pressure	8300 hPa at 20 °C
Vapour density	data not available
Relative density	data not available
Solubility(ies)	
solubility in water	almost insoluble
solubility in fats	data not available
Partition coefficient: n-octanol/water	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
Viscosity	data not available
Explosive properties	data not available
Oxidising properties	data not available
data not available	

9.2. Other information

Density	0.78 g/cm ³ at 20 °C
ignition temperature	180 °C
solid content (dry matter)	26.1 % volume
VOC limit value	cat. B (e) : 840 g/l
Max. VOC content in the product in its ready to use condition	645.2 g/l

SECTION 10: Stability and reactivity**10.1. Reactivity**

not available

10.2. Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

BLACK MATT SPRAY

Creation date 09. July 2019
Revision date Version 2.0

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

not available

10.5. Incompatible materials

not available

10.6. Hazardous decomposition products

Unknown.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

acetone

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	5800 mg/kg		Rat	
Dermal	LD ₅₀	20000 mg/kg		Rabbit	

butane (containing < 0,1 % butadiene (203-450-8))

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
	LC ₅₀	658000 mg/m ³	4 hour	Rat	

n-butyl acetate

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	10770 mg/kg		Rat	
Dermal	LD ₅₀	>17600 mg/kg		Rabbit	
Inhalation	LC ₅₀	>21 mg/m ³	4 hour	Rat	

Skin corrosion/irritation

Based on available data the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

BLACK MATT SPRAY

Creation date

09. July 2019

Revision date

Version

2.0

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

Based on available data the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity****Acute toxicity**

Data for the mixture are not available.

n-butyl acetate

Parameter	Value	Time of exposure	Species	Environment
EC ₅₀	44 mg/l	48 hour	Daphnia (Daphnia magna)	
EC ₅₀	320 mg/l	96 hour	Algae	
LC ₅₀	205 mg/l	24 hour	Daphnia (Daphnia magna)	
LC ₅₀	18 mg/l	96 hour	Fishes (Pimephales promelas)	

12.2. Persistence and degradability

Not available.

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Other adverse effects

Additional ecological information:

General notes: Water hazard class 1 (german Regulation, self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

Packaging waste type code

15 01 11 metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

BLACK MATT SPRAY

Creation date 09. July 2019
Revision date Version 2.0

SECTION 14: Transport information

- 14.1. UN number**
UN 1950
- 14.2. UN proper shipping name**
AEROSOLS
- 14.3. Transport hazard class(es)**
2 Gases
- 14.4. Packing group**
not available
- 14.5. Environmental hazards**
No
- 14.6. Special precautions for user**
Reference in the Sections 4 to 8.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**
not available

Additional information

Hazard identification No.  (Kemler Code)
UN number 1950
Classification code 5F
Safety signs 2.1

**Road transport - ADR**

Limited quantities 1L
Excepted quantities E0
Transport category 2
Tunnel restriction code (D)

Marine transport - IMDG

EmS (emergency plan) F-D, S-U
Marine Pollutant No

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

15.2. Chemical safety assessment

not available

SECTION 16: Other information**A list of standard risk phrases used in the safety data sheet**

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.

BLACK MATT SPRAY

Creation date	09. July 2019	Version	2.0
Revision date			

H226	Flammable liquid and vapour.
H228	Flammable solid.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to in accordance with national regulations.

A list of additional standard phrases used in the safety data sheet

EUH 066	Repeated exposure may cause skin dryness or cracking.
---------	---

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
DNEL	Derived no-effect level
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
IC ₅₀	Concentration causing 50% blockade
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LOAEC	Lowest observed adverse effect concentration
LOAEL	Lowest observed adverse effect level

BLACK MATT SPRAY

Creation date	09. July 2019	Version	2.0
Revision date			

log Kow	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution From Ships
NOAEC	No observed adverse effect concentration
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
NOEL	No observed effect level
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted no-effect concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Aerosol	Aerosol
Aquatic Chronic	Hazardous to the aquatic environment
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Flam. Sol.	Flammable solid
Press. Gas	Gases under pressure
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

2, 3, 8, 11, 12, 15, 16

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.