

BODY PAINT

Creation date 11. March 2019
Revision date Version 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture
Number
BODY PAINT
mixture
YELLOW GREY - 1 35462; CEMENT GREY - 1 35463;
TRAFFIC GREY - 1 35464
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
Mixture uses advised against
1K acrylic lacquer.
For professional use only.
- 1.3. Details of the supplier of the safety data sheet**
Supplier
Name or trade name
Address
Identification number (CRN)
Phone
E-mail
Web address
RETECH, s.r.o.
Vackova 1541/4, Praha 5 - Stodůlky, 155 00
Czech Republic
25018205
+420327596428
info@retech.cz
www.retech.com
- Competent person responsible for the safety data sheet**
Name
E-mail
RETECH, s.r.o.
info@retech.cz
- 1.4. Emergency telephone number**
RETECH, Suchdol 212, 285 02 Suchdol u Kutné Hory, Czech Republic; Telephone number: +420 327 596 128 (7.30-16.00 hour)
Poisoning information centre, Na Bojišti 1, Praha, Czech Republic, Tel.: non-stop +420 224 919 293 or +420 224 915 402, Information on health risks only - acute poisoning of humans and animals.

SECTION 2: Hazards identification

- 2.1. Substance or mixture classification**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Aerosol 1, H222, H229
Eye Irrit. 2, H319
STOT SE 3, H336

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Extremely flammable aerosol. Pressurised container: May burst if heated.

Most serious adverse effects on human health and the environment

Causes serious eye irritation. May cause drowsiness or dizziness.

- 2.2. Label elements**
Hazard pictogram

**Signal word**

Danger

Hazardous substances

acetone
n-butyl acetate

BODY PAINT

Creation date 11. March 2019
Revision date Version 1.1

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container to in accordance with national regulations.

Supplemental information

2.3. Other hazards

Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note.
CAS: 67-64-1 EC: 200-662-2 Registration number: 01-2119471330-49	acetone	25-50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	1
CAS: 106-97-8 EC: 203-448-7	butane (containing < 0,1 % butadiene (203-450-8))	10-25	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	1
CAS: 1330-20-7 EC: 215-535-7 Registration number: 01-2119488216-32	xylene (mixture of isomers)	5-10	Flam. Liq. 3, H226 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315	1
CAS: 74-98-6 EC: 200-827-9 Registration number: 01-2119486944-21	propane	5-10	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	
CAS: 123-86-4 EC: 204-658-1 Registration number: 01-2119485493-29	n-butyl acetate	5-10	Flam. Liq. 3, H226 STOT SE 3, H336	1
CAS: 9004-70-0 EC: 618-392-2	Nitrocellulose	5-10	Flam. Sol. 1, H228	

BODY PAINT

Creation date 11. March 2019

Revision date Version 1.1

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note.
CAS: 108-65-6 EC: 203-603-9 Registration number: 01-2119475791-29	2-methoxy-1-methylethyl acetate	2,5-5	Flam. Liq. 3, H226	1
CAS: 64-17-5 EC: 200-578-6 Registration number: 01-2119457610-43	ethanol	2,5-5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2, H319: C ≥ 50 %	1
Index: 606-004-00-4 CAS: 108-10-1 EC: 203-550-1 Registration number: 01-2119473980-30	4-methylpentan-2-one	2,5-5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335	1

Notes

1 Substance for which exposure limits of Community for working environment exist.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

Inhalation

Terminate the exposure immediately; move the affected person to fresh air.

Skin contact

Immediately wash with water and soap and rinse thoroughly.

Eye contact

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Provide medical treatment, specialized if possible.

Ingestion

Provide medical treatment if the person has any health problems.

4.2. Most important symptoms and effects, both acute and delayed**Inhalation**

May cause drowsiness or dizziness.

Skin contact

not available

Eye contact

Causes serious eye irritation.

Ingestion

not available

4.3. Indication of any immediate medical attention and special treatment needed

not available

BODY PAINT

Creation date 11. March 2019
 Revision date Version 1.1

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide, powder, water spray jet. Fight larger fires with water spray or foam.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

Vapours mixed up with air can be explosive.

5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Use personal protective equipment for work. Keep unprotected persons away.

6.2. Environmental precautions

Do not allow product to reach sewage system or any water course.

6.3. Methods and material for containment and cleaning up

Provide sufficient ventilation. Dispose of the collected material according to the instructions in the section 13. Do not flush with water or aqueous cleansing agents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Use only outdoors or in a well-ventilated area. Do not spray on an open flame or other ignition source. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. No smoking. Take precautionary measures against static discharge. Pressurised container: May burst if heated. Keep away from sources of heating, ignition and direct sunlight. Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Keep cool. Protect from sunlight. Keep container tightly closed. Do not expose to temperatures exceeding 50 ° C.

Storage class 2B - Aerosols

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

Austria

Substance name (component)	Type	Time of exposure	Value	Note	Source
acetone (CAS: 67-64-1)	MAK	8 hours	1200 mg/m ³		AUT
	MAK	Short-term	4800 mg/m ³		
	MAK	8 hours	500 ppm		
	MAK	Short-term	2000 ppm		
butane (containing < 0,1 % butadiene (203-450-8)) (CAS: 106-97-8)	MAK	8 hours	800 ppm		AUT

BODY PAINT

Creation date

11. March 2019

Revision date

Version

1.1

Austria

Substance name (component)	Type	Time of exposure	Value	Note	Source
butane (containing < 0,1 % butadiene (203-450-8)) (CAS: 106-97-8)	MAK	8 hours	1900 mg/m ³		AUT
	MAK	8 hours	1600 ppm		
	MAK	Short-term	3800 mg/m ³		
xylene (mixture of isomers) (CAS: 1330-20-7)	MAK	8 hours	221 mg/m ³	Skin	AUT
	MAK	Short-term	442 mg/m ³	Skin	
	MAK	8 hours	50 ppm	Skin	
	MAK	Short-term	100 ppm	Skin	
propane (CAS: 74-98-6)	MAK	8 hours	1800 mg/m ³		AUT
	MAK	Short-term	3600 mg/m ³		
	MAK	8 hours	1000 ppm		
	MAK	Short-term	2000 ppm		
n-butyl acetate (CAS: 123-86-4)	MAK	8 hours	480 mg/m ³		AUT
	MAK	Short-term	480 mg/m ³		
	MAK	8 hours	100 ppm		
	MAK	Short-term	100 ppm		
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	MAK	8 hours	275 mg/m ³	Skin	AUT
	MAK	Short-term	550 mg/m ³	Skin	
	MAK	8 hours	50 ppm	Skin	
	MAK	Short-term	100 ppm	Skin	
ethanol (CAS: 64-17-5)		8 hours	1900 mg/m ³		Gestis
		Short-term	3800 mg/m ³		
		8 hours	1000 ppm		
		Short-term	2000 ppm		
4-methylpentan-2-one (CAS: 108-10-1)	MAK	8 hours	83 mg/m ³	Skin	AUT
	MAK	Short-term	208 mg/m ³	Skin	
	MAK	8 hours	20 ppm	Skin	
	MAK	Short-term	50 ppm	Skin	

BODY PAINT

Creation date

11. March 2019

Revision date

Version

1.1

European Union

Substance name (component)	Type	Time of exposure	Value	Note	Source
acetone (CAS: 67-64-1)	OEL	8 hours	1210 mg/m ³		EU limits
	OEL	8 hours	500 ppm		
xylene (mixture of isomers) (CAS: 1330-20-7)	OEL	8 hours	221 mg/m ³		EU limits
	OEL	8 hours	50 ppm		
	OEL	Short-term	442 mg/m ³		
	OEL	Short-term	100 ppm		
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	OEL	8 hours	275 mg/m ³		EU limits
	OEL	8 hours	50 ppm		
	OEL	Short-term	550 mg/m ³		
	OEL	Short-term	100 ppm		
4-methylpentan-2-one (CAS: 108-10-1)	OEL	8 hours	83 mg/m ³		EU limits
	OEL	8 hours	20 ppm		
	OEL	Short-term	208 mg/m ³		
	OEL	Short-term	50 ppm		

United Kingdom of Great Britain and Northern Ireland

Substance name (component)	Type	Time of exposure	Value	Note	Source
acetone (CAS: 67-64-1)	WEL	8 hours	1210 mg/m ³		GBR
	WEL	15 minutes	3620 mg/m ³		
	WEL	8 hours	500 ppm		
	WEL	15 minutes	1500 ppm		
butane (containing < 0,1 % butadiene (203-450-8)) (CAS: 106-97-8)	WEL	8 hours	600 ppm		GBR
	WEL	8 hours	1450 mg/m ³		
	WEL	15 minutes	1810 mg/m ³		
	WEL	15 minutes	750 ppm		

BODY PAINT

Creation date

11. March 2019

Revision date

Version

1.1

United Kingdom of Great Britain and Northern Ireland

Substance name (component)	Type	Time of exposure	Value	Note	Source
xylene (mixture of isomers) (CAS: 1330-20-7)	WEL	8 hours	220 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
	WEL	15 minutes	441 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	8 hours	50 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	15 minutes	100 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
n-butyl acetate (CAS: 123-86-4)	WEL	8 hours	724 mg/m ³		GBR
	WEL	15 minutes	966 mg/m ³		
	WEL	8 hours	150 ppm		
	WEL	15 minutes	200 ppm		
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	WEL	8 hours	274 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
	WEL	15 minutes	548 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	8 hours	50 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	

BODY PAINT

Creation date

11. March 2019

Revision date

Version

1.1

United Kingdom of Great Britain and Northern Ireland

Substance name (component)	Type	Time of exposure	Value	Note	Source
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	WEL	15 minutes	100 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
ethanol (CAS: 64-17-5)	WEL	8 hours	1920 mg/m ³		Gestis
	WEL	8 hours	1000 ppm		
4-methylpentan-2-one (CAS: 108-10-1)	WEL	8 hours	208 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
	WEL	15 minutes	416 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	8 hours	50 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	15 minutes	100 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	

8.2. Exposure controls

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

Eye/face protection

Tightly sealed goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. Material of gloves: Nitrile rubber, NBR. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Protective gloves shall be replaced immediately when damaged.

Other protection: protective workwear.

Respiratory protection

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter A1P2.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

BODY PAINT

Creation date 11. March 2019
Revision date Version 1.1

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	aerosol
Physical state	liquid at 20°C
color	grey
Odour	characteristic
Odour threshold	data not available
pH	data not available
Melting point/freezing point	data not available
Initial boiling point and boiling range	data not available
Flash point	<0 °C
Evaporation rate	non-applicable
Flammability (solid, gas)	Extremely flammable aerosol.
Upper/lower flammability or explosive limits	
flammability limits	data not available
explosive limits	
bottom	1.5 %
upper	13.0 %
Vapour pressure	3600 hPa at 20 °C
Vapour density	data not available
Relative density	data not available
Solubility(ies)	
solubility in water	almost insoluble
solubility in fats	data not available
Partition coefficient: n-octanol/water	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
Viscosity	data not available
Explosive properties	data not available
Oxidising properties	data not available
data not available	

9.2. Other information

Density	data not available
ignition temperature	365 °C
content of organic solvents (VOC)	82.7 %
solid content (dry matter)	16.1 % volume
Max. VOC content in the product in its ready to use condition	683 g/l

SECTION 10: Stability and reactivity**10.1. Reactivity**

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Protect against strong acids, bases and oxidizing agents.

10.4. Conditions to avoid

not available

10.5. Incompatible materials

not available

10.6. Hazardous decomposition products

not available

BODY PAINTCreation date 11. March 2019
Revision date Version 1.1**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

xylene (mixture of isomers)

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	4300 mg/kg		Rat	
Dermal	LD ₅₀	2000 mg/kg		Rabbit	
Inhalation	LC ₅₀	21.7 mg/l	4 hour	Rat	

Skin corrosion/irritation

Based on available data the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

Based on available data the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity****Acute toxicity**

Data for the mixture are not available.

xylene (mixture of isomers)

Parameter	Value	Time of exposure	Species	Environment
LC ₅₀	1570 µg/l	96 hour	Fishes (Cyprinus carpio)	

12.2. Persistence and degradability

Data not available.

12.3. Bioaccumulative potential

BODY PAINT

Creation date	11. March 2019	Version	1.1
Revision date			

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Other adverse effects

Additional ecological information:

General notes: Water hazard class 1 (german Regulation, self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

Packaging waste type code

15 01 10 packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information**14.1. UN number**

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not available

14.5. Environmental hazards

No

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not available

Additional information

Hazard identification No.

UN number

Classification code

Safety signs

	(Kemler Code)
---	---------------

5F

2.1



BODY PAINT

Creation date	11. March 2019	Version	1.1
Revision date			

Road transport - ADR

Limited quantities	1 L
Excepted quantities	E2
Transport category	2
Tunnel restriction code	(D)

Marine transport - IMDG

EmS (emergency plan)	F-D, S-U
Marine Pollutant	No

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

15.2. Chemical safety assessment

not available

SECTION 16: Other information**A list of standard risk phrases used in the safety data sheet**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H312+H332	Harmful in contact with skin or if inhaled.

Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with national regulations.

A list of additional standard phrases used in the safety data sheet

EUH 066	Repeated exposure may cause skin dryness or cracking.
---------	---

Other important information about human health protection

BODY PAINT

Creation date	11. March 2019	Version	1.1
Revision date			

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
DNEL	Derived no-effect level
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
IC ₅₀	Concentration causing 50% blockade
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LOAEC	Lowest observed adverse effect concentration
LOAEL	Lowest observed adverse effect level
log Kow	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution From Ships
NOAEC	No observed adverse effect concentration
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
NOEL	No observed effect level
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted no-effect concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Acute Tox.	Acute toxicity
Aerosol	Aerosol
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gas

BODY PAINT

Creation date	11. March 2019	Version	1.1
Revision date			

Flam. Liq.	Flammable liquid
Flam. Sol.	Flammable solid
Press. Gas	Gases under pressure
Skin Irrit.	Skin irritation
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

2, 3, 8, 9, 11, 12, 15, 16

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.