

According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue:09/05/2017Trade name:Page: 1/10Reviewed on:EASY ZINC SPRAYVersion: 1.0

1. Section 1. Identification of the substance/mixture and of the company/undertaking:

1.1. Product identifier:

Trade name: EASY ZINC SPRAY

Product code: 1 20517

1.2. Relevant identified uses of the substance or mixture and uses advised against:

Uses of the mixture: Zinc spray.

Sector of use category:

SU22 Professional uses: Public domain (administration, education, entertainment, services,

SU3 craftsmen)

Process category:

1.3.

PROC7 Industrial spraying
PROC11 Non industrial spraying

Environmental release category:

ERC8a Wide dispersive indoor use of processing aids in open systems
ERC8d Wide dispersive outdoor use of processing aids in open systems

Uses advised against: Not known. Details of the supplier of the safety data sheet:

Identification of manufacturer/Supplier:

RETECH, s.r.o. Vackova 1541/4

150 00 Praha 5 - Stodůlky

Telephone number/Fax: +420 327 596 128, +420 327 596 428

E-mail: info@retech.cz

1.4. Emergency telephone number: RETECH, Suchdol 212, 285 02 Suchdol u Kutné Hory, Czech Republic

Telephone number: +420 327 596 128 (7.30-16.00 hour)

Toxikologické informační středisko (Toxicology information centre),

Na bojišti 1, 128 08 PRAHA 2, Czech Republic

Telephone number: +420 224 919 293, +420 224 915 402 (24 hours a day)

2. Section 2. Hazard identification:

2.1. Classification of the substance or mixture:

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements:

Labelling according to Regulation (EC) No 1272/2008 [CLP]:









Signal Word: Danger

Hazard Statements:

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.



According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue:09/05/2017Trade name:Page: 2/10Reviewed on:EASY ZINC SPRAYVersion: 1.0

P211 Do not spray on an open flame or other ignition source.

P273 Avoid release to the environment.

P271 Use only outdoors or in a well-ventilated area.

P261 Avoid breathing mist/vapours/spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P391 Collect spillage.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with national regulation.

Supplemental Hazard information (EU):

EUH066 Repeated exposure may cause skin dryness or cracking.

Contained dangerous substances:

67-64-1 Acetone

2.3. Other hazards:

Results of PBT and vPvB assessment:

PBT: Not applicable. vPvB: Not applicable.

3. Section 3. Composition/information on ingredients:

3.2. Mixtures:

Description of the mixture: Mixture of active ingredients with propellants

Hazardous ingredients:

646	67.64.4		25 . 50.0/
CAS:	67-64-1	Acetone	25 -< 50 %
	200-662-2	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
	01-2119471330-49		
CAS:	106-97-8	Butane (containing < 0.1 % butadiene)	10 -< 25 %
EINECS:	203-448-7	Flam. Gas 1, H220; Press. Gas, H280	
Reg. No.	: 01-2119474691-32		
CAS:	74-98-6	Propane	10 -< 25 %
EINECS:	200-827-9	Flam. Gas 1, H220; Press. Gas, H280	
Reg. No.	: 01-2119486944-21		
CAS:	123-86-4	n-Butyl acetate	3 -< 10 %
EINECS:	204-658-1	Flam. Liq. 3, H226; STOT SE 3, H336	
Reg. No.	: 01-2119485493-29		
CAS:	1330-20-7	Xylene (mixture of isomers)	3 -< 10 %
EINECS:	215-535-7	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332;	
Reg. No.	01-2119488216-32	Skin Irrit. 2, H315	
CAS:	7440-66-6	Zinc powder - zinc dust (pyrophoric)	2.5 -< 3 %
EINECS:	231-175-3	Pyr. Sol. 1, H250; Water-react. 2, H260; Aquatic Acute 1,	
		H400; Aquatic Chronic 1, H410	
CAS:	7429-90-5	Aluminium powder (stabilised)	1.0 -< 2.5 %
EINECS:	231-072-3	Flam. Sol. 1, H228	
CAS:	100-41-4	Ethylbenzene	1.0 -< 2.5 %
EINECS:	202-849-4	Flam. Liq. 2, H225; Acute Tox. 4, H332	
CAS:	64742-95-6	Solvent naphtha (petroleum), light arom.	0.3 -< 1 %
EINECS:	265-199-0	(containing < 0.1 % benzene)	
		Flam. Liq. 3, H226; Asp. Tox. 1, H304	
CAS:	7779-90-0	Trizinc bis(orthophosphate)	0.3 -< 1 %
EINECS:	231-944-3	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	



According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue:	09/05/2017	Trade name:	Page: 3/10
Reviewed on:		EASY ZINC SPRAY	Version: 1.0

CAS:	1314-13-2	Zinc oxide	0.1 -< 0.25 %
EINECS:	215-222-5	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

For full text of H-statements: see SECTION 16

4. Section 4. First aid measures:

4.1. Description of first aid measures:

General notes: When in doubt or if symptoms are observed, get medical advice.

After inhalation: Move affected person to fresh air.

Get medical attention if any discomfort continues.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under runni

Rinse opened eye for several minutes under running water.

Remove contact lenses, if present and easy to do. Continue rinsing.

Get medical attention if any discomfort continues.

After swallowing: Do not induce vomiting.

Immediately call a doctor.

4.2. Most important symptoms and effects, both acute and delayed:

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5. Section 5. Fire fighting measures:

5.1. Extinguishing media:

Suitable extinguishing agents: Water haze, carbon dioxide, fire-extinguishing powder, alcohol resistant foam.

Unsuitable extinguishing

agents: Water jet.

5.2. Special hazards arising from the substance or mixture:

No further relevant information available.

5.3. Advice for firefighters: No special requirements.

Wear protective clothing and self-contained breathing apparatus.

6. Section 6. Accidental release measures:

6.1. Personal precautions, protective equipment and emergency procedures:

Wear protective equipment, see Section 8.

Keep unprotected persons away. Ensure adequate ventilation.

6.2. Environmental precautions: Do not allow to enter sewage system, surface or ground water.

Inform respective authorities in case product reaches water course or sewage

system.

6.3. Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose contaminated material as waste according to Section 13.

6.4. Reference to other sections: See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7. Section 7. Handling and storage:

7.1. Precautions for safe handling:

Protective measures: Wear protective equipment, see Section 8.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Measures to prevent fire: Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures

exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.



According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue:	09/05/2017	Trade name:	Page: 4/10
Reviewed on:		EASY ZINC SPRAY	Version: 1.0

7.2. Conditions for safe storage, including any incompatibilities:

Requirements for storage rooms and vessels:

Store in cool, dry conditions in well sealed receptacles.

Observe official regulations on storing packagings with pressurized containers.

Technical measures and storage conditions:

Store in a cool place.

Observe official regulations on storing packagings with pressurized containers.

Further information on storage conditions:

Protect from heat and direct sunlight.

7.3. Specific end use(s): No further relevant information available.

8. Section 8. Exposure controls/personal protection:

8.1. Control parameters:

Components with limit values that require monitoring at the workplace:

WEL (United Kingdom): EH40/2005

CAS	Substance	U	-term ref. period)		t-term ref. period)	Comments
		ppm	mg/m ³	ppm	mg/m³	
67-64-1	Acetone	500	1210	1500	3620	
106-97-8	Butane	600	1450	750	1810	Carc, (only applies if Butane contains more than 0.1 % of buta-1,3-diene)
123-86-4	Butyl acetate	150	724	200	966	
7429-90-5	Aluminium metal inhalable dust	-	10	-	-	
100-41-4	Ethylbenzene	100	441	125	552	Skin

OFI (FU): 2000/39/FG 2006/15/FG 2009/161/FG

OLL (LO): 20	LL (LO): 2000/33/LG, 2000/13/LG, 2003/101/LG					
CAS	Name of agent	Eight hours		Short-term		Notation
		ppm	mg/m³	ppm	mg/m³	
67-64-1	Acetone	500	1210	-	-	
1330-20-7	Xylene, mixed isomers,	50	221	100	442	Skin
	pure					
100-41-4	Ethylbenzene	100	442	200	884	Skin

Biological limit values:

BMGV: EH40/2005

CAS	Substance	BMGV	Sampling time
1330-20-7	Xylene, o-, m-, p- or	650 mmol methyl hippuric acid/mol	
	mixed isomers	creatinine in urine	Post shift

DNEL

67-64-1 Acetone

Inhalation	Chronic effects systemic	1210	mg/m ³	Workers
	Chronic effects systemic	200	mg/m³	Consumers
	Acute effects local	2420	mg/m ³	Workers
Dermal	Chronic effects systemic	186	mg/kg Body weight/day	Workers
	Chronic effects systemic	62	mg/kg Body weight/day	Consumers
Oral	Chronic effects systemic	62	mg/kg Body weight/day	Consumers

PNEC

67-64-1 Acetone

67-64-1 Acetone		
Freshwater	10.6	mg/l
Marine water	1.06	mg/l
Intermittent releases	21	mg/l
Sewage treatement plant	100	mg/l
Sediment (freshwater)	30.4	mg/kg
Sediment (marine water)	3.04	mg/kg



According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue: 09/05/2017 Trade name: Page: 5/10
Reviewed on: EASY ZINC SPRAY Version: 1.0

Soil 29.5 mg/kg

Additional information: The lists that were valid during the compilation were as basis.

8.2. Exposure controls:

Technical measures to prevent exposure:

Ensure good ventilation/exhaustion at the workplace.

General protective measures: Store away from foodstuffs, beverages and feed.

Take off immediately all contaminated clothing. Wash hands before breaks and at the end of work.

Avoid breathing gas/vapours/spray.

Avoid skin and eye contact. Personal protection equipment:

Respiratory protection: In case of brief exposure or low pollution use respiratory filter device.

Filter: AX/P2

During intensive or longer exposure use self-contained breathing apparatus.

Eye protection: Tightly sealed goggles.
Hand protection: Protective gloves
Solvent resistant gloves

The final selection of the glove material must be carried out on the basis

of penetration times, permeation rates and degradation.

Material of gloves: nitrile rubber Penetration time of glove material:

The exact break through time has to be found out by the manufacturer

of the protective gloves and has to be observed.

Skin protection: Protective clothing.

9. Section 9. Physical and chemical properties:

9.1. Information on basic physical and chemical properties:

Form: Aerosol Colour: Silver

Odour: Charakteristic
Odour threshold: Not determined.
Value pH at 20 °C: Not determined.
Melting point/freezing point: Not determined.

Initial boiling point/boiling

range: -44 °C Flash point: -97 °C

Evaporation rate: Not determined. Flammability (solid, gas): Not determined.

Explosive properties: The product is not explosive. However, formation of explosive air/steam

mixtures is possible.

Explosive limits:

lower: 1.0 Vol %
 upper: 13.0 Vol %
 Vapour pressure at 20°C: 4 Bar

Vapour density at 20 °C: Not determined.

Density at 20 °C: 0.733 g/cm³

Relative density: Not determined.

Solubility in/miscibility: Water: Not miscible or difficult to mix.

Partition coefficient (n-octa-

nol/water): Not determined.

Ignition temperature: 365 °C

Decomposition temperature: Not determined.

Self-ignition temperature: The product is not selfigniting.

Viscosity: Not determined. Oxidising properties: Not determined.



According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue:	09/05/2017	Trade name:	Page: 6/10
Reviewed on:		EASY ZINC SPRAY	Version: 1.0

9.2. Other information:

 VOC (EU):
 645.9 g/l

 VOC (CH):
 86.8 %

 Organic solvent:
 86.8 %

 Solid content:
 13.2 %

10. Section 10. Stability and reactivity:

10.1. Reactivity: No further relevant information available.

10.2. Chemical stability: No decomposition if used according to specifications.

10.3. Possibility of hazardous reactions:

No dangerous reactions known.

10.4. Conditions to avoid: No further relevant information available.10.5. Incompatible materials: No further relevant information available.

10.6. Hazardous decomposition products:

No dangerous decomposition products known.

11. Section 11. Toxicological information:

11.1. Information on toxicological effects:

Acute toxicity: Based on available data, the classification criteria are not met.

Relevant hazards for substance:

67-64-1 Acetone

Oral	LD50	rat	5800	mg/kg
Dermal	LD50	rabbit	7800	mg/kg
Inhalative	LC50/4h	rat	> 20	mg/l

1330-20-7 Xylene (mixture of isomers)

Oral	LD50 rat	4300	mg/kg
Dermal	LD50 rabbit	2000	mg/kg

7440-66-6 Zinc powder - zinc dust (pyrophoric)

Oral	LD50 rat	> 2000 mg/kg
	LDLO duck	388 mg/kg

100-41-4 Ethylbenzene

Oral	LD50 rat	3500	mg/kg
Dermal	LD50 rabbit	17800	mg/kg
Inhalative	LC50 rat	> 2000	mg/l

7779-90-0 Trizinc bis(orthophosphate)

Urai LD50 rat 5000 mg/kg		Oral	LD50 rat	5000	mg/kg
--------------------------	--	------	----------	------	-------

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Causes serious eye irritation.

Respiratory or skin sensitiza-

tion: Based on available data, the classification criteria are not met.
Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity

- single exposure: May cause drowsiness or dizziness.

Specific target organ toxicity

- repeated exposure: Based on available data, the classification criteria are not met.
Aspiration hazard: Based on available data, the classification criteria are not met.

Other information: No further relevant information available.

12. Section 12. Ecological information:

12.1. Toxicity:

Aquatic toxicity: No further relevant information available.

67-64-1 Acetone

Fish: EC50/96 h 8300 mg/l



According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue:	09/05/2017	Trade name:	Page: 7/10
Reviewed on:		EASY ZINC SPRAY	Version: 1.0

		LAST ZINC SI NAT		
	•			
Invertebrates:	EC50	Daphnia magna	8800	mg/l
1330-20-7 Xylene (mix	xture of is	omers)		
Fish: L	.C50/96 h	Pimephales promelas	8.9 – 16.4	mg/l
Invertebrates: E	C50/48 h	Daphnia magna	3.2 - 9.5	mg/l
7440-66-6 Zinc powde	er - zinc dı	ust (pyrophoric)		
Fish: L	.C50/96 h	Onchorhynchus mykiss	0.24	mg/l
L	.C50/96 h	Pimephales promelas	0.238	mg/l
Invertebrates:	LC50	Daphnia magna	0.57	mg/l
E	C50/48 h	Daphnia magna	2.8	mg/l
100-41-4 Ethylbenzen	ie			
Fish: L	.C50/96 h		> 10	mg/l
Invertebrates:	EC50	Daphnia magna	> 100	mg/l
7779-90-0 Trizinc bis(c	orthophos	sphate)		
Fish: L	.C50/96 h	Onchorhynchus mykiss	0.14	mg/l
Invertebrates: E	C50/48 h	Daphnia magna	2.34	mg/l
Algae: Er	C50/72 h	Desmodesmus subspicatus	0.14	mg/l
Persistence and degradability:		No further relevant information available.		
Bioaccumulative potential:		No further relevant information available.		
Mobility in soil:		No further relevant information available.		
Additional ecological i	informatio	on:		
Ecotoxic effects:		Remark: Toxic for fish.		
General notes:		Also poisonous for fish and plankton in water bodies	S.	
		Toxic to aquatic life with long lasting effects.		
Results of PBT and vPv	vB assessr	ment:		
PBT:		Not applicable.		

12.5.

PBT: Not applicable. VPvB: Not applicable.

12.6. Other adverse effects: No further relevant information available.

13. Section 13. Disposal considerations:

13.1. Waste treatment methods:

12.2. 12.3. 12.4.

> Product disposal: Must not be disposed together with household garbage.

> > Do not allow product to reach sewage system.

European Waste Catalogue:

08 01 11* waste paint and varnish containing organic solvents or other

hazardous substances (*hazardous waste)

Packagings disposal: Disposal must be made according to official regulations.

European Waste Catalogue:

15 01 11* metallic packaging containing a hazardous solid porous matrix

(for example asbestos), including empty pressure containers

(*hazardous waste)

Uncontaminated packaging can be recycled.

Other disposal recommen-

dations: Disposal must be made according to official regulations.

> The final decisions on the appropriate waste management method, in line with regional, national and European legislation, and possible adaptation to local conditions, remains the responsibility of the waste treatment operator.

14. **Section 14. Transport information:**

14.1. UN number:

ADR, IMDG, IATA UN 1950

14.2. UN proper shipping name:

ADR UN 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

IMDG AEROSOLS (ZINC POWDER, Solvent naphtha (petroleum), light arom.

(containing < 0.1 % benzene), MARINE POLLUTANT



According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue:09/05/2017Trade name:Page: 8/10Reviewed on:EASY ZINC SPRAYVersion: 1.0

IATA AEROSOLS, flammable

14.3. Transport hazard class(es):

ADR

(1) (¥2)

Class 2 5F Gases

Hazard label 2.1

IMDG

Class 2.1

Hazard label 2.1

IATA

2

Class 2.1 Hazard label 2.1

14.4. Packing group:

ADR, IMDG, IATA Void

14.5. Environmental hazards: The product contains environmentally hazardous substances:

Zinc powder - zinc dust (pyrophoric)

Marine pollutant: Yes

Symbol (fish and tree)

Special marking (ADR): Symbol (fish and tree)
14.6. Special precautions for user: Warning: Gases

EMS Number: F-D, S-U

Danger Code (Kemler):

Segregation group: Heavy metals and their salts (including their organometallic compounds)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code:

Not applicable

ADR

Tunnel restriction code: D

UN "Model Regulation": UN 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1

L5. Section 15. Regulatory information:

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture:

Used legislation:

Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals, as amended (REACH)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures, as amended (CLP)

Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, as amended Commission Decision 2000/532/EC establishing a list of wastes, as amended

Council Directive 89/686/EEC on the approximation of the laws of the Member States relating to personal protective equipment, as amended

Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended

Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values Commission Directive 2006/15/EC establishing a second list of indicative occupational exposure limit values Commission Directive 2009/161/EU establishing a third list of indicative occupational exposure limit values Directive 2004/42/CE of the European Parliament and of the Council on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC, as amended

EU limit for this product is (Cat. B/e): 840 g/l (2007).

This product contains max. 645.9 g/I VOC.



According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue:09/05/2017Trade name:Page: 9/10Reviewed on:EASY ZINC SPRAYVersion: 1.0

Class NK, 75 -< 100 % VOC-CH: 88.11 % Danish MAL Code: 4-3

15.2. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16. Section 16. Other information:

Relevant H-statements (Section 3):

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H250 Catches fire spontaneously if exposed to air.

H228 Flammable solid.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level

EC50: Median effective concentration to 50% of a population

EINECS: European Inventory of Existing Commercial Chemical Substances

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods LC50: Median concentration lethal to 50 % of a test population

LD50: Median dose lethal to 50 % of a test population

OEL: Occupational Exposure Limit
PBT: Persistent, Bioaccumulative, Toxic
PNEC: Predicted No-Effect Concentration

Reg.nr.: Registration number VOC: Volatile Organic Compounds

vPvB: Very Persistent, Very Bioaccumulative

WEL: Workplace exposure limits
Acute Tox. 4: Acute toxicity, category 4
Aerosol 1: Flammable aerosol, category 1

Aquatic Acute 1: Hazardous to the aquatic environment, category 1 Aquatic Chronic 1: Hazardous to the aquatic environment, category 1 Aquatic Chronic 2: Hazardous to the aquatic environment, category 2

Asp. Tox. 1: Aspiration hazard, category 1 Eye Irrit. 2: Serious eye irritation, category 2 Flam. Gas 1: Flammable gas, category 1 Flam. Liq. 2: Flammable liquid, category 2 Flam. Liq. 3: Flammable liquid, category 3

Flam. Sol 1: Flammable solid, category 1 Press. Gas: Gases under pressure

Pyr. Sol 1: Pyrophoric solid, category 1 Skin Irrit. 2: Skin irritation, category 2

STOT SE 3: Specific target organ toxicity — single exposure, category 3



According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue:	09/05/2017	Trade name:	Page: 10/10
Reviewed on:		EASY ZINC SPRAY	Version: 1.0

Water-react. 2: Substance or mixture which in contact with water emits flammable gas, category 2

The information contained herein is based on our best knowledge and the present legislation. Further, the Safety Data Sheet has been elaborated on the basis of the original Safety Data Sheet provided by the manufacturer. These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

*Compared to the last version the data has been changed.