

EPOXY PRIMER SPRAY

Creation date	23rd September 2022	Version	3.0
Revision date			

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier** EPOXY PRIMER SPRAY
Substance / mixture mixture
Number 1 35079
UFI 8532-6DEN-400C-0HH6

1.2. Relevant identified uses of the substance or mixture and uses advised against**Mixture's intended use**

Varnish.

The use descriptors

SU 22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PROC 7	Industrial spraying
PROC 11	Non industrial spraying

Mixture uses advised against

For professional use only.

1.3. Details of the supplier of the safety data sheet**Supplier**

Name or trade name	RETECH, s.r.o.
Address	Vackova 1541/4, Praha 5 - Stodůlky, 155 00 Czech Republic
Identification number (CRN)	25018205
VAT Reg No	CZ25018205
Phone	+420327596428
E-mail	info@retech.cz
Web address	www.retech.com

Competent person responsible for the safety data sheet

Name	RETECH, s.r.o.
E-mail	info@retech.cz

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification of the mixture in accordance with Regulation (EC) No 1272/2008**

The mixture is classified as dangerous.

Aerosol 1, H222, H229
Skin Irrit. 2, H315
Skin Sens. 1, H317
Eye Dam. 1, H318
STOT SE 3, H336
Aquatic Chronic 3, H412

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Extremely flammable aerosol. Pressurised container: May burst if heated.

Most serious adverse effects on human health and the environment

May cause drowsiness or dizziness. Causes serious eye damage. Causes skin irritation. May cause an allergic skin reaction.
Harmful to aquatic life with long lasting effects.

EPOXY PRIMER SPRAY

Creation date

23rd September 2022

Revision date

Version

3.0

2.2. Label elements**Hazard pictogram****Signal word**

Danger

Hazardous substances

acetone
n-butyl acetate
butan-1-ol
epoxy resin

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P280	Wear eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to in accordance with national regulations.

Supplemental information

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Density	0,8 g/cm ³ at 20 °C
VOC	90,5 %
Dry matter	8,4 % volume
VOC limit value	cat. B (e) : 840 g/l
Max. VOC content in the product in its ready to use condition	724,0 g/l

2.3. Other hazards

Buildup of explosive mixtures possible without sufficient ventilation. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

EPOXY PRIMER SPRAY

Creation date 23rd September 2022

Revision date

Version

3.0

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 603-019-00-8 CAS: 115-10-6 EC: 204-065-8 Registration number: 01-2119472128-37	dimethyl ether	25-<50	Flam. Gas 1A, H220 Press. Gas (compressed gas), H280	4
Index: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 Registration number: 01-2119471330-49	acetone	12,5-<20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	4
Index: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 Registration number: 01-2119485493-29	n-butyl acetate	12,5-<20	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	
Index: 603-004-00-6 CAS: 71-36-3 EC: 200-751-6 Registration number: 01-2119484630-38	butan-1-ol	5-<10	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335, H336	
Index: 601-022-00-9 EC: 905-588-0 Registration number: 01-2119488216-32	xylene	2,5-<5,0	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373	
Index: 022-006-00-2 CAS: 13463-67-7 EC: 236-675-5 Registration number: 01-2119489379-17	titanium dioxide	2,5-<5,0	Carc. 2, H351 (inhalation)	1, 2, 3
Index: 030-011-00-6 CAS: 7779-90-0 EC: 231-944-3 Registration number: 01-2119485044-40	trizinc bis(orthophosphate)	<2,5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25	propan-2-ol	<2,5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
CAS: 25036-25-3	epoxy resin	<2,5	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319	
Index: 030-013-00-7 CAS: 1314-13-2 EC: 215-222-5 Registration number: 01-2119463881-32	zinc oxide	<2,5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	

EPOXY PRIMER SPRAY

Creation date

23rd September 2022

Revision date

Version

3.0

Notes

- 1 Note V: If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.
- 2 Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

- 3 Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.
- 4 Substance with a Union workplace exposure limit.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Provide medical treatment. In case of unconsciousness place patient stably in side position for transportation.

If on skin

Wash with plenty of soap and water.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Provide medical treatment.

If swallowed

Rinse out the mouth with water and provide 2-5 dL of water. Provide medical treatment.

4.2. Most important symptoms and effects, both acute and delayed**If inhaled**

May cause drowsiness or dizziness.

If on skin

May cause an allergic skin reaction. Causes skin irritation.

If in eyes

Causes serious eye damage.

If swallowed

not available

4.3. Indication of any immediate medical attention and special treatment needed

not available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide, powder, water spray jet. Fight larger fires with water spray or alcohol resistant foam. Accommodate extinguishing components to the location of fire.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire toxic gases may arise.

5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Put on breathing apparatus. Use personal protective equipment for work. Keep unprotected persons away. Extremely flammable aerosol. Pressurised container: May burst if heated. Remove all ignition sources.

EPOXY PRIMER SPRAY

Creation date 23rd September 2022

Revision date Version 3.0

6.2. Environmental precautions

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

6.3. Methods and material for containment and cleaning up

Provide sufficient ventilation. Use neutralising agent. Dispose of the collected material according to the instructions in the section 13.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Do not spray on an open flame or other ignition source. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. No smoking. Take precautionary measures against static discharge. Pressurised container: May burst if heated. Keep away from sources of heating, ignition and direct sunlight. Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

EU limits

Substance name (component)	Type	Value
dimethyl ether (CAS: 115-10-6)	OEL 8 hours	1920 mg/m ³
	OEL 8 hours	1000 ppm
acetone (CAS: 67-64-1)	OEL 8 hours	1210 mg/m ³
	OEL 8 hours	500 ppm

8.2. Exposure controls

Do not store together with food, drink and animal feed. Remove contaminated clothes. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest. Do not inhale aerosols. Do not inhale gases and vapours. Prevent contact with skin and eyes.

Eye/face protection

Tightly sealed goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. Material of gloves: Butyl rubber. Recommended thickness of the material: ≥ 0.4 mm. Penetration time of glove material: 42-480 min. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear.

Respiratory protection

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self contained respiratory protective device. Filter A2/P3.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state gas
Colour grey
Odour characteristic

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

EPOXY PRIMER SPRAY

Creation date	23rd September 2022	Version	3.0
Revision date			

Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	data not available
Flammability	Extremely flammable aerosol.
Lower and upper explosion limit	
bottom	1,2 % (CAS: 123-86-4)
upper	26,2 % (CAS: 115-10-6)
Flash point	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	data not available
Kinematic viscosity	data not available
Solubility in water	almost insoluble
Solubility in fats	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	247 hPa at 20 °C (CAS: 67-64-1)
Density and/or relative density	
Density	0,8 g/cm ³ at 20 °C
Form	aerosol dispenser: spray aerosol
data not available	

9.2. Other information

Evaporation rate	data not available
Ignition temperature	240 °C
Content of organic solvents (VOC)	90,5 %
Solid content (dry matter)	8,4 % volume
VOC limit value	cat. B (e) : 840 g/l
Max. VOC content in the product in its ready to use condition	724,0 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

not available

10.5. Incompatible materials

not available

10.6. Hazardous decomposition products

Unknown.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀		5800 mg/kg		Rat	
Dermal	LD ₅₀		>15800 mg/kg		Rabbit	
Inhalation	LC ₅₀		76 mg/l	4 hour	Rat	

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

EPOXY PRIMER SPRAY

Creation date 23rd September 2022

Revision date

Version

3.0

butan-1-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀		2292 mg/kg		Rat	
Dermal	LD ₅₀		3430 mg/kg		Rabbit	
Inhalation	LC ₅₀		17000 mg/m ³	4 hour	Rat	

n-butyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀	OECD 401	10800 mg/kg		Rat	
Dermal	LD ₅₀		>17600 mg/kg		Rabbit	
Inhalation	LC ₅₀		>21 mg/m ³	4 hour	Rat	

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀		5840 mg/kg		Rat	
Dermal	LD ₅₀		13900 mg/kg		Rabbit	
Inhalation	LC ₅₀		>25 mg/l	6 hour	Rat	

xylene

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀		3523 mg/kg		Rat	
Dermal	LD ₅₀		2000 mg/kg		Rabbit	
Inhalation	LC ₅₀		29000 mg/m ³	4 hour	Rat	

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

Based on available data the classification criteria are not met.

11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

Harmful to aquatic life with long lasting effects.

acetone

Parameter	Value	Exposure time	Species	Environment
LC ₅₀	8300 mg/l	96 hour	Fishes	
EC ₅₀	7200 mg/l	96 hour	Algae	

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

EPOXY PRIMER SPRAY

Creation date 23rd September 2022

Revision date

Version

3.0

acetone

Parameter	Value	Exposure time	Species	Environment
LC ₅₀	8450 mg/l	48 hour	Crustaceans	

butan-1-ol

Parameter	Value	Exposure time	Species	Environment
LC ₅₀	1376 mg/l	96 hour	Fishes	

dimethyl ether

Parameter	Value	Exposure time	Species	Environment
EC ₅₀	155 mg/l	96 hour	Algae	
LC ₅₀	>4000 mg/l	48 hour	Daphnia (Daphnia magna)	
LC ₅₀	>4000 mg/l	96 hour	Fishes	

propan-2-ol

Parameter	Value	Exposure time	Species	Environment
LC ₅₀	9640 mg/l	96 hour	Fishes (Pimephales promelas)	
LC ₅₀	9714 mg/l	24 hour	Daphnia (Daphnia magna)	

xylene

Parameter	Value	Exposure time	Species	Environment
EC ₅₀	7.4 mg/l	48 hour	Daphnia (Daphnia magna)	
LC ₅₀	13.5 mg/l	96 hour	Fishes	

12.2. Persistence and degradability

Not available.

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Water hazard class 2 (German Regulation; Self-assessment): hazardous for water. Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances *

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

EPOXY PRIMER SPRAY

Creation date 23rd September 2022
Revision date Version 3.0

Packaging waste type code

15 01 11 metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers *

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not relevant

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information


Stowage Code: SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. Segregation Code: SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

Hazard identification No.

UN number

Classification code

Safety signs



5F

2.1



Road transport - ADR

Limited quantities

Excepted quantities

Transport category

Tunnel restriction code

1L

E0

2

(D)

Railway transport - RID

Marine transport - IMDG

EmS (emergency plan)

F-D, S-U

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended. Product contains reportable explosives precursors: Reporting of suspicious transactions, disappearances and thefts according to Regulation (EU) 2019/1148, Article 9.

EPOXY PRIMER SPRAY

Creation date 23rd September 2022

Revision date

Version

3.0

15.2. Chemical safety assessment

not available

SECTION 16: Other information**A list of standard risk phrases used in the safety data sheet**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H312+H332	Harmful in contact with skin or if inhaled.

Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P280	Wear eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to in accordance with national regulations.

A list of additional standard phrases used in the safety data sheet

EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH066	Repeated exposure may cause skin dryness or cracking.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
ES	Identification code for each substance listed in EINECS
EU	European Union
EuPCS	European Product Categorisation System

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

EPOXY PRIMER SPRAY

Creation date	23rd September 2022	Version	3.0
Revision date			

IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
log K _{ow}	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution from Ships
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Acute Tox.	Acute toxicity
Aerosol	Aerosol
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
Carc.	Carcinogenicity
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Press. Gas	Gases under pressure
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 3.0 replaces the SDS version from 07 August 2020. Changes were made in sections 11, 12, 13, 15 and 16.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

EPOXY PRIMER SPRAY

Creation date

23rd September 2022

Revision date

Version

3.0