

HEADLIGHT UV PROTECTOR

Creation date 10th November 2020
Revision date Version 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture HEADLIGHT UV PROTECTOR
Number mixture
1 35165
UFI SHA2-QDSS-F00W-VVMR
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use Diluent.
Mixture uses advised against For professional use only.
- 1.3. Details of the supplier of the safety data sheet**
Supplier
Name or trade name RETECH, s.r.o.
Address Vackova 1541/4, Praha 5 - Stodůlky, 155 00
Czech Republic
Identification number (CRN) 25018205
VAT Reg No CZ25018205
Phone +420327596428
E-mail info@retech.cz
Web address www.retech.com
- Competent person responsible for the safety data sheet**
Name RETECH, s.r.o.
E-mail info@retech.cz
- 1.4. Emergency telephone number**
European emergency number: 112

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Flam. Liq. 3, H226
Asp. Tox. 1, H304
STOT SE 3, H336
Aquatic Chronic 3, H412

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Flammable liquid and vapour.

Most serious adverse effects on human health and the environment

May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

2.2. Label elements**Hazard pictogram****Signal word**

Danger

HEADLIGHT UV PROTECTOR

 Creation date 10th November 2020
 Revision date Version 2.0

Hazardous substances

 n-butyl acetate
 hydrocarbons, C9, aromatics

Hazard statements

 H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 No smoking.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P331 Do NOT induce vomiting.

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 Registration number: 01-2119485493-29	n-butyl acetate	65-<70	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	1
Index: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9 Registration number: 01-2119475791-29	2-methoxy-1-methylethyl acetate	24,0- <26,5	Flam. Liq. 3, H226	1
EC: 918-668-5 Registration number: 01-2119455851-35	hydrocarbons, C9, aromatics	10,0- <12,5	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335, H336 Aquatic Chronic 2, H411 EUH066	

Notes

1 Substance for which exposure limits of Community for working environment exist.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

HEADLIGHT UV PROTECTOR

Creation date

10th November 2020

Revision date

Version

2.0

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. In the event of issues, find medical help.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. In the event of issues, find medical help. Wash contaminated clothing before reuse.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. In the event of issues, find medical help.

If swallowed

Do not induce vomiting unless directed to do so by medical personnel. Provide medical treatment.

4.2. Most important symptoms and effects, both acute and delayed**If inhaled**

May cause drowsiness or dizziness.

If on skin

not available

If in eyes

not available

If swallowed

not available

4.3. Indication of any immediate medical attention and special treatment needed

not available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide, foam, powder. Water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

Container: May burst if heated. Do not breathe smoke.

5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water. Dispose of contaminated extinguishing water and remains after the fire in accordance with the official regulations.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Stop leak if safe to do so. Remove all ignition sources. Use non-sparking tools. Use personal protective equipment for work. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. Provide sufficient ventilation.

6.4. Reference to other sections

See the Section 7, 8 and 13.

HEADLIGHT UV PROTECTOR

Creation date 10th November 2020
Revision date Version 2.0

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Use only outdoors or in a well-ventilated area. Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air. Take action to prevent static discharges. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Keep only in original packaging. Store in a well-ventilated place. Keep away from sources of heating, ignition and direct sunlight.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value	Note
n-butyl acetate (CAS: 123-86-4)	OEL 8 hours	241 mg/m ³	
	OEL 8 hours	50 ppm	
	OEL 15 minutes	723 mg/m ³	
	OEL 15 minutes	150 ppm	
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	OEL 8 hours	275 mg/m ³	Skin
	OEL 8 hours	50 ppm	
	OEL 15 minutes	550 mg/m ³	
	OEL 15 minutes	100 ppm	

HEADLIGHT UV PROTECTOR

Creation date

10th November 2020

Revision date

Version

2.0

DNEL

2-methoxy-1-methylethyl acetate

Workers / consumers	Route of exposure	Value	Effect	Determining method
Consumers	Oral	1.67 mg/kg	Systemic chronic effects	
Consumers	Inhalation	33 mg/m ³	Systemic chronic effects	
Workers	Inhalation	275 mg/m ³	Systemic chronic effects	
Consumers	Dermal	54.8 mg/kg	Systemic chronic effects	
Workers	Dermal	153.5 mg/kg	Systemic chronic effects	
Consumers	Inhalation	33 mg/m ³	Local chronic effects	

hydrocarbons, C9, aromatics

Workers / consumers	Route of exposure	Value	Effect	Determining method
Consumers	Oral	11 mg/kg	Systemic chronic effects	
Consumers	Inhalation	32 mg/m ³	Systemic chronic effects	
Consumers	Dermal	11 mg/kg	Systemic chronic effects	
Workers	Inhalation	150 mg/m ³	Systemic chronic effects	
Workers	Dermal	25 mg/kg	Systemic chronic effects	

n-butyl acetate

Workers / consumers	Route of exposure	Value	Effect	Determining method
Consumers	Inhalation	300 mg/m ³	Local acute effects	
Workers	Inhalation	600 mg/m ³	Local acute effects	
Consumers	Inhalation	300 mg/m ³	Systemic acute effects	
Workers	Inhalation	600 mg/m ³	Systemic acute effects	
Consumers	Inhalation	35.7 mg/m ³	Local chronic effects	
Workers	Inhalation	300 mg/m ³	Local chronic effects	
Consumers	Inhalation	35.7 mg/m ³	Systemic chronic effects	
Workers	Inhalation	300 mg/m ³	Systemic chronic effects	
Consumers	Oral	2 mg/kg bw/day	Systemic acute effects	
Consumers	Oral	2 mg/kg bw/day	Systemic chronic effects	
Consumers	Dermal	6 mg/kg bw/day	Systemic acute effects	
Consumers	Dermal	6 mg/kg bw/day	Systemic chronic effects	
Workers	Dermal	11 mg/kg bw/day	Systemic chronic effects	

PNEC

2-methoxy-1-methylethyl acetate

Route of exposure	Value	Determining method
Freshwater environment	0.635 mg/l	
Seawater	0.0635 mg/l	
Freshwater sediment	3.29 mg/kg	
Sea sediments	0.329 mg/kg	
Microorganisms in wastewater treatment plants	100 mg/l	
Soil (agricultural)	0.29 mg/kg	

HEADLIGHT UV PROTECTOR

Creation date	10th November 2020	Version	2.0
Revision date			

2-methoxy-1-methylethyl acetate

Route of exposure	Value	Determining method
Water (intermittent release)	6.35 mg/l	

n-butyl acetate

Route of exposure	Value	Determining method
Freshwater environment	0.18 mg/l	
Seawater	0.018 mg/l	
Freshwater sediment	0.981 mg/kg	
Water (intermittent release)	0.36 mg/l	
Soil (agricultural)	0.0903 mg/kg	
Microorganisms in wastewater treatment plants	35.6 mg/l	
Sea sediments	0.0981 mg/kg	

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. Remove contaminated clothes. Contaminated skin should be washed thoroughly. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Tightly sealed goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. Category III. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: Wear category I professional long-sleeved overalls and safety footwear.

Respiratory protection

Use a mask with filter when the exposition limits of the substances are exceeded or at the place with insufficient ventilation. Filter A. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. The protection provided by masks is in any case limited.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
physical state	liquid at 20 °C
color	colourless
Odour	characteristic
Odour threshold	data not available
pH	data not available
Melting point/freezing point	data not available
Initial boiling point and boiling range	130 °C
Flash point	35 °C
Evaporation rate	data not available
Flammability (solid, gas)	data not available
Upper/lower flammability or explosive limits	
flammability limits	data not available
explosive limits	data not available
Vapour pressure	data not available
Vapour density	data not available

HEADLIGHT UV PROTECTOR

Creation date	10th November 2020	Version	2.0
Revision date			

Relative density	0.9
Solubility(ies)	
solubility in water	insoluble
solubility in fats	data not available
solubility in organic solvents	soluble
Partition coefficient: n-octanol/water	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
Viscosity	data not available
Explosive properties	data not available
Oxidising properties	data not available
data not available	

9.2. Other information

Density	data not available
ignition temperature	data not available
content of organic solvents (VOC)	100 %
Max. VOC content in the product in its ready to use condition	900 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

When used in the standard way, there is not any dangerous reaction with other substances.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Vapours mixed up with air can be explosive.

10.4. Conditions to avoid

Protect against overheating. Take action to prevent static discharges. Remove all ignition sources.

10.5. Incompatible materials

not available

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	8530 mg/kg		Rat	
Dermal	LD ₅₀	>5000 mg/kg		Rat	
Inhalation	LC ₅₀	>10.6 mg/l	6 hour	Rat	

hydrocarbons, C9, aromatics

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	>8 ml/kg bw		Rat	
Dermal	LD ₅₀	>3160 mg/kg		Rabbit	

HEADLIGHT UV PROTECTOR

Creation date 10th November 2020

Revision date Version 2.0

hydrocarbons, C9, aromatics

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Inhalation	LC ₅₀	>6193 mg/m ³		Rat	

n-butyl acetate

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	>6400 mg/kg		Rat	
Dermal	LD ₅₀	>5000 mg/kg		Rabbit	
Inhalation	LC ₅₀	21.1 mg/l	4 hour	Rat	

Skin corrosion/irritation

Based on available data the classification criteria are not met.

Serious eye damage/irritation

Based on available data the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information
12.1. Toxicity
Acute toxicity

Harmful to aquatic life with long lasting effects.

2-methoxy-1-methylethyl acetate

Parameter	Value	Time of exposure	Species	Environment
LC ₅₀	100 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	
EC ₅₀	450 mg/l	48 hour	Daphnia (Daphnia magna)	

HEADLIGHT UV PROTECTOR

Creation date 10th November 2020

Revision date

Version

2.0

hydrocarbons, C9, aromatics

Parameter	Value	Time of exposure	Species	Environment
EC ₅₀	3.2 mg/l	48 hour	Daphnia (Daphnia magna)	
EC ₅₀	2.9 mg/l	72 hour	Algae (Pseudokirchneriella subcapitata)	
LC ₅₀	9.2 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	

n-butyl acetate

Parameter	Value	Time of exposure	Species	Environment
LC ₅₀	18 mg/l	96 hour	Fishes (Pimephales promelas)	
EC ₅₀	44 mg/l	48 hour	Daphnia (Daphnia magna)	
EC ₅₀	397 mg/l	72 hour	Algae (Pseudokirchneriella subcapitata)	

Chronic toxicity

2-methoxy-1-methylethyl acetate

Parameter	Value	Time of exposure	Species	Environment
NOEC	47.5 mg/l	14 day	Fishes (Oncorhynchus mykiss)	
NOEC	>100 mg/l	21 day	Daphnia (Daphnia magna)	
NOEC	>1000 mg/l	96 hour	Algae (Selenastrum capricornutum)	

12.2. Persistence and degradability
Biodegradability

2-methoxy-1-methylethyl acetate

Parameter	Value	Time of exposure	Environment	Result
	>10000 mg/l			Biodegradable
	83 %	28 day		

n-butyl acetate

Parameter	Value	Time of exposure	Environment	Result
	1000-10000 mg/l			Biodegradable
	83 %	28 day		

Not available.

12.3. Bioaccumulative potential

HEADLIGHT UV PROTECTOR

Creation date

10th November 2020

Revision date

Version

2.0

2-methoxy-1-methylethyl acetate

Parameter	Value	Time of exposure	Species	Environment	Surrounding temperature [°C]
Kow	1.2				

n-butyl acetate

Parameter	Value	Time of exposure	Species	Environment	Surrounding temperature [°C]
Kow	2.3				
BCF	15.3				

Not available.

12.4. Mobility in soil

n-butyl acetate

Parameter	Value	Environment	Surrounding temperature
K(soil-water)	<3		

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances *

Packaging waste type code

15 01 10 packaging containing residues of or contaminated by hazardous substances *

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number

UN 1993

14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. (n-butyl acetate; 2-methoxy-1-methylethyl acetate)

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

III - substances presenting low danger

14.5. Environmental hazards

No.

HEADLIGHT UV PROTECTOR

Creation date	10th November 2020	Version	2.0
Revision date			

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not available


Additional information

Special instructions: A3

Hazard identification No.

UN number

Safety signs



3

**Road transport - ADR**

Limited quantities

5 L

Transport category

3

Tunnel restriction code

(D/E)

Air transport - ICAO/IATA

Packaging instructions passenger

355

Cargo packaging instructions

366

Marine transport - IMDG

EmS (emergency plan)

F-E, S-E

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

15.2. Chemical safety assessment

not available

SECTION 16: Other information**A list of standard risk phrases used in the safety data sheet**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331	Do NOT induce vomiting.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.

HEADLIGHT UV PROTECTOR

Creation date	10th November 2020	Version	2.0
Revision date			

A list of additional standard phrases used in the safety data sheet

EUH066 Repeated exposure may cause skin dryness or cracking.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
DNEL	Derived no-effect level
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
IC ₅₀	Concentration causing 50% blockade
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LOAEC	Lowest observed adverse effect concentration
LOAEL	Lowest observed adverse effect level
log K _{ow}	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution From Ships
NOAEC	No observed adverse effect concentration
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
NOEL	No observed effect level
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted no-effect concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Aquatic Chronic	Hazardous to the aquatic environment (chronic)

HEADLIGHT UV PROTECTOR

Creation date	10th November 2020	Version	2.0
Revision date			

Asp. Tox.	Aspiration hazard
Flam. Liq.	Flammable liquid
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 2.0 replaces the SDS version from 30th July 2015. Changes were made in sections 2, 3, 8, 9, 11, 12, 15 and 16.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.