

Date of issue: 3.5.2016	Trade name:	Page: 1/10
Reviewed on:	IMPREGNATION EXPERT	Version: 1.0

1. Section 1. Identification of the substance/mixture and of the company/undertaking:

- 1.1. Product identifier:
Trade name: **IMPREGNATION EXPERT**
Product code: **R 34060**
- 1.2. Relevant identified uses of the substance or mixture and uses advised against:
Uses of the mixture: Spray impregnation for textiles.
For professional and industrial use only.
Uses advised against: Not known.
- 1.3. Details of the supplier of the safety data sheet:
Identification of manufacturer/Supplier:
RETECH, s.r.o.
Vackova 1541/4
150 00 Praha 5 - Stodůlky
Telephone number/Fax: +420 327 596 128, +420 327 596 428
E-mail: info@retech.cz
- 1.4. Emergency telephone number: RETECH, Suchdol 212, 285 02 Suchdol u Kutné Hory, Czech Republic
Telephone number: +420 327 596 128 (7.30-16.00 hour)
Toxikologické informační středisko (Toxicology information centre),
Na bojišti 1, 128 08 PRAHA 2, Czech Republic
Telephone number: +420 224 919 293, +420 224 915 402 (24 hours a day)

2. Section 2. Hazard identification:

- 2.1. Classification of the substance or mixture:
Classification according to Regulation (EC) No 1272/2008 [CLP]:
Flam. Aerosol 1 H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2. Label elements:
Labelling according to Regulation (EC) No 1272/2008 [CLP]:



Signal Word: Danger

Hazard Statements:

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/eye protection.

Safety Data Sheet

According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue: 3.5.2016	Trade name:	Page: 2/10
Reviewed on:	IMPREGNATION EXPERT	Version: 1.0

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with national regulation.

Contained dangerous substances:

CAS 67-63-0 Propan-2-ol;

EC 927-510-4 hydrocarbons, C7, n-alkanes, isoalkanes, cyclics;

EC 921-024-6 hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane;

CAS 108-21-4 isopropyl acetate

- 2.3. Other hazards: Buildup of explosive mixtures possible without sufficient ventilation.
Results of PBT and vPvB assessment: Not applicable.

3. Section 3. Composition/information on ingredients:

3.2. Mixtures:

Description of the mixture: Mixture of active ingredients with propellants

Hazardous ingredients:

CAS: 75-28-5 EINECS: 200-857-2 Reg. nr.: 01-2119485395-27	Isobutane (containing < 0.1 % butadiene) Flam. Gas 1, H220; Press. Gas C, H280	25 - 50 %
CAS: 74-98-6 EINECS: 200-827-9 Reg. nr.: 01-2119486944-21	Propane Flam. Gas 1, H220; Press. Gas C, H280	10 - 20 %
CAS: 67-63-0 EINECS: 200-661-7 Reg. nr.: 01-2119457558-25	Propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10 - 20 %
EC-nr.: 927-510-4 Reg. nr.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	10 - 20 %
EC-nr.: 921-024-6 Reg. nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	10 - 20 %
CAS: 106-97-8 EINECS: 203-448-7 Reg. nr.: 01-2119474691-32	Butane (containing < 0.1 % butadiene) Flam. Gas 1, H220; Press. Gas C, H280	2.5 - 10 %
CAS: 108-21-4 EINECS: 203-561-1	Isopropyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	2.5 - 10 %
CAS: 123-86-4 EINECS: 204-658-1 Reg. nr.: 01-2119485493-29	Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5 - 10 %

For full text of H-statements: see SECTION 16.

4. Section 4. First aid measures:

4.1. Description of first aid measures:

- General notes: When in doubt or if symptoms are observed, get medical advice.
After inhalation: Move affected person to fresh air and keep at rest.
If experiencing respiratory symptoms, call for a doctor.
After skin contact: Wash immediately with plenty of water and soap and rinse thoroughly.
Take off immediately all contaminated clothing.
After eye contact: Rinse opened eye for several minutes under running water.
Remove contact lenses, if present and easy to do. Continue rinsing.

Safety Data Sheet

According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue: 3.5.2016	Trade name:	Page: 3/10
Reviewed on:	IMPREGNATION EXPERT	Version: 1.0

After swallowing:	Get medical attention if any discomfort continues. Do not induce vomiting.
4.2. Most important symptoms and effects, both acute and delayed:	Get medical attention if any discomfort continues. Breathing difficulties, headaches, nausea, dizziness, cough
4.3. Indication of any immediate medical attention and special treatment needed:	If swallowed or in case of vomiting, danger of entering the lungs. Subsequent observation for pneumonia and pulmonary oedema.

5. Section 5. Fire fighting measures:	
5.1. Extinguishing media:	
Suitable extinguishing agents:	Carbon dioxide (CO ₂), extinguishing powder, foam.
Unsuitable extinguishing agents:	Water jet.
5.2. Special hazards arising from the substance or mixture:	Formation of explosive gas-air mixtures is possible. Formation of toxic gases and vapours is possible during heating or in case of fire. Carbon monoxid, carbon dioxide.
5.3. Advice for firefighters:	Wear protective clothing and self-contained breathing apparatus. Cool endangered receptacles with water spray. Dispose contaminated extinguishing water and remains after the fire in accordance with the official regulations.

6. Section 6. Accidental release measures:	
6.1. Personal precautions, protective equipment and emergency procedures:	Wear protective equipment, see Section 8. Keep unprotected person away. Ensure adequate ventilation. Keep away from ignition sources.
6.2. Environmental precautions:	Do not allow to enter sewage system, surface, ground water and soil. Inform respective authorities in case product reaches water course or sewage system.
6.3. Methods and material for containment and cleaning up:	Ensure adequate ventilation. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.
6.4. Reference to other sections:	See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7. Section 7. Handling and storage:	
7.1. Precautions for safe handling:	
Protective measures:	Wear protective equipment, see Section 8. Ensure good ventilation/exhaustion at the workplace. Avoid contact with skin and eyes.
Measures to prevent fire:	Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
7.2. Conditions for safe storage, including any incompatibilities:	
Requirements for storage rooms and vessels:	Store in a cool place. Observe official regulations on storing packagings with pressurized containers.

Safety Data Sheet

According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue: 3.5.2016	Trade name:	Page: 4/10
Reviewed on:	IMPREGNATION EXPERT	Version: 1.0

Technical measures and storage conditions:

Observe official regulations on storing packagings with pressurized containers.

Further information on storage conditions:

Protect from heat and direct sunlight.

7.3. Specific end use(s): No further relevant information available.

8. Section 8. Exposure controls/personal protection:

8.1. Control parameters:

Components with limit values that require monitoring at the workplace:

WEL (United Kingdom): EH40/2005

CAS	Substance	Long-term (8-hr TWA ref. period)		Short-term (15 minute ref. period)		Comments
		ppm	mg/m ³	ppm	mg/m ³	
67-63-0	Propan-2-ol	400	999	500	1250	-
106-97-8	Butane	600	1450	750	1810	Carc, (only applies if Butane contains more than 0.1 % of buta-1,3-diene)
108-21-4	Isopropyl acetate	-	-	200	849	-
123-86-4	Butyl acetate	150	724	200	966	-

OEL (EU): 2000/39/EG, 2006/15/EG, 2009/161/EG

Contains no substances with occupational exposure limit values.

DNEL

67-63-0 Propan-2-ol

Inhalation	Chronic effects systemic	500	mg/m ³	Workers
	Chronic effects systemic	89	mg/m ³	Consumers
Dermal	Chronic effects systemic	888	mg/kg Body weight/day	Workers
	Chronic effects systemic	319	mg/kg Body weight/day	Consumers
Oral	Chronic effects systemic	26	mg/kg Body weight/day	Consumers

Hydrocarbons. C7. n-alkanes. isoalkanes. cyclics

Inhalation	Chronic effects systemic	2085	mg/m ³	Workers
	Chronic effects systemic	447	mg/m ³	Consumers
Dermal	Chronic effects systemic	300	mg/kg Body weight/day	Workers
	Chronic effects systemic	149	mg/kg Body weight/day	Consumers
Oral	Chronic effects systemic	149	mg/kg Body weight/day	Consumers

Hydrocarbons. C6-C7. n-alkanes. isoalkanes. cyclics. <5% n-hexane

Inhalation	Chronic effects systemic	2035	mg/m ³	Workers
	Chronic effects systemic	608	mg/m ³	Consumers
Dermal	Chronic effects systemic	773	mg/kg Body weight/day	Workers
	Chronic effects systemic	699	mg/kg Body weight/day	Consumers
Oral	Chronic effects systemic	699	mg/kg Body weight/day	Consumers

123-86-4 Butyl acetate

Inhalation	Chronic effects systemic	48	mg/m ³	Workers
	Chronic effects systemic	12	mg/m ³	Consumers
Dermal	Chronic effects systemic	7	mg/kg Body weight/day	Workers
	Chronic effects systemic	3.4	mg/kg Body weight/day	Consumers
Oral	Chronic effects systemic	3.4	mg/kg Body weight/day	Consumers

PNEC

67-63-0 Propan-2-ol

Freshwater	140.9	mg/l
Marine water	140.9	mg/l
Intermittent releases	140.9	mg/l
Sewage treatment plants	2251	mg/l
Sediment (freshwater)	552	mg/kg
Sediment (marine water)	552	mg/kg
Soil	28	mg/kg

Safety Data Sheet

According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue: 3.5.2016	Trade name:	Page: 5/10
Reviewed on:	IMPREGNATION EXPERT	Version: 1.0

123-86-4 Butyl acetate

Freshwater	0.18 mg/l
Marine water	0.018 mg/l
Intermittent releases	0.36 mg/l
Sewage treatment plants	35.6 mg/l
Sediment (freshwater)	0.981 mg/kg
Sediment (marine water)	0.0981 mg/kg
Soil	0.0903 mg/kg

Additional information: The lists that were valid during the compilation were as basis.

8.2. Exposure controls:

Technical measures to prevent exposure:

Ensure good ventilation/exhaustion at the workplace.

General protective measures:

Store away from foodstuffs, beverages and feed.

Take off immediately all contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale vapours/spray.

Avoid contact with skin, eyes.

Personal protection equipment:

Respiratory protection:

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device with filter type AX.

During intensive or longer exposure use self-contained breathing apparatus.

Eye protection:

Tightly sealed goggles.

Hand protection:

Protective gloves

The glove material must be impermeable and resistant against the product / substance / preparation.

Recommend material of gloves: nitrilrubber

Recommended thickness of the material: ≥ 0.7 mm

Penetration time of glove material: ≥ 240 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Skin protection:

Protective clothing.

9. Section 9. Physical and chemical properties:

9.1. Information on basic physical and chemical properties:

Form:	Aerosol
Colour:	Colourless
Odour:	Alcohol-like
Odour threshold:	Not determined.
Value pH at 20 °C:	Not determined.
Melting point/freezing point:	Not determined.
Initial boiling point/boiling range:	Not determined.
Flash point:	Not determined.
Evaporation rate:	Not determined.
Flammability (solid, gas):	Not determined.
Explosive properties:	The product is not explosive. However, formation of explosive air/steam mixtures is possible.
Explosive limits:	
– lower:	Not determined.
– upper:	Not determined.
Vapour pressure at 20°C:	Not determined.
Vapour density at 20 °C:	Not determined.
Density at 20°C:	0.636 g/cm ³
Relative density:	Not determined.
Solubility in/miscibility:	Partly miscible with water.

Safety Data Sheet

According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue: 3.5.2016	Trade name:	Page: 6/10
Reviewed on:	IMPREGNATION EXPERT	Version: 1.0

Partition coefficient (n-octanol/water): Not determined.
 Ignition temperature: > 200 °C
 Decomposition temperature: Not determined.
 Self-ignition temperature: Not determined.
 Viscosity: Not determined.
 Oxidising properties: Not determined.

9.2. Other information:
 VOC: 626.2 g/l
 Organic solvent: 98.5 %

10. Section 10. Stability and reactivity:

10.1. Reactivity: No further relevant information available.
 10.2. Chemical stability: No decomposition if used according to specifications.
 10.3. Possibility of hazardous reactions:
 No dangerous reactions known.
 10.4. Conditions to avoid: No further relevant information available.
 10.5. Incompatible materials: No further relevant information available.
 10.6. Hazardous decomposition products:
 Carbon monoxide, carbon dioxide, aldehydes.

11. Section 11. Toxicological information:

11.1. Information on toxicological effects:
 Acute toxicity: Based on available data, the classification criteria are not met.

ATE

Inhalative	LC50/4 h	Rat	116 mg/l
------------	----------	-----	----------

75-28-5 Isobutane

Inhalative	LC50/4 h	Rat	>50 mg/l
------------	----------	-----	----------

74-98-6 Propane

Inhalative	LC50/4 h	Rat	20 mg/l
------------	----------	-----	---------

67-63-0 Propan-2-ol

Oral	LD50	Rat	5045 mg/kg
Dermal	LD50	Rabbit	12800 mg/kg
Inhalative	LC50/4 h	Rat	30 mg/l

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Oral	LD50	Rat	>5840 mg/kg
Dermal	LD50	Rat	>2920 mg/kg
Inhalative	LC50/4 h	Rat	>23.3 mg/l

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	Rat	>5840 mg/kg
Dermal	LD50	Rat	>2920 mg/kg
Inhalative	LC50/4 h	Rat	<25.2 mg/l

106-97-8 Butane

Inhalative	LC50/4 h	Rat	658 mg/l
------------	----------	-----	----------

108-21-4 Isopropyl acetate

Oral	LD50	Rat	3000 mg/kg
------	------	-----	------------

123-86-4 Butyl acetate

Oral	LD50	Rat	13100 mg/kg
Dermal	LD50	Rabbit	>5000 mg/kg
Inhalative	LC50/4 h	Rat	>21 mg/l

Skin corrosion/irritation: Causes skin irritation.
 Serious eye damage/irritation: Causes serious eye irritation.
 Respiratory or skin sensitization:
 Based on available data, the classification criteria are not met.
 Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Safety Data Sheet

According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue: 3.5.2016	Trade name:	Page: 7/10
Reviewed on:	IMPREGNATION EXPERT	Version: 1.0

Carcinogenicity:	Based on available data, the classification criteria are not met.
Reproductive toxicity:	Based on available data, the classification criteria are not met.
STOT - single exposure:	May cause drowsiness or dizziness.
STOT - repeated exposure:	Based on available data, the classification criteria are not met.
Aspiration hazard:	Based on available data, the classification criteria are not met.
Other information:	No further relevant information available.

12. Section 12. Ecological information:

12.1. Toxicity:

Aquatic toxicity:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Invertebrates:	EC50/48 h	Daphnia magna	3 mg/l
----------------	-----------	---------------	--------

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Invertebrates:	EC50/48 h	Daphnia magna	3 mg/l
----------------	-----------	---------------	--------

12.2. Persistence and degradability: No further relevant information available.

12.3. Bioaccumulative potential: No further relevant information available.

12.4. Mobility in soil: No further relevant information available.

Additional ecological information:

General notes: Water danger class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow to enter water courses, ground water or drains.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms.

12.5. Results of PBT and vPvB assessment:

PBT Not applicable.

vPvB Not applicable.

12.6. Other adverse effects: No further relevant information available.

13. Section 13. Disposal considerations:

13.1. Waste treatment methods:

Product disposal: Must not be disposed together with household garbage.

Do not allow product to reach sewage system.

European Waste Catalogue:

16 03 05* organic wastes containing hazardous substances

(*hazardous waste)

Packagings disposal:

Disposal must be made according to official regulations. Incineration is the recommended method of disposal.

European Waste Catalogue:

15 01 11* metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers

(*hazardous waste)

Other disposal recommendations:

Disposal must be made according to official regulations.

The final decisions on the appropriate waste management method, in line with regional, national and European legislation, and possible adaptation to local conditions, remains the responsibility of the waste treatment operator.

14. Section 14. Transport information:

14.1. UN number:

ADR, IMDG, IATA UN 1950

14.2. UN proper shipping name:

ADR 1950 AEROSOLS




IMDG AEROSOLS

IATA AEROSOLS, flammable

Safety Data Sheet

According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue: 3.5.2016	Trade name:	Page: 8/10
Reviewed on:	IMPREGNATION EXPERT	Version: 1.0

14.3. Transport hazard class(es): ADR	
Class	2 5F Gases
Hazard label	2.1
IMDG	
Class	2.1
Hazard label	2.1
IATA	
Class	2.1
Hazard label	2.1
14.4. Packing group: ADR, IMDG, IATA	Void
14.5. Environmental hazards: Marine pollutant:	NO
14.6. Special precautions for user:	Warning: gases
EMS Number:	F-D, S-U
Danger Code (Kemler):	-
Stowage Code:	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code:	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code:	Not applicable
ADR	
Limited quantities (LQ):	1L
Excepted quantities (EQ):	Code: E0 Not permitted as Excepted Quantity
Transport category:	2
Tunnel restriction code:	D
IMDG	
Limited quantities (LQ):	1L
Excepted quantities (EQ):	Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950, AEROSOLS, 2.1
15. Section 15. Regulatory information:	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture:	
Used legislation:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals, as amended (REACH) Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures, as amended (CLP) Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, as amended Commission Decision 2000/532/EC establishing a list of wastes, as amended

Safety Data Sheet

According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue: 3.5.2016	Trade name:	Page: 9/10
Reviewed on:	IMPREGNATION EXPERT	Version: 1.0

Council Directive 89/686/EEC on the approximation of the laws of the Member States relating to personal protective equipment, as amended
 Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended
 Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
 Commission Directive 2006/15/EC establishing a second list of indicative occupational exposure limit values
 Commission Directive 2009/161/EU establishing a third list of indicative occupational exposure limit values
 Directive 2004/42/CE of the European Parliament and of the Council on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC, as amended

15.2. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16. Section 16. Other information:

Relevant H-statements (Section 3):

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- EC-nr.: EINECS and ELINCS Number
- EC50: Median effective concentration to 50% of a population
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- IATA: International Air Transport Association
- IMDG: International Maritime Code for Dangerous Goods
- LC50: Median concentration lethal to 50 % of a test population
- LD50: Median dose lethal to 50 % of a test population
- OEL: Occupational Exposure Limit
- PBT: Persistent, Bioaccumulative, Toxic
- Reg.nr.: Registration number
- VOC: Volatile Organic Compounds
- vPvB: Very Persistent, Very Bioaccumulative
- WEL: Workplace exposure limits
- Aquatic Chronic 2: Hazardous to the aquatic environment, category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment, category 3
- Asp. Tox. 1: Aspiration hazard, category 1
- Eye Irrit. 2: Serious eye irritation, category 2
- Flam. Aerosol 1: Flammable aerosol, category 1
- Flam. Gas 1: Flammable gas, category 1
- Flam. Liq. 2: Flammable liquid, category 2
- Flam. Liq. 3: Flammable liquid, category 3
- Press. Gas: Gases under pressure
- Skin Irrit. 2: Skin irritation, category 2
- STOT SE 3: Specific target organ toxicity — single exposure, category 3

Safety Data Sheet

According to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

Date of issue:	3.5.2016	Trade name:	Page: 10/10
Reviewed on:		IMPREGNATION EXPERT	Version: 1.0

The information contained herein is based on our best knowledge and the present legislation. Further, the Safety Data Sheet has been elaborated on the basis of the original Safety Data Sheet provided by the manufacturer. These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

***Compared to the last version the data has been changed.**