

I. C. CLEANER

Creation date 08. November 2018
Revision date Version 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture I. C. CLEANER
Number R 50200
Other mixture names I. C. - INJECTION AND CARBURETTOR CLEANER
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
mixture's intended use Cleaning agent.

The use descriptors

- SU 3 Industrial uses: Uses of substances as such or in preparations* at industrial sites
SU 22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PROC 7 Industrial spraying
PROC 11 Non industrial spraying

Disapproved uses of mixture For professional use only.

1.3. Details of the supplier of the safety data sheet
Supplier

- Name or trade name RETECH, s.r.o.
Address Vackova 1541/4, Praha 5 - Stodůlky, 155 00
Czech Republic
Identification number (ID) 25018205
Phone +420327596428
E-mail info@retech.cz
Web address www.retech.com

Competent person responsible for the safety data sheet

- Name RETECH, s.r.o.
E-mail info@retech.cz

1.4. Emergency telephone number

RETECH, Suchdol 212, 285 02 Suchdol u Kutné Hory, Czech Republic; Telephone number: +420 327 596 128 (7.30-16.00 hour)
Poisoning information centre, Na Bojišti 1, Praha, Czech Republic, Tel.: non-stop +420 224 919 293 or +420 224 915 402, Information on health risks only - acute poisoning of humans and animals.

SECTION 2: Hazards identification**2.1. Substance or mixture classification****Classification of the mixture in accordance with Regulation (EC) No 1272/2008**

The mixture is classified as dangerous.

Aerosol 1, H222, H229
Asp. Tox. 1, H304
Skin Irrit. 2, H315
Eye Irrit. 2, H319
Acute Tox. 4, H332
STOT SE 3, H336
Aquatic Chronic 3, H412

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Extremely flammable aerosol. Pressurised container: May burst if heated.

Most serious adverse effects on human health and the environment

Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

I. C. CLEANER

Creation date

08. November 2018

Revision date

Version

1.1

2.2. Label elements**Hazard pictogram****Signal word**

Danger

Hazardous substances

xylene (mixture of isomers)

butanone

Naphtha (petroleum), hydrotreated light

2-butoxyethanol

Hazard statements

- H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P273 Avoid release to the environment.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331 Do NOT induce vomiting.
P403 Store in a well-ventilated place.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container to in accordance with national regulations.

Supplemental information

>=30 % aliphatic hydrocarbons, 15-<30 % aromatic hydrocarbons

2.3. Other hazards

Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

I. C. CLEANERCreation date 08. November 2018
Revision date Version 1.1**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note.
CAS: 1330-20-7 EC: 215-535-7 Registration number: 01-2119488216-32	xylene (mixture of isomers)	25-<50	Flam. Liq. 3, H226 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315	1
CAS: 78-93-3 EC: 201-159-0 Registration number: 01-2119457290-43	butanone	20-<25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	1
CAS: 74-98-6 EC: 200-827-9 Registration number: 01-2119486944-21	propane	10-<25	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	
CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25	propan-2-ol	15-<20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
CAS: 64742-49-0 Registration number: 01-2119473851-33	Naphtha (petroleum), hydrotreated light	15-<20	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411	
CAS: 111-76-2 EC: 203-905-0	2-butoxyethanol	1,0-<2,5	Acute Tox. 4, H302, H312, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319	1

Notes

1 Substance for which exposure limits of Community for working environment exist.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

Symptoms of poisoning may manifest after many hours, medical supervision is necessary for 48 hours after the accident.

Inhalation

Terminate the exposure immediately; move the affected person to fresh air. Keep the affected person warm and at rest. In the event of issues, find medical advice. In case of unconsciousness place patient stably in side position for transportation.

Skin contact

Immediately wash with water and soap and rinse thoroughly.

Eye contact

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. In the event of issues, find medical advice.

Ingestion

DO NOT INDUCE VOMITING! Provide medical treatment.

I. C. CLEANER

Creation date	08. November 2018	Version	1.1
Revision date			

4.2. Most important symptoms and effects, both acute and delayed**Inhalation**

Harmful if inhaled. May cause drowsiness or dizziness.

Skin contact

Causes skin irritation.

Eye contact

Causes serious eye irritation.

Ingestion

not available

4.3. Indication of any immediate medical attention and special treatment needed

not available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

not available

5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide sufficient ventilation. Use personal protective equipment for work. Keep unprotected persons away.

6.2. Environmental precautions

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

6.3. Methods and material for containment and cleaning up

Provide sufficient ventilation. Dispose of the collected material according to the instructions in the section 13. Do not flush with water or aqueous cleansing agents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Do not spray on an open flame or other ignition source. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. No smoking. Take precautionary measures against static discharge. Pressurised container: May burst if heated. Keep away from sources of heating, ignition and direct sunlight. Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Storage class

2B - Aerosols

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

The mixture contains substances for which occupational exposure limits are set.

I. C. CLEANER

Creation date

08. November 2018

Revision date

Version

1.1

European Union

Substance name (component)	Type	Time of exposure	Value	Note	Source
xylene (mixture of isomers) (CAS: 1330-20-7)	OEL	8 hours	221 mg/m ³		EU limits
	OEL	8 hours	50 ppm		
	OEL	Short-term	442 mg/m ³		
	OEL	Short-term	100 ppm		
butanone (CAS: 78-93-3)	OEL	8 hours	600 mg/m ³		EU limits
	OEL	8 hours	200 ppm		
	OEL	Short-term	900 mg/m ³		
	OEL	Short-term	300 ppm		
2-butoxyethanol (CAS: 111-76-2)	OEL	8 hours	98 mg/m ³		EU limits
	OEL	8 hours	20 ppm		
	OEL	Short-term	246 mg/m ³		
	OEL	Short-term	50 ppm		

United Kingdom of Great Britain and Northern Ireland

Substance name (component)	Type	Time of exposure	Value	Note	Source
xylene (mixture of isomers) (CAS: 1330-20-7)	WEL	8 hours	220 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
	WEL	15 minutes	441 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	8 hours	50 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	15 minutes	100 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	

I. C. CLEANER

Creation date

08. November 2018

Revision date

Version

1.1

United Kingdom of Great Britain and Northern Ireland

Substance name (component)	Type	Time of exposure	Value	Note	Source
butanone (CAS: 78-93-3)	WEL	8 hours	600 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
	WEL	15 minutes	899 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	8 hours	200 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	15 minutes	300 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
propan-2-ol (CAS: 67-63-0)	WEL	8 hours	999 mg/m ³		GBR
	WEL	15 minutes	1250 mg/m ³		
	WEL	8 hours	400 ppm		
	WEL	15 minutes	500 ppm		
2-butoxyethanol (CAS: 111-76-2)	WEL	8 hours	123 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	GBR
	WEL	15 minutes	246 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	8 hours	25 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	
	WEL	15 minutes	50 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.	

I. C. CLEANER

Creation date 08. November 2018

Revision date

Version

1.1

DNEL

butanone

Workers / consumers	Route of exposure	Value	Effect	Determining method
Workers	Inhalation	600 mg/m ³	Systemic chronic effects	
Workers	Dermal	1161 mg/kg bw/day	Systemic chronic effects	
Consumers	Inhalation	106 mg/m ³	Systemic chronic effects	
Consumers	Dermal	412 mg/kg bw/day	Systemic chronic effects	
Consumers	Oral	31 mg/kg bw/day	Systemic chronic effects	

Naphtha (petroleum), hydrotreated light

Workers / consumers	Route of exposure	Value	Effect	Determining method
Consumers	Oral	699 mg/kg bw/day	Systemic chronic effects	
Consumers	Dermal	699 mg/kg bw/day	Systemic chronic effects	
Workers	Dermal	773 mg/kg bw/day	Systemic chronic effects	
Consumers	Inhalation	608 mg/m ³	Systemic chronic effects	
Workers	Inhalation	2035 mg/m ³	Systemic chronic effects	

propan-2-ol

Workers / consumers	Route of exposure	Value	Effect	Determining method
Consumers	Oral	26 mg/kg bw/day	Systemic chronic effects	
Consumers	Dermal	319 mg/kg bw/day	Systemic chronic effects	
Workers	Dermal	888 mg/kg bw/day	Systemic chronic effects	
Consumers	Inhalation	89 mg/m ³	Local chronic effects	
Workers	Inhalation	500 mg/kg	Systemic chronic effects	

8.2. Exposure controls

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

Eye/face protection

Tightly sealed goggles.

Skin protection

Hand protection: Solvent resistant gloves. The final selection of the glove material must be carried out on the basis of penetration times, permeation rates and degradation. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Material of gloves: Nitrile rubber, NBR. Penetration time of glove material: The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Other protection: protective workwear.

I. C. CLEANER

Creation date	08. November 2018	Version	1.1
Revision date			

Respiratory protection

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter AX/P2.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	aerosol
Physical state	liquid at 20°C
color	transparent
Odour	characteristic
Odour threshold	data not available
pH	data not available
Melting point/freezing point	data not available
Initial boiling point and boiling range	-44 °C
Flash point	-97 °C
Evaporation rate	data not available
Flammability (solid, gas)	Extremely flammable aerosol.
Upper/lower flammability or explosive limits	
flammability limits	data not available
explosive limits	
bottom	0.7 %
upper	12.0 %
Vapour pressure	5 Bar at 20 °C
Vapour density	data not available
Relative density	data not available
Solubility(ies)	
solubility in water	almost insoluble
solubility in fats	data not available
Partition coefficient: n-octanol/water	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
Viscosity	data not available
Explosive properties	The product does not have explosive properties but can be explosive when blended with air.
Oxidising properties	data not available
data not available	

9.2. Other information

Density	0.745 g/cm ³ at 20 °C
ignition temperature	200 °C
content of organic solvents (VOC)	99.9 %
solid content (dry matter)	0.1 % volume
Max. VOC content in the product in its ready to use condition	745.0 g/l
Product is not selfigniting.	

SECTION 10: Stability and reactivity**10.1. Reactivity**

not available

I. C. CLEANER

Creation date 08. November 2018

Revision date Version 1.1

10.2. Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

not available

10.5. Incompatible materials

not available

10.6. Hazardous decomposition products

Unknown.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

No toxicological data is available for the mixture.

Acute toxicity

Harmful if inhaled.

2-butoxyethanol

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	300 mg/kg		Rabbit	
Oral	LD ₅₀	470 mg/kg		Rat	
Dermal	LD ₅₀	2000 mg/kg		Rabbit	

butanone

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	>2193 mg/kg		Rat	
Dermal	LD ₅₀	>5000 mg/kg		Rabbit	

Naphtha (petroleum), hydrotreated light

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	>5000 mg/kg		Rat	
Dermal	LD ₅₀	>2800 mg/kg		Rabbit	
Inhalation	LC ₅₀	>23 mg/l	4 hour	Rat	

propan-2-ol

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	5840 mg/kg		Rat	
Dermal	LD ₅₀	13900 mg/kg		Rabbit	
Inhalation	LC ₅₀	25000 mg/m ³	6 hour	Rat	

xylene (mixture of isomers)

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	4300 mg/kg		Rat	
Dermal	LD ₅₀	2000 mg/kg		Rabbit	

Skin corrosion/irritation

Causes skin irritation.

I. C. CLEANER

Creation date

08. November 2018

Revision date

Version

1.1

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

Harmful to aquatic life with long lasting effects.

2-butoxyethanol

Parameter	Value	Time of exposure	Species	Environment
LC ₅₀	1490 mg/l	96 hour	Fishes (Lepomis macrochirus)	

butanone

Parameter	Value	Time of exposure	Species	Environment
EC ₅₀	308 mg/l	48 hour	Invertebrates (Daphnia magna)	
LC ₅₀	2993 mg/l	96 hour	Fishes (Pimephales promelas)	

Naphtha (petroleum), hydrotreated light

Parameter	Value	Time of exposure	Species	Environment
EL ₅₀	10-30 mg/l	72 hour	Algae (Pseudokirchneriella subcapitata)	
EC ₅₀	3 mg/l	48 hour	Invertebrates (Daphnia magna)	
LL ₅₀	>13.4 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	

I. C. CLEANER

Creation date 08. November 2018

Revision date

Version

1.1

Naphtha (petroleum), hydrotreated light

Parameter	Value	Time of exposure	Species	Environment
LOEC	0.32 mg/l	21 day	Invertebrates (Daphnia magna)	
NOEC	0.17 mg/l	21 day	Invertebrates (Daphnia magna)	
NOELR	10 mg/l	72 hour	Algae (Pseudokirchneriella subcapitata)	

propan-2-ol

Parameter	Value	Time of exposure	Species	Environment
LC ₅₀	9714 mg/l	24 hour	Invertebrates (Daphnia magna)	
LC ₅₀	9640 mg/l	96 hour	Fishes (Pimephales promelas)	
LOEC	1000 mg/l	8 day	Algae	

xylene (mixture of isomers)

Parameter	Value	Time of exposure	Species	Environment
EC ₅₀	3.2-9.5 mg/l	48 hour	Invertebrates (Daphnia magna)	
LC ₅₀	8.9-16.4 mg/l	96 hour	Fishes (Pimephales promelas)	

12.2. Persistence and degradability

Data not available.

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Other adverse effects

Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water. Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations
13.1. Waste treatment methods

Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste.

Legislation of waste

Council Directive 75/442/EEC on waste, as amended. Decree No. 383/2001 Coll., on details regarding waste handling as amended. Decree No. 93/2016 Coll., (waste catalogue) as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

16 03 05 organic wastes containing dangerous substances

I. C. CLEANERCreation date 08. November 2018
Revision date Version 1.1**Packaging waste type code**

15 01 11 metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

SECTION 14: Transport information**14.1. UN number**

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not available

14.5. Environmental hazards

No

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not available


Additional information

Hazard identification No.

UN number

Classification code

Safety signs

 (Kemler Code)
1950

5F

2.1

**Road transport ADR**

Tunnel restriction code

(D)

Marine transport - IMDG

EmS (emergency plan)

F-D, S-U

Marine pollution

No

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended. The Act No. 350/2011 Coll., on Chemical Substances and Chemical Preparations as amended (the Chemical Act). Decree No. 80/2014 Coll., amending the Decree No. 194/2001 Coll., laying down technical requirements for aerosol sprays as amended. Decree No. 432/2003 Coll., laying down conditions for assigning categories to individual jobs, limit values of indices from biological exposure tests, conditions for the sampling of biological materials for biological exposure and the particulars of the reports on work with asbestos and biological agents as amended. REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents, as amended.

I. C. CLEANER

Creation date	08. November 2018	Version	1.1
Revision date			

15.2. Chemical safety assessment

not available

SECTION 16: Other information**A list of standard risk phrases used in the safety data sheet**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H312+H332	Harmful in contact with skin or if inhaled.

Guidelines for safe handling used in the safety data sheet

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P211	Do not spray on an open flame or other ignition source.
P273	Avoid release to the environment.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331	Do NOT induce vomiting.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with national regulations.
P403	Store in a well-ventilated place.

A list of additional standard phrases used in the safety data sheet

EUH 066	Repeated exposure may cause skin dryness or cracking.
---------	---

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
DNEL	Derived no-effect level
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances

I. C. CLEANER

Creation date	08. November 2018	Version	1.1
Revision date			

EmS	Emergency plan
EU	European Union
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
IC ₅₀	Concentration causing 50% blockade
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LOAEC	Lowest observed adverse effect concentration
LOAEL	Lowest observed adverse effect level
log K _{ow}	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution From Ships
NOAEC	No observed adverse effect concentration
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
NOEL	No observed effect level
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted no-effect concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative

Acute Tox.	Acute toxicity
Aerosol	Flammable aerosol
Aquatic Chronic	Hazardous to the aquatic environment
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Press. Gas	Gases under pressure
Skin Irrit.	Skin irritation
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

I. C. CLEANER

Creation date 08. November 2018

Revision date Version 1.1

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. The Act No. 350/2011 Coll., on Chemical Substances and Chemical Preparations as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

2, 3, 8, 11, 12, 15, 16

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.