

METALLIC FILLER

Creation date	23rd March 2021	Version	3.0
Revision date			

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture METALLIC FILLER
Number mixture
1 35071
UFI HF22-4DWF-P00D-QSUP
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
Polyester putty.
Mixture uses advised against
For professional use only.
- 1.3. Details of the supplier of the safety data sheet**
Supplier
Name or trade name RETECH, s.r.o.
Address Vackova 1541/4, Praha 5 - Stodůlky, 155 00
Czech Republic
Identification number (CRN) 25018205
VAT Reg No CZ25018205
Phone +420327596428
E-mail info@retech.cz
Web address www.retech.com
Competent person responsible for the safety data sheet
Name RETECH, s.r.o.
E-mail info@retech.cz
- 1.4. Emergency telephone number**
European emergency number: 112

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Flam. Liq. 3, H226
Skin Irrit. 2, H315
Eye Irrit. 2, H319
Repr. 2, H361d
STOT RE 1, H372
Aquatic Chronic 3, H412

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Flammable liquid and vapour.

Most serious adverse effects on human health and the environment

Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

- 2.2. Label elements**
Hazard pictogram



Signal word
Danger

METALLIC FILLER

Creation date	23rd March 2021	Version	3.0
Revision date			

Hazardous substances

styrene

Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-026-00-0 CAS: 100-42-5 EC: 202-851-5 Registration number: 01-2119457861-32	styrene	<12,5	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 Repr. 2, H361d STOT RE 1, H372 Aquatic Chronic 3, H412	
Index: 030-011-00-6 CAS: 7779-90-0 EC: 231-944-3 Registration number: 01-2119485044-40-0000	trizinc bis(orthophosphate)	1-5	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures

Symptoms of poisoning may manifest after many hours, medical supervision is necessary for 48 hours after the accident. Remove contaminated clothes immediately. Terminate the exposure immediately; move the affected person to fresh air. In case of unconsciousness place patient stably in side position for transportation.

METALLIC FILLER

Creation date

23rd March 2021

Revision date

Version

3.0

If inhaled

Transfer the affected person to the fresh air and ensure calm environment for body and mind. If required, provide artificial respiration. In the event of issues, find medical advice. In case of unconsciousness place patient stably in side position for transportation.

If on skin

Immediately wash with water and soap and rinse thoroughly. Provide medical treatment if skin irritation persists.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. In the event of issues, find medical advice.

If swallowed

DO NOT INDUCE VOMITING! Rinse out the mouth with water and provide 2-5 dL of water. Provide medical treatment.

4.2. Most important symptoms and effects, both acute and delayed**If inhaled**

Dizziness, headaches, nausea. Cough. Profuse sweating.

If on skin

Causes skin irritation.

If in eyes

Causes serious eye irritation.

If swallowed

Nausea.

4.3. Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide, powder, water spray jet. Fight larger fires with water spray or alcohol resistant foam.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise.

5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing. Do not inhale gases and vapours. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water. Dispose of contaminated extinguishing water and remains after the fire in accordance with the official regulations.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide sufficient ventilation. Flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Keep unprotected persons away.

6.2. Environmental precautions

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. Provide sufficient ventilation.

6.4. Reference to other sections

See the Section 7, 8 and 13.

METALLIC FILLER

Creation date

23rd March 2021

Revision date

Version

3.0

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Store in tightly closed containers in a cool, dry place intended for this purpose. Keep away from sources of heating, ignition and direct sunlight. Prevent formation of aerosols. Ensure good interior ventilation, especially at floor level (Fumes are heavier than air). Use only outdoors or in a well-ventilated area. Keep away from heat, open flames. No smoking. Take precautionary measures against static discharge.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Keep only in original packaging. The floor must be impermeable. Do not expose to sunlight. Do not expose to temperatures exceeding 50 °C. Keep container tightly closed. Keep cool. Do not store together with acids. Do not store together with alkalis (caustic solutions). Do not store together with oxidising agent. Do not store together with food, drink and animal feed.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

DNEL

styrene

Workers / consumers	Route of exposure	Value	Effect	Determining method
Workers	Inhalation	85 mg/m ³	Systemic chronic effects	
Workers	Inhalation	289-306 mg/m ³	Systemic acute effects	
Workers	Dermal	406 mg/kg bw/day	Systemic chronic effects	
Consumers	Inhalation	10.2 mg/m ³	Systemic chronic effects	
Consumers	Inhalation	174.25-182.75 mg/m ³	Systemic acute effects	
Consumers	Dermal	343 mg/kg bw/day	Systemic chronic effects	
Consumers	Oral	2.1 mg/kg bw/day	Systemic chronic effects	

trizinc bis(orthophosphate)

Workers / consumers	Route of exposure	Value	Effect	Determining method
Workers	Inhalation	5 mg/m ³	Systemic chronic effects	
Workers	Dermal	83 mg/kg bw/day	Systemic chronic effects	
Consumers	Inhalation	2.5 mg/m ³	Systemic chronic effects	
Consumers	Dermal	83 mg/kg bw/day	Systemic chronic effects	
Consumers	Oral	0.83 mg/kg bw/day	Systemic chronic effects	

PNEC

styrene

Route of exposure	Value	Determining method
Freshwater environment	0.028 mg/l	
Water (intermittent release)	0.04 mg/l	
Seawater	0.014 mg/l	
Microorganisms in wastewater treatment plants	5 mg/l	

METALLIC FILLER

Creation date 23rd March 2021

Revision date Version 3.0

styrene

Route of exposure	Value	Determining method
Freshwater sediment	0.614 mg/kg of dry substance of sediment	
Sea sediments	0.307 mg/kg of dry substance of sediment	
Sea sediments	0.2 mg/kg of dry substance of soil	

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. Take off contaminated clothing. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest. Prevent contact with skin and eyes. Do not inhale gases and vapours. Do not inhale aerosols. Apply solvent resistant skin cream before starting work. Use skin protection cream for skin protection. Do not eat, drink, smoke and sniff during work. Do not store together with food, drink and animal feed.

Eye/face protection

Tightly sealed goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. Material of gloves: Fluororubber. Butyl rubber. Penetration time of glove material: ≤ 480 min. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. After use of gloves apply skin-cleaning agents and skin cosmetics. Not suitable are gloves made of the following materials: leather gloves, strong material gloves. Nitrile rubber, NBR. Rubber (natural, latex). Chloroprene rubber. Neoprene. Other protection: protective workwear.

Respiratory protection

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter A/P2.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	liquid
Color	grey
Odour	characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	145 °C
Flammability	data not available
Lower and upper explosion limit	
bottom	1,2 %
upper	8,9 %
Flash point	32 °C
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	data not available
Kinematic viscosity	data not available
Solubility in water	almost insoluble
Solubility in fats	data not available
Solubility solubility in organic solvents	soluble
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	6 hPa at 20 °C
Density and/or relative density	
Density	2,01 g/cm ³ at 20 °C
Form	liquid: viscous
data not available	

METALLIC FILLER

Creation date	23rd March 2021	Version	3.0
Revision date			

9.2. Other information

Evaporation rate	non-applicable
Ignition temperature	480 °C
Explosive properties	The product does not have explosive properties but can be explosive when blended with air.
Content of organic solvents (VOC)	11,2 %
Solid content (dry matter)	88 % volume
Product is not selfigniting.	

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Exothermic polymerization. Reacts with peroxides and other radical forming substances. Reacts with strong alkali. Reacts with acids.

10.4. Conditions to avoid

not available

10.5. Incompatible materials

not available

10.6. Hazardous decomposition products

Not developed under normal uses.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

METALLIC FILLER

Route of exposure	Parameter	Method	Value	Time of exposure	Species	Sex	Determining method
Inhalation	LC ₅₀		104 mg/l	4 hour			Estimated value

styrene

Route of exposure	Parameter	Method	Value	Time of exposure	Species	Sex	Determining method
Oral	LD ₅₀		>2000 mg/kg		Rat		
Dermal	LD ₅₀	OECD 402	>2000 mg/kg		Rat		
Inhalation	LC ₅₀		11.8 mg/l	4 hour	Rat		
Inhalation	LC ₅₀		9.5 mg/m ³	4 hour	Mouse		
Inhalation	NOAEC		4.34 mg/l		Rat		

trizinc bis(orthophosphate)

Route of exposure	Parameter	Method	Value	Time of exposure	Species	Sex	Determining method
Oral	LD ₅₀		>5000 mg/kg		Rat		
Inhalation	LC ₅₀		>5.7 mg/l	4 hour	Rat		

Skin corrosion/irritation

Causes skin irritation.

METALLIC FILLER

Creation date 23rd March 2021
Revision date Version 3.0

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Suspected of damaging the unborn child.

Toxicity for specific target organ - single exposure

Based on available data the classification criteria are not met.

Toxicity for specific target organ - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data the classification criteria are not met.

11.2. Information on other hazards

not available

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

Harmful to aquatic life with long lasting effects.

styrene

Parameter	Method	Value	Time of exposure	Species	Environment	Source
EC 10	EPA OTS 797.1050	0.28 mg/l		Algae (Pseudokirchneriella subcapitata)		
EC 10	EPA OTS 797.1050	72 mg/l	16 hour	Microorganisms (Pseudomonas putida)		
EC 20	OECD 209	140 mg/l	0,5 hour	BES		
EC ₅₀		500 mg/l		BES		ISO 8192-1986 E
EC ₅₀		5.5 mg/l		Bacteria (Salmonella typhimurium)		
EC ₅₀		>72 mg/l	16 hour	Bacteria (Pseudomonas putida)		
EC ₅₀		0.56 mg/l	48 hour	Algae		
EC ₅₀		4.7 mg/l	48 hour	Invertebrates (Daphnia magna)		
EC ₅₀		0.46-4.3 mg/l	72 hour	Algae (Pseudokirchneriella subcapitata)		

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

METALLIC FILLER

Creation date

23rd March 2021

Revision date

Version

3.0

styrene

Parameter	Method	Value	Time of exposure	Species	Environment	Source
EC ₅₀		>1-<10 mg/l	72 hour	Algae		
EC ₅₀		>200 mg/l	8 day	Algae (Scenedesmus quadricauda)		
EC ₅₀		0.15-3.2 mg/l	96 hour	Algae (Pseudokirchneriella subcapitata)		
IC ₅₀		>200 mg/l	8 day	Algae (Scenedesmus quadricauda)		
IC ₅₀		4.9 mg/l	72 hour	Algae		
IC ₅₀		1.4 mg/l	72 hour	Algae (Selenastrum capricornutum)		
LC ₅₀		4.9 mg/l	72 hour	Algae		
LC ₅₀		>1-<10 mg/l	96 hour	Fishes		
LC ₅₀		25 mg/l	96 hour	Lem		
LC ₅₀		32 mg/l	96 hour	Fishes (Pimephales promelas)		
LC ₅₀		4.02 mg/l	96 hour	Fishes (Pimephales promelas)		
LC ₅₀		58.75-95.32 mg/l	96 hour	Fishes (Poecilia reticulata)		

trizinc bis(orthophosphate)

Parameter	Method	Value	Time of exposure	Species	Environment	Source
EC ₅₀		28.2 mg/l	48 hour	Invertebrates (Daphnia magna)		
ErC ₅₀		<0.3 mg/l	72 hour	Algae (Desmodesmus subspicatus)		
EC ₅₀		<1.7 mg/l	48 hour	Invertebrates (Daphnia magna)		
EC ₅₀		0.28 mg/l	72 hour	Algae (Selenastrum capricornutum)		
LC ₅₀		<5.1 mg/l	96 hour	Fishes (Oncorhynchus mykiss)		

12.2. Persistence and degradability

Data not available.

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

not available

12.7. Other adverse effects

METALLIC FILLER

Creation date	23rd March 2021	Version	3.0
Revision date			

Water hazard class 2 (German Regulation; Self-assessment): hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Perfectly cleaned containers can be submitted for recycling. Recommended cleansing agents: Alcohol.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

20 01 27 paint, inks, adhesives and resins containing hazardous substances *

Packaging waste type code

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by hazardous substances *

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number or ID number

UN 3269

14.2. UN proper shipping name

POLYESTER RESIN KIT

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

III - substances presenting low danger

14.5. Environmental hazards

not available

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not available

Additional information

Stowage category: A

Hazard identification No.

UN number

Safety signs



3



Road transport - ADR

Limited quantities

5 L

Excepted quantities

E0

Transport category

3

Tunnel restriction code

(E)

Marine transport - IMDG

EmS (emergency plan)

F-E, S-D

Marine Pollutant

No

METALLIC FILLER

Creation date	23rd March 2021	Version	3.0
Revision date			

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
DNEL	Derived no-effect level
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

METALLIC FILLER

Creation date	23rd March 2021	Version	3.0
Revision date			

IC ₅₀	Concentration causing 50% blockade
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LOAEC	Lowest observed adverse effect concentration
LOAEL	Lowest observed adverse effect level
log K _{ow}	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution From Ships
NOAEC	No observed adverse effect concentration
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
NOEL	No observed effect level
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted no-effect concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative

Acute Tox.	Acute toxicity
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
Repr.	Reproductive toxicity
Skin Irrit.	Skin irritation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 3.0 replaces the SDS version from 16 August 2018 . Changes were made in sections 1, 2, 3, 8, 11, 12, 13, 15 and 16.

Statement

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

METALLIC FILLER

Creation date 23rd March 2021

Revision date Version 3.0

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.