

Date of issue: 10.10.2011	Trade name:	Page: 1/8
Reviewed on:	QUICK OFF	Version: 1.0

1. Section 1. Identification of the substance/mixture and of the company/undertaking:1.1. Product identifier : **QUICK OFF - 02.0014**1.2. Relevant identified uses of the substance or Releaser of rusty joints
mixture and uses advised against:1.3. Details of the supplier of the safety data sheet:
Identification of manufacturer/Supplier:

RETECH, s.r.o.

Vackova 1541/4

150 00 Praha-5 Stodůlky

Telephone/Fax: +420 327 596 128, +420 327 596 428

Information: info@retech.cz

1.4. Emergency telephone number:

RETECH Suchdol 212, Suchdol u Kutné Hory

Tel.+420 327 596 128 (7.30-16.00 hour)

Toxicology information number, Na bojišti 1, 128 08 PRAHA 2

Tel. +420 224 919 293, +420 224 915 402 (24 hours a day)

2. Section 2. Hazard identification:

The product is labeled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

The classification is in line with current EC lists, It is expanded, however, by information from technical literature and by information furnished by supplier companies.

2.1. Classification of the substance or mixture:

Classification according to Regulation (EC) No 1272/2008:

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC:

F+ Extremely flammable R12 Extremely flammable

Xi-Irritant R36/38 Irritating to eye and skin.

N-Dangerous for the environment R51/53 Toxic to aquatic organisms, may cause long-term effects in aquatic environment.

R67 Vaporous may cause drowsiness and dizziness.

2.2. Label elements:

Labelling according to Regulation (EC) No 1272/2008:

GHS02



DANGER

GHS07



WARNING

GHS09



H222 Extremely flammable aerosol.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Date of issue: 10.10.2011	Trade name:	Page: 2/8
Reviewed on:	QUICK OFF	Version: 1.0

Labelling according to Directive 1999/45/EC:



Extremely flammable



Irritant



Dangerous for the Environment

- R 12 Extremely flammable.
R 36/ 38 Irritating to eyes and skin.
R 51/53 Toxic to aquatic organisms, may cause long-term effects in aquatic environment.
R 67 Vaporous may cause drowsiness and dizziness.

Special labeling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition.- No smoking. Keep out of reach of children.

- 2.3. Other hazards:
Results of PBT and vPvB assessment:
PBT: Not applicable
vPvB: Not applicable
Buildup of explosive mixtures possible without sufficient ventilation.

3. Section 3. Composition/information on ingredients:

3.2. Mixtures:

Description: The active ingredient in propellants

Dangerous components:

CAS: 64742-49-0 EINECS: 265-151-9 Reg.nr.: 01-2119475514-35	Naphtha (petroleum); Hydrotreated light (contains less than 0.1% benzene) F R11; Xi R38; N51/53; Xn R65; R67 GHS02 Flam. Liq. 2, H225; GHS08 Asp. Tox. 1, H304; GHS09 Aquatic Chronic 2, H411; GHS07 Skin Irrit. 2, H315; STOT SE 3, H336	25-<50%
CAS: 67-63-0 EINECS: 200-661-7	Propan-2-ol F R 11; Xi R36; R67 GHS02 Flam. Liq. 2, H225; GHS07 Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	Butane (containing <0,1% butadiene (203-450-8)) F+ R12 GHS02 Flam. Gas 1, H220; GHS04 Press. Gas, H280	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	Propane F+ R12 GHS02 Flam. Gas 1, H220; GHS04 Press. Gas, H280	10-<25%

Additional information: For the wording of the listed risk phrases refer to section 16.

Ingredients according to detergents guideline 648/2004/EC: Aliphatic hydrocarbons $\geq 30\%$,

4. Section 4. First aid measures:

4.1. Description of first aid measures:

- After inhalation: Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.
- After skin contact: Instantly remove any clothing soiled by the product, immediately wash with water and

Date of issue: 10.10.2011	Trade name:	Page: 3/8
Reviewed on:	QUICK OFF	Version: 1.0

After eye contact: soap and rinse thoroughly. Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing: Do not induce vomiting, rinse mouth with water and drink plenty of water. Seek for medical advice immediately. Do not give water if the person is unconscious.

Most important symptoms and effects, both acute and delayed: In case of unconsciousness place patient stable in side position for transportation.

Indication of any immediate medical attention and special treatment needed: No further relevant information available.

5. Section 5. Fire fighting measures:

5.1. Extinguishing media:
 Suitable extinguishing agents: Carbon dioxide (CO₂), fire-extinguishing powder, water haze or alcohol resistant foam.
 For safety reasons unsuitable extinguishing agents: Water with full jet.

5.2. Special hazards arising from the substance or mixture:
 Information not available.

5.3. Advice for firefighters: Wear protective equipment/clothing when fighting fires. Aerosols may explode when overheated. Containers close to fire should be removed or cooled with water.

6. Section 6. Accidental release measures:

6.1. Personal precautions, protective equipment and emergency procedures:
 Wear protective equipment see Section 8.2. Ensure adequate ventilation. Let evaporate. Keep unprotected person away. Keep away from ignition sources.

6.2. Environmental precautions:
 Do not allow product to reach sewage system, surface or ground water.
 Inform respective authorities in case of seepage into water course or sewage system.

6.3. Methods and material for containment and cleaning up:
 Ensure adequate ventilation.
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections:
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment
 See Section 13 for disposal information.

7. Section 7. Handling and storage:

7.1. Information for safe handling:
 Information about protection against explosions and fires: Ensure good ventilation/exhaustion at the workplace. Beware: Container is pressurized. Keep away from direct sun exposure and temperatures over 50°C. i.e. electric lights.
 Do not open by force or throw into fire even after use.
 Do not spray on flames or red-hot objects.
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.

7.2. Conditions for safe handling, including any incompatibilities:
 Requirements to be met by storerooms and containers: Store in cool dry location. Observe official regulations on storing packaging with pressurized containers.
 Information about storage in one common storage facility: Observe official regulations on storing packaging with pressurized containers.
 Further information about storage conditions: Store in cool, dry conditions. Protect from heat and direct sunlight.

Date of issue: 10.10.2011	Trade name:	Page: 4/8
Reviewed on:	QUICK OFF	Version: 1.0

7.3. Specific end use(s): No further relevant information available.

8. Section 8. Exposure controls and personal protection:

8.1. Control parameters:

Components with limit values that require monitoring at the workplace:

106-97-8 butane (containing < butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

74-98-6 Propane

WEL Short-term value: 3600 mg/cm³, 2000 ppm

Long-term value: 1800 mg/m³, 1000 ppm

67-63-0 propan-2-ol

OES Short-term value: 1250 mg/m³, 500 ppm

Long-term value: 999 mg/m³, 400 ppm

Additional information: The lists that were valid during the compilation were as basis.

DNELs

67-63-0 propan-2-ol

Oral DNEL 26 mg/kg bw/day (Consumer) (Chronische Blootstelling, Systeem Effecten)

Dermal DNEL 319 mg/kg bw/day (Consumer) (Chronische Blootstelling, Systeem Effecten)

888 mg/kg bw/day (Worker) (Chronische Blootstelling, Systeem Effecten)

Inhalative DNEL 89 mg/m³ (Consumer) (Chronische Blootstelling, Systeem Effecten)

500 mg/m³ (Worker) (Chronische Blootstelling, Systeem Effecten)

8.2. Exposure controls:

Eye protection:

Tightly safety goggles.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

Recommended filter device for short term use – Filter AX/P2.

Protection of hands:

Protective gloves.

Solvent resistant gloves

Selection of glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves: Nitrile rubber, NBR

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Protection of skin:

Protective clothing

8.3 General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin. Do not inhale gases/fumes/aerosols.

9. Section 9. Physical and chemical properties:

Appearance:

form:

Aerosol

colour:

Clear

Odour threshold:

Characteristic

Value pH:

Not determined

Melting point/freezing point:

Not determined

Initial boiling point/boiling range:

-44°C

Flash point:

-97°C

Evaporation rate:

Not determined

Flammability (solid,gas):

Not applicable

Ignition temperature:

200°C

Explosive properties:

Product is not explosive. However, formation of explosive air/steam mixtures is possible.

Date of issue: 10.10.2011	Trade name:	Page: 6/8
Reviewed on:	QUICK OFF	Version: 1.0

<p>Remark: Toxic for fish Water hazard class 2 (Self-assessment): hazardous for water. Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic to aquatic organisms.</p> <p>12.2. Persistence and degradability: No further relevant information available. 12.3. Bioaccumulative potential: No further relevant information available. 12.4. Mobility in soil: No further relevant information available. 12.5. Results of PBT and vPvB assessment: PBT: Not applicable vPvB: Not applicable 12.6. Other adverse effects: No further relevant information available.</p>		
<p>13. Section 13. Disposal considerations:</p> <p>13.1 Waste treatment methods: Product: Must not be disposed together with household garbage. Do not allow product to reach sewage system. Uncleaned packagings: Disposal must be made according to official regulations.</p>		
<p>14. Section 14. Transport information:</p> <p>14.1. Land transport: ADR/RID-GGVS/E class: 2 5F Gases Danger code (Kemler): Not determined Packaging group: Not determined Hazard label: 2.1 Special marking: Symbol (fish and tree) Number UN: 1950 Limited quantities (LQ): LQ2; 1L Transport category: 2 Tunnel restriction code: D UN proper shipping name: 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS</p> <p>14.2. Maritime transport: IMDG-class: 2.1 Number UN: 1950 Label: 2.1 Packaging group: Not determined EMS-group: F-D,S-U Marine pollutant: No Proper shipping name: Aerosols</p> <p>14.3. Air transport: ICAO / IATA -class: 2.1 UN/ID number: 1950 Label: 2.1 Packaging group: Not determined Proper shipping name: Aerosols, flammable UN "Model Regulation": UN1950; AEROSOLS; ENVIRONMENTALLY HAZARDOUS 2.1 Special precautions for users - Waring: Gases Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable</p>		
<p>15. Section 15. Regulatory information:</p> <p>15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture: Labeling according to law line: The product has been classified and marked in according with EU Directives/Ordinance on Hazardous Materials.</p>		

Date of issue: 10.10.2011	Trade name:	Page: 7/8
Reviewed on:	QUICK OFF	Version: 1.0

Danger of determining components and mark to labeling:

74-98-6 Propane, 106-97-8 Butane, 67-63-0 Propanol, 64742-49-0, 64742-49-0 Naphtha (petroleum), hydrotreated light

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after burn. Do not spray on a naked flame or any incandescent material.

Labeling hazardousness:



F+ - Extremely flammable



Xi- Irritant



N – Dangerous for the environment

Numbers and word reading associated hazard R-sentences :

R 12 Extremely flammable

R 36/ 38 Irritating to eyes and skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 67 Vapours may cause drowsiness and dizziness.

Numbers and word reading associated security S-sentences:

S 2 Keep out of reach of children.

S 16 Keep away from sources of ignition – No smoking.

S 23 Do not breathe vapours / aerosol.

S 24/25 Avoid contact with skin and eyes.

S 46 If swallowed, seek medical advice immediately and show this container or label.

S 51 Use only in well-ventilated areas

S 56 Dispose of this material and its container at hazardous or special waste collection point.

S 61 Avoid release to the environment. Refer to special instructions / Safety data sheets.

On the packaging there is not included info in accordance with European Regulation No 1999/45/EC (chapter 2.5.).

Density: 0,677 g/cm³

VOC: 643.1 g/l

National regulations:

Danish MAL Code 5-3

Used legislation:

European Regulation (EC) No 1907/2006 – REACH.

Commission Regulation (EU) No 453/2010.

European Regulation No 67/548EEC and 1999/45/EC.

Commission Regulation (EC) No 1272/2006 – CLP.

Commission Regulation (EC) No 790/2009.

Regulation (EC) No 648/2004 (detergents).

15.2. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16. Section 16. Other information:

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relative R+H phrases:

R 11 Highly flammable.

R 12 Extremely flammable.

R 36 Irritating to eyes.

R 38 Irritating to skin.

Date of issue: 10.10.2011	Trade name:	Page: 8/8
Reviewed on:	QUICK OFF	Version: 1.0

- R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 65 Harmful: May cause lung damage if swallowed.
R 67 Vapours may cause drowsiness and dizziness.
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

WEL- Workplace exposure limits

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

***Compared to the last version the data has been changed.**