

Date of issue: 28.7.2011	Trade name:	Page: 1/8
Reviewed on:	<b>RUBBER PROTECTION</b>	Version: 1.0

**1. Section 1. Identification of the substance/mixture and of the company/undertaking:**

- 1.1. Product identifier : **RUBBER PROTECTION – R 50110 (spray)**
- 1.2. Relevant identified uses of the substance or mixture and uses advised against: Rubber structure protection.
- 1.3. Details of the supplier of the safety data sheet:  
Identification of manufacturer/Supplier:  
RETECH, s.r.o.  
Vackova 1541/4  
150 00 Praha-5 Stodůlky  
Telephone/Fax: +420 327 596 128, +420 327 596 428  
Information: [info@retech.cz](mailto:info@retech.cz)
- 1.4. Emergency telephone number:  
RETECH Suchdol 212, Suchdol u Kutné Hory  
Tel.+420 327 596 128 (7.30-16.00 hour)  
Toxicology information number, Na bojišti 1, 128 08 PRAHA 2  
Tel. +420 224 919 293, +420 224 915 402 (24 hours a day)

**2. Section 2. Hazard identification:**

The product is labeled due to the calculation procedure of the “General Classification guideline for preparations of the EU” in the latest valid version.  
The classification is in line with current EC lists, It is expanded, however, by information from technical literature and by information furnished by supplier companies.

- 2.1. Classification of the substance or mixture:  
Classification according to Regulation (EC) No 1272/2008:  
Flam. Aerosol 1 H222 Extremely flammable aerosol.  
Skin Irrit. 2 H315 Causes skin irritation.  
STOT SE 3 H336 May cause drowsiness or dizziness.  
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC:

F+ Extremely flammable R12 Extremely flammable  
Xi-Irritant R38 Irritating to skin.  
N-Dangerous for the environment R51/53 Toxic to aquatic organisms, may cause long-term effects in aquatic environment.  
R67 Vaporous may cause drowsiness and dizziness.

2.2. Label elements:

Labelling according to Regulation (EC) No 1272/2008:

GHS02



DANGER

GHS07



WARNING

GHS09



H222 Extremely flammable aerosol.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

Labelling according to Directive 1999/45/EC:

F+



Extremely flammable

Xi



Irritant

N



Dangerous for the Environment

Date of issue: 28.7.2011	Trade name:	Page: 2/8
Reviewed on:	<b>RUBBER PROTECTION</b>	Version: 1.0

- R 12 Extremely flammable.  
R 38 Irritating to skin.  
R 51/53 Toxic to aquatic organisms, may cause long-term effects in aquatic environment.  
R 67 Vaporous may cause drowsiness and dizziness.

Special labeling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition.- No smoking. Keep out of reach of children.

2.3. Other hazards:

Results of PBT and vPvB assessment:

PBT: Not applicable

vPvB: Not applicable

Buildup of explosive mixtures possible without sufficient ventilation.

**3. Section 3. Composition/information on ingredients:**

3.2. Mixtures:

Description: The active ingredient in propellants

Dangerous components:

CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum); Hydrotreated light (contains less than 0.1% benzene) F R11; Xi R38; N51/53; Xn R65; R67 GHS02 Flam. Liq. 2, H225; GHS08 Asp. Tox. 1, H304; GHS09 Aquatic Chronic 2, H411; GHS07 Skin Irrit. 2, H315; STOT SE 3, H336	10-<25%
CAS: 106-97-8 EINECS: 203-448-7	Butane (containing <0,1% butadiene (203-450-8)) F+ R12 GHS02 Flam. Gas 1, H220; GHS04 Press. Gas, H280	10-<25%
CAS: 74-98-6 EINECS: 200-827-9	Propane F+ R12 GHS02 Flam. Gas 1, H220; GHS04 Press. Gas, H280	10-<25%
CAS: 141-78-6 EINECS: 205-500-4	Ethylacetate F R11; Xi R36; R66,R67 GHS02 Flam. Liq. 2, H225; GHS07 Eye Irrit. 2, H319; STOT SE 3 H336; EUH066	10-<25%
CAS: 123-86-4 EINECS: 204-658-1	Butylacetate R10-66-67 GHS02 Flam. Liq. 3, H226; GHS07 STOT SE 3 H336, EUH066	5-10%
CAS: 78-93-3 EINECS: 201-159-0	Butanone (ethyl methyl ketone) F R 11; Xi R36; R66; R67 GHS02 Flam. Liq. 2, H225; GHS07 Eye Irrit. 2, H319; STOT SE 3, H336; EUH066	5-10%
CAS: 110-82-7 EINECS: 203-806-2	Cyclohexane F R11; Xi R38; N R50/53; Xn R65; R67 GHS02 Flam. Liq. 2, H225; GHS08 Asp. Tox. 1, H304; GHS09 Aquatic Acute 1, H410, Aquatic Chronic 1, H411; GHS07 Skin Irrit. 2, H315; STOT SE 3, H336	1-<5%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom light (contains less than 0.1% benzene) R 10; Xi R37; N R51/53; Xn R65; R 66 R67 GHS02 Flam. Liq. 3, H226; GHS08 Asp. Tox. 1, H304; GHS09 Aquatic Chronic 2, H411; GHS07 STOT SE 3, H335; STOT SE 3,	1-<5%

Date of issue: 28.7.2011	Trade name:	Page: 3/8
Reviewed on:	<b>RUBBER PROTECTION</b>	Version: 1.0

	H336; EUH066	
--	--------------	--

Additional information: For the wording of the listed risk phrases refer to section 16.

**4. Section 4. First aid measures:**

- 4.1. Description of first aid measures:
- After inhalation: Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.
- After skin contact: Instantly remove any clothing soiled by the product, immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- After swallowing: Do not induce vomiting, rinse mouth with water and drink plenty of water. Seek for medical advice immediately. Do not give water if the person is unconscious.
- Most important symptoms and effects, both acute and delayed: In case of unconsciousness place patient stable in side position for transportation.
- Indication of any immediate medical attention and special treatment needed: No further relevant information available.

**5. Section 5. Fire fighting measures:**

- 5.1. Extinguishing media:
- Suitable extinguishing agents: Carbon dioxide (CO<sub>2</sub>), fire-extinguishing powder, water haze or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet.
- 5.2. Special hazards arising from the substance or mixture:
- Information not available.
- 5.3. Advice for firefighters: Wear protective equipment/clothing when fighting fires. Aerosols may explode when overheated. Cool the container with water.

**6. Section 6. Accidental release measures:**

- 6.1. Personal precautions, protective equipment and emergency procedures:
- Wear protective equipment see Section 8.2. Ensure adequate ventilation. Let evaporate. Keep unprotected person away. Keep away from ignition sources.
- 6.2. Environmental precautions:
- Do not allow product to reach sewage system, surface or ground water.
- Inform respective authorities in case of seepage into water course or sewage system.
- 6.3. Methods and material for containment and cleaning up:
- Ensure adequate ventilation.
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose of contaminated material as waste according to Section 13.
- 6.4. Reference to other sections:
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment
- See Section 13 for disposal information.

**7. Section 7. Handling and storage:**

- 7.1. Information for safe handling:
- Information about protection against explosions and fires:
- Ensure good ventilation/exhaustion at the workplace.
- Beware: Container is pressurized. Keep away from direct sun exposure and temperatures over 50°C. i.e. electric lights.
- Do not open by force or throw into fire even after use.
- Do not spray on flames or red-hot objects.
- Keep ignition sources away - Do not smoke.

Date of issue: 28.7.2011	Trade name:	Page: 4/8
Reviewed on:	<b>RUBBER PROTECTION</b>	Version: 1.0

- 7.2. Conditions for safe handling, including any incompatibilities: Protect against electrostatic charges.  
 Requirements to be met by storerooms and containers: Store in cool dry location.  
 Observe official regulations on storing packaging with pressurized containers.  
 Information about storage in one common storage facility: Observe official regulations on storing packaging with pressurized containers.  
 Further information about storage conditions: Store in cool, dry conditions.  
 Protect from heat and direct sunlight.
- 7.3. Specific end use(s): No further relevant information available.

**8. Section 8. Exposure controls and personal protection:**

- 8.1. Control parameters:  
 Components with limit values that require monitoring at the workplace:  
 106-97-8 butane (containing < butadiene (203-450-8))  
 WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
 Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
 Carc (if more than 0.1% of buta-1.3-diene)  
 74-98-6 Propane  
 WEL Short-term value: 3600 mg/cm<sup>3</sup>, 2000 ppm  
 Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm  
 110-82-7 Cyklohexane  
 WEL Short-term value: 1050 mg/cm<sup>3</sup>, 300 ppm  
 Long-term value: 350 mg/cm<sup>3</sup>, 100 ppm  
 Additional information: The lists that were valid during the compilation were as basis.
- 8.2. Exposure controls:  
 Eye protection: Tightly safety goggles.  
 Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.  
 In case of brief exposure or low pollution use respiratory filter device (Filter AX/P2).  
 In case of intensive or longer exposure use self-contained respiratory protective device.  
 Protection of hands: Protective gloves.  
 Solvent resistant gloves  
 Selection of glove material on consideration of the penetration times, rates of diffusion and the degradation  
 Material of gloves: Nitrile rubber, NBR  
 Penetration time of glove material > 480 min.  
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- 8.3. Protection of skin: Protective clothing  
 General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands during breaks and at the end of the work.  
 Avoid contact with the eyes and skin. Do not inhale gases/fumes/aerosols.

**9. Section 9. Physical and chemical properties:**

- 9.1. Information on basic physical and chemical properties:  
 Appearance:  
 form: Aerosol  
 colour: Black  
 Odour threshold: Characteristic  
 Value pH: Not determined  
 Melting point/freezing point: Not determined  
 Melting point/freezing point: Not determined  
 Initial boiling point/boiling range: -44°C



Date of issue: 28.7.2011	Trade name:	Page: 6/8
Reviewed on:	<b>RUBBER PROTECTION</b>	Version: 1.0

<p>Water hazard class 1 (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic to aquatic organisms.</p> <p>12.2. Persistence and degradability: No further relevant information available. 12.3. Bioaccumulative potential: No further relevant information available. 12.4. Mobility in soil: No further relevant information available. 12.5. Results of PBT and vPvB assessment: PBT: Not applicable vPvB: Not applicable 12.6. Other adverse effects: No further relevant information available.</p>		
<p><b>13. Section 13. Disposal considerations:</b></p> <p>13.1 Waste treatment methods: Product: Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose in safe manner in accordance with local/national regulation. Uncleaned packagings: Disposal must be made according to official regulations.</p>		
<p><b>14. Section 14. Transport information:</b></p> <p>14.1. Land transport: ADR/RID-GGVS/E class: 2 5F Gases Danger code (Kemler): Not determined Packaging group: Not determined Hazard label: 2.1 Special marking: Symbol (fish and tree) Number UN: 1950 Limited quantities (LQ): LQ2; 1L Transport category: 2 Tunnel restriction code: D UN proper shipping name: 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS</p> <p>14.2. Maritime transport: IMDG-class: 2.1 Number UN: 1950 Packaging group: Not determined EMS-group: F-D, S-U Marine pollutant: YES Symbol (fish and tree) Proper shipping name: Aerosols, Naphtha (petroleum), hydrotreated light)</p> <p>14.3. Air transport: ICAO / IATA -class: 2.1 UN/ID number: 1950 Label: 2.1 Packaging group: Not determined Proper shipping name: Aerosols, flammable UN "Model Regulation": UN1950; AEROSOLS; ENVIRONMENTALLY HAZARDOUS 2.1 Product contains environmentally hazardous substances: Cyclohexane Special precautions for users - Waring: Gases Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable Transport/Additional information: For ADR and IMDG: Transport and packing are in accordance with the regulation for limited quantities. These products are therefore classified as no dangerous goods.</p>		
<p><b>15. Section 15. Regulatory information:</b></p> <p>15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture:</p>		

Date of issue: 28.7.2011	Trade name:	Page: 7/8
Reviewed on:	<b>RUBBER PROTECTION</b>	Version: 1.0

Labelling according to law line:

The product has been labeled in accordance with EC Directives / relevant national laws.

Danger of determining components and mark to labelling:

64742-49-0 Naphtha (petroleum), hydrotreated light

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after burn. Do not spray on a naked flame or any incandescent material.

Labelling hazardousness:



F+ - Extremely flammable



Xi- Irritant



N- Dangerous for the environment

Numbers and word reading associated hazard R-sentences :

R 12 Extremely flammable

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term effects in aquatic environment.

R 67 Vapours may cause drowsiness and dizziness.

Numbers and word reading associated security S-sentences:

S 2 Keep out of the reach children.

S 16 Keep away from sources of ignition – No smoking.

S 23 Do not breathe vapours / spray

S 24/25 Avoid contact with skin and eyes.

S 51 Use only in well-ventilated areas.

S 56 Dispose of this material and its container at hazardous or special waste collection point.

S 61 Avoid release to the environment. Refer to special instructions / Safety data sheets.

On the packaging there is not included info in accordance with European Regulation No 1999/45/EC (chapter 2.5.).

Density: 0,880 g/cm<sup>3</sup>

VOC: 2004/42/IIB(e)(840) – 637 g/l

Used legislation:

European Regulation (EC) No 1907/2006 – REACH.

Commission Regulation (EU) No 453/2010.

European Regulation No 67/548EEC and 1999/45/EC.

Commission Regulation (EC) No 1272/2006 – CLP.

Commission Regulation (EC) No 790/2009.

Regulation (EC) No 648/2004 (detergents).

15.2. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16. Section 16. Other information:

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relative R+H phrases:

R 10 Flammable.

R 11 Highly flammable.

R 12 Extremely flammable.

R 36 Irritating to eyes.

R 37 Irritating to respiratory system.

R 38 Irritating to skin.

Date of issue: 28.7.2011	Trade name:	Page: 8/8
Reviewed on:	<b>RUBBER PROTECTION</b>	Version: 1.0

R 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R 65 Harmful: May cause lung damage if swallowed.  
R 66 Repeated exposure may cause skin dryness or cracking.  
R 67 Vapours may cause drowsiness and dizziness.  
H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
EUH066 Repeated exposure may cause skin dryness or cracking.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

WEL- Workplace exposure limits

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

**\*Compared to the last version the data has been changed.**