

SILICONE GREASE

Creation date	21. January 2015	Version	2.0
Revision date	10. May 2018		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier** SILICONE GREASE
Substance / mixture mixture
Number R 34400
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
mixture's intended use Grease.

The use descriptors

- | | |
|---------|--|
| SU 3 | Industrial uses: Uses of substances as such or in preparations* at industrial sites |
| SU 22 | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| PROC 7 | Industrial spraying |
| PROC 11 | Non industrial spraying |
| ERC 8a | Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) |
| ERC 8d | Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) |

Disapproved uses of mixture For professional use only.

1.3. Details of the supplier of the safety data sheet**Supplier**

Name or trade name	RETECH, s.r.o.
Address	Vackova 1541/4, Praha 5 - Stodůlky, 155 00 Czech Republic
Identification number (ID)	25018205
Phone	+420327596428
E-mail	info@retech.cz
Web address	www.retech.com

Competent person responsible for the safety data sheet

Name	RETECH, s.r.o.
E-mail	info@retech.cz

1.4. Emergency telephone number

Poisoning information centre, Na Bojišti 1, Praha, Czech Republic, Tel.: non-stop +420 224 919 293 or +420 224 915 402, Information on health risks only - acute poisoning of humans and animals.
RETECH, Suchdol 212, 285 02 Suchdol u Kutné Hory, Czech Republic; Telephone number: +420 327 596 128 (7.30-16.00 hour)

SECTION 2: Hazards identification**2.1. Substance or mixture classification****Classification of the mixture in accordance with Regulation (EC) No 1272/2008**

The mixture is classified as dangerous.

Aerosol 1, H222, H229
Asp. Tox. 1, H304
STOT SE 3, H336
Aquatic Chronic 3, H412

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Extremely flammable aerosol. Pressurised container: May burst if heated.

Most serious adverse effects on human health and the environment

May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

SILICONE GREASE

Creation date 21. January 2015
Revision date 10. May 2018 Version 2.0

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazardous substances

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hazard statements

- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/eye protection.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P403 Store in a well-ventilated place.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container to in accordance with national regulations.

Supplemental information

>=30 % aliphatic hydrocarbons

2.3. Other hazards

Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Buildup of explosive mixtures possible without sufficient ventilation.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note.
CAS: 106-97-8 EC: 203-448-7 Registration number: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8))	50-75	Flam. Gas 1, H220 Press. Gas, H280	
CAS: 74-98-6 EC: 200-827-9 Registration number: 01-2119486944-21	propane	10-25	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	

SILICONE GREASE

Creation date	21. January 2015	Version	2.0	
Revision date	10. May 2018			
Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note.
Registration number: 01-2119473851-33	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	10-25	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411	

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

Inhalation

Terminate the exposure immediately; move the affected person to fresh air. In the event of issues, find medical advice.

Skin contact

Generally the product does not irritate the skin.

Eye contact

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. In the event of issues, find medical advice.

Ingestion

DO NOT INDUCE VOMITING! Provide medical treatment.

4.2. Most important symptoms and effects, both acute and delayed**Inhalation**

not available

Skin contact

not available

Eye contact

not available

Ingestion

not available

4.3. Indication of any immediate medical attention and special treatment needed

not available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

not available

5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide sufficient ventilation. Use personal protective equipment for work. Keep unprotected persons away.

6.2. Environmental precautions

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

SILICONE GREASE

Creation date 21. January 2015
Revision date 10. May 2018 Version 2.0

- 6.3. Methods and material for containment and cleaning up**
Provide sufficient ventilation. Do not flush with water or aqueous cleansing agents.
- 6.4. Reference to other sections**
See the Section 7, 8 and 13.

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Do not spray on an open flame or other ignition source. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. No smoking. Take precautionary measures against static discharge. Pressurised container: May burst if heated. Keep away from sources of heating, ignition and direct sunlight. Do not pierce or burn, even after use.
- 7.2. Conditions for safe storage, including any incompatibilities**
Keep cool. Observe official regulations on storing packagings with pressurized containers.
Storage class 2B - Aerosols
The specific requirements or rules relating to the substance/mixture
Store in tightly closed containers in a cool, dry place intended for this purpose. Keep away from sources of heating, ignition and direct sunlight.
- 7.3. Specific end use(s)**
not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

United Kingdom of Great Britain and Northern Ireland

Substance name (component)	Type	Time of exposure	Value	Note	Source
butane (containing < 0,1 % butadiene (203-450-8)) (CAS: 106-97-8)	WEL	8 hours	600 ppm		GBR
	WEL	8 hours	1450 mg/m ³		
	WEL	15 minutes	1810 mg/m ³		
	WEL	15 minutes	750 ppm		

DNEL

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Workers / consumers	Route of exposure	Value	Effect	Determining method
Consumers	Oral	699 mg/kg bw/day	Systemic chronic effects	
Consumers	Dermal	699 mg/kg bw/day	Systemic chronic effects	
Workers	Dermal	773 mg/kg bw/day	Systemic chronic effects	
Consumers	Inhalation	608 mg/m ³	Systemic chronic effects	
Workers	Inhalation	2035 mg/m ³	Systemic chronic effects	

SILICONE GREASE

Creation date	21. January 2015	Version	2.0
Revision date	10. May 2018		

8.2. Exposure controls

Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest. Do not inhale gases and vapours. Do not inhale aerosols.

Eye/face protection

Tightly sealed goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. The final selection of the glove material must be carried out on the basis of penetration times, permeation rates and degradation. Material of gloves: As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Nitrile rubber, NBR. Recommended thickness of the material: ≥ 0.5 mm. Penetration time of glove material: The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Other protection: protective workwear.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter AX/P2.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	aerosol
Physical state	gas at 20°C
color	grey
Odour	characteristic
Odour threshold	data not available
pH	data not available
Melting point/freezing point	data not available
Initial boiling point and boiling range	-44 °C
Flash point	-97 °C
Evaporation rate	data not available
Flammability (solid, gas)	Extremely flammable aerosol.
Upper/lower flammability or explosive limits	
flammability limits	data not available
explosive limits	
bottom	1.0 %
upper	10.9 %
Vapour pressure	8300 hPa at 20 °C
Vapour density	data not available
Relative density	data not available
Solubility(ies)	
solubility in water	almost insoluble
solubility in fats	data not available
Partition coefficient: n-octanol/water	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
Viscosity	data not available
Explosive properties	The product does not have explosive properties but can be explosive when blended with air.
Oxidising properties	data not available
data not available	

9.2. Other information

SILICONE GREASE

Creation date	21. January 2015	Version	2.0
Revision date	10. May 2018		

Density	0.62 g/cm ³ at 20 °C
ignition temperature	>200 °C
content of organic solvents (VOC)	81.6 %
solid content (dry matter)	1.4 % volume
Max. VOC content in the product in its ready to use condition	505.1 g/l
Product is not selfigniting.	

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

not available

10.5. Incompatible materials

not available

10.6. Hazardous decomposition products

Unknown.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	>5000 mg/kg		Rat	
Dermal	LD ₅₀	>2800 mg/kg		Rat	
Inhalation	LC ₅₀	>23 mg/l	4 hour	Rat	

Skin corrosion/irritation

Based on available data the classification criteria are not met.

Serious eye damage/irritation

Based on available data the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

SILICONE GREASE

Creation date 21. January 2015
Revision date 10. May 2018 Version 2.0

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

Harmful to aquatic life with long lasting effects.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Parameter	Value	Time of exposure	Species	Environment
NOELR	10 mg/l	72 hour	Algae (Selenastrum capricornutum)	
LL 50	>13.4 mg/l	72 hour	Fishes (Oncorhynchus mykiss)	
NOEC	0.17 mg/l	21 day	Invertebrates (Daphnia magna)	
LOEC	0.32 mg/l	21 day	Invertebrates (Daphnia magna)	
EC50	3 mg/l	48 hour	Invertebrates (Daphnia magna)	
EL 50	10-30 mg/l	72 hour	Algae (Selenastrum capricornutum)	

12.2. Persistence and degradability

Not available.

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Other adverse effects

Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water. Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste.

SILICONE GREASE

Creation date	21. January 2015	Version	2.0
Revision date	10. May 2018		

Legislation of waste

Council Directive 75/442/EEC on waste, as amended. Decree No. 383/2001 Coll., on details regarding waste handling as amended. Decree No. 93/2016 Coll., (waste catalogue) as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

16 03 05 organic wastes containing dangerous substances

Packaging waste type code

15 01 11 metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

SECTION 14: Transport information

14.1. UN number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not available

14.5. Environmental hazards

not available

14.6. Special precautions for user


Reference in the Sections 4 to 8.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not available

Additional information

Stowage Code: SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. Segregation Code: SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

Hazard identification No.  (Kemler Code)

UN number **1950**

Classification code 5F

Safety signs 2.1



Road transport ADR

Limited amount 1L

Extracted amounts E0

Tunnel restriction code (D)

Marine transport - IMDG

EmS (emergency plan) F-D, S-U

Marine pollution No

SILICONE GREASE

Creation date	21. January 2015	Version	2.0
Revision date	10. May 2018		

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended. The Act No. 350/2011 Coll., on Chemical Substances and Chemical Preparations as amended (the Chemical Act). Decree No. 80/2014 Coll., amending the Decree No. 194/2001 Coll., laying down technical requirements for aerosol sprays as amended. Decree No. 432/2003 Coll., laying down conditions for assigning categories to individual jobs, limit values of indices from biological exposure tests, conditions for the sampling of biological materials for biological exposure and the particulars of the reports on work with asbestos and biological agents as amended. REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents, as amended.

15.2. Chemical safety assessment

not available

SECTION 16: Other information**A list of standard risk phrases used in the safety data sheet**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P211	Do not spray on an open flame or other ignition source.
P280	Wear protective gloves/eye protection.
P273	Avoid release to the environment.
P271	Use only outdoors or in a well-ventilated area.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P403	Store in a well-ventilated place.
P501	Dispose of contents/container in accordance with national regulations.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
DNEL	Derived no-effect level

SILICONE GREASE

Creation date	21. January 2015	Version	2.0
Revision date	10. May 2018		

EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
IC ₅₀	Concentration causing 50% blockade
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LOAEC	Lowest observed adverse effect concentration
LOAEL	Lowest observed adverse effect level
log K _{ow}	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution From Ships
NOAEC	No observed adverse effect concentration
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
NOEL	No observed effect level
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted no-effect concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative

Aerosol	Flammable aerosol
Aquatic Chronic	Hazardous to the aquatic environment
Asp. Tox.	Aspiration hazard
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Press. Gas	Gases under pressure
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

SILICONE GREASE

Creation date	21. January 2015	Version	2.0
Revision date	10. May 2018		

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

2, 3, 15, 16.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.