

Chain Lube High Pressure

Grease for heavy-duty chain gears.



Specifications:

- Long-lasting lubrication
- High mechanical durability
- Excellent penetration
- Silicone free

Advantages:

- Resists corrosion
- Contains PTFE for better lubricity
- Anti-fling properties

Applications:

Semi-synthetic multipurpose grease with strong adhesive properties and high mechanical durability designed for high-speed, high-stress applications. Resistant to “fling-off” through centrifugal force.

Usage:

On any moving metal parts to improve slip and to prevent malfunction and seizure. Perfect for lubrication at a wide temperature range and in both wet and dry environment. Particularly suitable for gears, chains, conveyors etc.

Order codes:

Name	Storage code	Package	Volume / Size	Order number
Chain Lube High Pressure	CLH	Spray	400 ml	1 50056

Instructions for use:

1. Remove any old grease or lubricant from the surface; clean and degrease with a suitable **RETECH** degreaser.
2. Shake the container well before use (minimum of 1 minute).
3. Apply **CHAIN LUBE HIGH PRESSURE** on the inner side of the chain.
4. Wait for several minutes to ensure perfect penetration and adhesion of the grease.

ONLY FOR PROFESSIONAL AND INDUSTRIAL USE!**Technical data:**

Specific gravity:	0.81g/cm ³
Application temperature:	ambient temperature
Temperature resistance:	-15 °C to 150 °C (short term)
Flash point:	< -20 °C

Storage:

In a dry place, at a temperature between 15 °C and 30 °C..

Health and Safety:

Please read our Material Safety Data Sheet.

Declaration:

The information and recommendations in this publication are to the best of our knowledge reliable. However nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Address:

RETECH, s.r.o., Vackova 1541/4; Praha 5 - Stodůlky; Czech Republic

Contact address: 285 02 Suchdol u Kutné Hory cp. 212; tel./fax: +420 327 596 128; e-mail: info@retech.cz