

# Epoxy Primer Spray



Universal 1K epoxy primer spray paint.



## Properties:

- Excellent adhesion on various materials
- Possible setting of application amount
- Excellent corrosion and humidity resistance
- Suitable for “wet-on-wet” application

## Advantages:

- Variable usage (steel and zinc-coated iron sheets, aluminium, anodized aluminium surfaces, ...)
- Saves work material, efficient application
- Long-term protection and “closing” of the repaired area
- Saves time for repair

## Applications:

**EPOXY PRIMER SPRAY** is a universal 1K epoxy primer spray paint. It can be applied as primer protection coating for various materials, such as steel and zinc-coated iron sheets, aluminium, anodized aluminium surfaces, as well as sanded and welded areas before applying sealants, fillers or screeds. Provides the treated area with excellent protection from corrosion and humidity. Improves adhesion of final varnishes.

## Order codes:

Name	Storage code	Package	Volume / Size	Order number
Epoxy Primer Spray	EPS	Spray	400 ml	1 35079

### Instructions for use:

1. Remove rust from metal surfaces.
2. Degrease and clean thoroughly.
3. Roughen with P320 sandpaper.
4. Clean, degrease and dry the surface again.
5. Shake the container well for min. 2 minutes.
6. Turn the nozzle to set the desired application amount.
7. Apply 1 to 2 even layers from a distance of about 25 cm.
8. Leave to air out for 3 to 5 minutes between applying layers.
9. Drying time depends on the layer thickness, air humidity and ambient temperature: ca 12 to 15 min (15 to 60 min for screeds).

**ONLY FOR PROFESSIONAL AND INDUSTRIAL USE!**

### Health and Safety:

Please read our Material Safety Data Sheet.

### Declaration:

The information and recommendations in this publication are to the best of our knowledge reliable. However nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

### Address:

**RETECH, s.r.o.**, Vackova 1541/4; Praha 5 - Stodůlky; Czech Republic  
**Contact address:** 285 02 Suchdol u Kutné Hory cp. 212; tel./fax: +420 327 596 128; e-mail: info@retech.cz