

Graphite Grease 3



Plastic grease with pure GRAPHITE powder for heavy duty operations.



Properties:

- Excellent pressure and shock load resistance
- Long-term resistance to water and dust particle penetration

Applications:

GRAPHITE GREASE 3 was developed for greasing of contact surfaces, sliding mechanisms, running gears and other contact parts who are under extreme load, whether from shocks or pressure.

Order codes:

Name	Storage code	Package	Volume / Size	Order number
Graphite Grease 3 - 8 kg	GG3	Bucket	8 kg	R 34453

Instructions for use:

1. Remove mechanical impurities and old grease remnants.
2. Degrease with a suitable **RETECH** degreaser and leave to air out.
3. Apply **GRAPHITE GREASE 3** using a grease gun, brush or other suitable tool.

ONLY FOR PROFESSIONAL AND INDUSTRIAL USE!**Technical data:**

NLGI grade	3
Consistency	Fat
Density	950 kg/m ³
Colour	Black
Odour	Plastic grease specific
Temperature resistance	-30 °C to +70 °C (short-term up to +80 °C)
Pressure resistance	10 MPa

Health and Safety:

Please read our Material Safety Data Sheet.

Declaration:

The information and recommendations in this publication are to the best of our knowledge reliable. However nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Address:

RETECH, s.r.o., Vackova 1541/4; Praha 5 - Stodůlky; Czech Republic

Contact address: 285 02 Suchdol u Kutné Hory cp. 212; tel./fax: +420 327 596 128; e-mail: info@retech.cz