

# H1-Silicone Oil



High-quality silicone lubricant of oily consistency,  
NSF/H1 registered.



## Properties:

- NSF H1 certified
- Lubricates rubber, plastic, metal and wood
- Excellent moisture protection
- 360° valve
- Temperature resistance -30 °C to +150 °C (short-term up to +250 °C)

## Advantages:

- Safe for use in food industry
- Application on various surfaces
- Long-term part conservation
- Application in any position of the container
- Variable usage

## Applications:

**H1-SILICONE OIL** is used as a protective lubricant for inaccessible areas of machines and other moving parts in food-related operations. It is also suitable for anti-corrosion and anti-moisture protection of electrical parts and connections. It forms a long-lasting protective film when applied to rubber or plastic. Reaches even inaccessible areas due to the oily consistency.

## Order codes:

Name	Storage code	Package	Volume / Size	Order number
H1-Silicone Oil	H1S0	Spray	400ml	1 35673

**Instructions for use:**

1. Shake well before use.
2. Apply **H1-SILICONE OIL** in the desired amount from a distance of 25-30 cm.
3. When applied to rubber or plastic, use a dry cloth to spread **H1-SILICONE OIL**.

**ONLY FOR PROFESSIONAL AND INDUSTRIAL USE!****Technical data:**

Consistency	Aerosol
Colour (visually)	Transparent
Density	0.585 g/cm <sup>3</sup>
Flash point	-97 °C
Fire point	+285 °C (the product is not self-igniting)
VOC	532.3 g/l
Temperature resistance	-30 °C to +150 °C (short-term up to +250 °C)

**Shelf life:**

Min. 2 years at a temperature T= +10 °C to +30 °C.

**Health and Safety:**

Please read our Material Safety Data Sheet.

**Declaration:**

The information and recommendations in this publication are to the best of our knowledge reliable. However nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

**Address:**

**RETECH, s.r.o.**, Vackova 1541/4; Praha 5 - Stodůlky; Czech Republic

**Contact address:** 285 02 Suchdol u Kutné Hory cp. 212; tel./fax: +420 327 596 128; e-mail: info@retech.cz