

# **Masking Tape**



Masking tape.





# **Properties:**

- High temperature resistance
- High solvent and water resistance
- Prevents paint and varnish leakage
- No glue residue after removing
- adhesiveness to a broad range of surfaces

# **Advantages:**

- Three different tape widths for multipurpose use
- Semitransparent tape material to ensure perfect tape adhesion to the surface
- The tape can be repeatedly moved to a proper position
- Leaves a sharp varnished edge after removing
- Suitable for both two-component and water-soluble paints and varnishes
- Simple application

#### **Applications:**

**RETECH Masking Tape** is a professional masking tape used especially to cover automotive parts when applying paint. Industrial use includes covering parts and plugging openings before manual pneumatic varnishing of welds, workpieces and other machine parts. It can be used in construction when painting and line finishing.

The bearing layer of **RETECH Masking Tap**e is made of smooth paper, carrying rubber resin based glue. The masking tape has high tensile strength, low elasticity and excellent initial adhesiveness. The tape can be easily applied in a radius and can be repeatedle moved into proper position before painting. It has high solvent and water resistance. It prevents paint and varnish leakage onto the masked surface.

**RETECH Masking Tape** is very easy to remove with no tears, it creates a sharp edge after removal and leaves no glue residue.



#### Instructions for use:

Before applying the tape, the surface must be dust-free, degreased, dry and clean.

## **ONLY FOR PROFESSIONAL AND INDUSTRIAL USE!**

#### Technical data:

Colour	yellow			
Tape thickness	0.15 mm			
Adhesiveness	7-10 N (19–48 mm)			
Elongation	Less than 4 %			
Application temperature	+10 °C to +35 °C			
Temperature resistance	up to +80 °C for 30 minutes			
Use	interior			
UV resistane	no			
Tube inside diameter	76.0 mm			

## Storage:

Store in a dry and dark place at a temperature between +5°C and +25°C and relative humidity between 40 and 60 %. The masking tape can be used for two years after purchase.

#### Order codes:

Name	Storage code	Package	Volume / Size	Order number
Masking Tape 19 mm - Set 15 pcs	MT19S	Set	15x 50 m	1 36524
Masking Tape 28 mm - Set 10 pcs	MT28S	Set	10x 50 m	1 36525
Masking Tape 48 mm - Set 6 pcs	MT48S	Set	6x 50 m	1 36527

## **Declaration:**

The information and recommendations in this publication are to the best of our knowledge reliable. However nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

#### Address:

**RETECH, s.r.o.**, Vackova 1541/4; Praha 5 - Stodůlky; Czech Republic **Contact address**: 285 02 Suchdol u Kutné Hory cp. 212; tel./fax: +420 327 596 128; e-mail: info@retech.cz