

NUTLOCK



Securing anaerobic sealant for screw connections.



Properties:

- Secures and seals any screw connection
- Medium connection strength
- Does not trickle or drip
- Guaranteed connection quality
- No hazard pictograms

Advantages:

- Multipurpose use
- Easy to disconnect using basic tools
- Does not leak from the application area
- Treated parts adhere and “stick together”

Applications:

Designed for easy installation and securing of screws and nuts and after curing as prevention against spontaneous loosening of the connection, e.g. as a result of vibrations. Created medium-strong connection, possible to disassemble using common procedures.

- replaces washers and other seals
- used to secure screws on shaping machines, hydraulic systems, transmission housing, bearing and shaft housing units, etc.
- any other construction applications with the need to secure and seal screw connections

Order codes:

Name	Storage code	Package	Volume / Size	Order number
Nutlock	NTL	Bottle	50 ml	R 34702

Instructions for use:

1. Remove any impurities and degrease the connected parts using **RETECH Clean**.
2. Apply **Nutlock** on the threads and assemble the connection.
3. Additional securing will take effect 5 to 10 minutes after assembling, depending on ambient conditions.

ONLY FOR PROFESSIONAL AND INDUSTRIAL USE!**Technical data:**

Temperature resistance	-55 °C to +180 °C
Colour	blue
Density	1.04 g/cm ³
Viscosity cPs	3000
Flash point	> 100 °C
Fixation time	< 10 minutes
Full curing	after 24 hours
Lap shear strength	15 - 25 Nm
Break loose torque	up to 30 Nm
Maximum clearance space	0.2 mm
Shelf life	12 months (20 °C)

Health and Safety:

Please read our Material Safety Data Sheet.

Declaration:

The information and recommendations in this publication are to the best of our knowledge reliable. However nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Address:

RETECH, s.r.o., Vackova 1541/4; Praha 5 - Stodůlky; Czech Republic

Contact address: 285 02 Suchdol u Kutné Hory cp. 212; tel./fax: +420 327 596 128; e-mail: info@retech.cz