

Sil Gasket Black Neutral



Black neutral RTV adhesive and Sealant material.



Properties:

- Neutral bases
- Excellent adhesion to various materials,
- Safe for sensors and lambda probes
- Excellent resistance to oils and chemicals
- Fast drying and no shrinking
- Sophisticated application

Advantages:

- Odorless application
- Versatility of use
- Use in demanding conditions
- Efficiency and perfect repair results
- No dispensing gun required

Applications:

SIL GASKET BLACK NEUTRAL is a neutral RTV adhesive and Sealant material. It is used for various sealing applications such as sealing of engine housings, oil pans, gear boxes, water pumps, heating radiators, thermostats, process openings, flanges, etc.

The product contains silicone.

Order codes:

Name	Storage code	Package	Volume / Size	Order number
Sil Gasket Black Neutral	SGBN	Pressure vessel	215 ml	1 35406

Instructions for use:

1. Both surfaces must be clean, dry and oil free.
2. Apply a uniform layer of **SIL GASKET BLACK NEUTRAL** directly from the pressure can onto only on one side of the joint.
3. Contact both surfaces within approx. 5 minutes and keep the gap between.
4. After approx. 30 minutes proceed the final assembly of both parts together.

ONLY FOR PROFESSIONAL AND INDUSTRIAL USE!**Technical data:**

Composition:	Polysiloxane base, neutral curing
Density	1,05 g/ml
Temperature resistance	-70 °C up to +330 °C (Shortly +350 °C)
Adhesion to the surface	2 MPa
Hardness (SHORE A)	35
Elongation to break	400 %
Drying speed (surface)	15 min (23 °C / 50 % RH)
Curing speed	3 mm/24 Hrs (23 °C / 50 % RH)
Shelf life	12 months (+5 °C to +25 °C)

Health and Safety:

Please read our Material Safety Data Sheet.

Declaration:

The information and recommendations in this publication are to the best of our knowledge reliable. However nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Address:

RETECH, s.r.o., Vackova 1541/4; Praha 5 - Stodůlky; Czech Republic
Contact address: 285 02 Suchdol u Kutné Hory cp. 212; tel./fax: +420 327 596 128; e-mail: info@retech.cz