

Smart LED Set



Rechargeable multipurpose LED inspection set.



Properties:

- Multipurpose design with an innovative quick LED torch exchange system
- Rechargeable torch with a strong magnet on the torch body
- High LED luminous intensity
- Two intensity settings
- USB-C connector charging

Advantages:

- All-round use for various maintenance and repair work
- Practical set of three torches in one package
- Flexi extension for lighting of inaccessible places
- Firm aluminium body with attractive design
- High resistance to weather conditions
- High mechanical resistance

Package Contents:

Aluminium torch body with a rechargeable battery	1 pc
Traditional LED torch with a zoom function	1 pc
Flexi LED torch with a zoom function	1 pc
Flat SLIM LED angle torch – 180°	1 pc
Charging adapter 230 V/50 Hz	1 pc
Charging adapter for a car 12 V / USB	1 pc
USB-A / USB-C charging cable	1 pc

Order codes:

Name	Storage code	Package	Volume / Size	Order number
Smart LED Set	SLS	Paper box	Set	R 34439

Use:

SMART LED SET is a professional rechargeable LED inspection set, used especially for auto repair and industrial use while performing inspection, maintenance and repair work. Thanks to its high resistance to weather conditions and mechanical resistance, the torch is suitable for both interior and exterior heavy duty operations. **SMART LED SET** includes three torch extensions for various applications. A traditional LED torch for normal use, a flexible LED torch for lighting of inaccessible places and a flat SLIM LED torch, adjustable to up to an 180° angle for surface lighting. Thanks to a strong magnet at the end of the torch, it can easily be attached to any ferro-magnetic surface.

Remove the current torch type from the torch body using a bayonet and attach your required type. Turn the torch on using the button for 50% / 100% / Off.

Do not look directly into the beam of light - DANGER OF SERIOUS DAMAGE!

Technical data:

	lighting time h		luminous intensity lm		light temperature K
	50 %	100 %	50 %	100 %	
Traditional LED torch with a zoom function	5.5	2.5	140	280	5800–6500
Flexi LED torch with a zoom function	8	5	100	200	
Flat SLIM LED angle torch – 180°	5.5	2.5	175	350	
Torch body material	Highly anodized aluminium				
Torch weight	954 g				
Torch body magnet strength	78 N				
Ingress Protection	IP54				
Mechanical resistance	IK07				
Operating temperature range	-20 °C to +50 °C				
Batteries used	1x 18650 2200 mAh Li-ion (2x CR123A)				



Storage:

In a dry place, in the original packaging.

Declaration:

The information and recommendations in this publication are to the best of our knowledge reliable. However nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Address:

RETECH, s.r.o., Vackova 1541/4; Praha 5 - Stodůlky; Czech Republic
Contact address: 285 02 Suchdol u Kutné Hory cp. 212; tel./fax: +420 327 596 128; e-mail: info@retech.cz