

Super Lube



Transparent industrial grease based on calcium.



Specifications:

- Does not contain acid or resin
- Top penetrability when applied
- Unique 360° valve
- Excellent adhesiveness and lubricating capability
- Temperature range -20 through $+160^{\circ}\text{C}$

Advantages:

- Applicable with all materials, including rubber and plastic
- Penetrates to all lubrication points
- Applicable at any position or angle
- Resistant even pressure washing
- Universal industrial grease

Applications:

The **SUPER LUBE** is used for greasing locks, connectors, lever mechanisms, bearings, cogwheels, gear mechanisms, joint systems, axial systems, chains, etc.

Order codes:

Name	Storage code	Package	Volume / Size	Order number
Super Lube	RSL	Spray	500 ml	R 34403

Instructions for use:

1. Before any application, shake the vessel first.
2. Apply the **SUPER LUBE** at reasonable layer onto the lubrication points.
3. To grease points with difficult access, use the applicator (a part of the supply).

ONLY FOR PROFESSIONAL AND INDUSTRIAL USE!

Health and Safety:

Please read our Material Safety Data Sheet.

Declaration:

The information and recommendations in this publication are to the best of our knowledge reliable. However nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Address:

RETECH, s.r.o., Vackova 1541/4; Praha 5 - Stodůlky; Czech Republic
Contact address: 285 02 Suchdol u Kutné Hory cp. 212; tel./fax: +420 327 596 128; e-mail: info@retech.cz