

ANTISTATIC SPRAY WAX

Creation date	16th December 2022	Version	3.0
Revision date			

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier** ANTISTATIC SPRAY WAX
Substance / mixture mixture
Number 1 35430
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
Cleaning agent.
Mixture uses advised against
For professional use only.
- 1.3. Details of the supplier of the safety data sheet**
Supplier
Name or trade name RETECH, s.r.o.
Address Vackova 1541/4, Praha 5 - Stodůlky, 155 00
Czech Republic
Identification number (CRN) 25018205
VAT Reg No CZ25018205
Phone +420327596428
E-mail info@retech.cz
Web address www.retech.com
- Competent person responsible for the safety data sheet**
Name RETECH, s.r.o.
E-mail info@retech.cz
- 1.4. Emergency telephone number**
European emergency number: 112

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008
The mixture is classified as dangerous.

Aerosol 1, H222, H229
STOT RE 1, H372
Aquatic Chronic 3, H412

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Extremely flammable aerosol. Pressurised container: May burst if heated.

Most serious adverse effects on human health and the environment

Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

- 2.2. Label elements**

Hazard pictogram**Signal word**

Danger

Hazardous substances

hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

ANTISTATIC SPRAY WAX

Creation date	16th December 2022	Version	3.0
Revision date			

H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Precautionary statements	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P314	Get medical advice/attention if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to in accordance with national regulations.

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.
>=30 % aliphatic hydrocarbons, <5 % non-ionic surfactants, <5 % Parfum

2.3. Other hazards

Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 64742-82-1 EC: 919-446-0 Registration number: 01-2119458049-33	hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	10-30	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 STOT RE 1, H372 Aquatic Chronic 2, H411	
CAS: 68476-85-7 EC: 270-704-2	Petroleum gases, liquefied	10-30	Flam. Gas 1, H220 Press. Gas (liquefied gas), H280	
CAS: 7632-00-0 EC: 231-555-9 Registration number: 01-2119471836-27	sodium nitrite	<1	Ox. Sol. 3, H272 Acute Tox. 3, H301 Eye Irrit. 2, H319 Aquatic Acute 1, H400 (M=1)	

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Transfer the affected person to the fresh air and ensure calm environment for body and mind. Remove person to fresh air and keep comfortable for breathing. In the event of issues, find medical advice.

If on skin

Immediately wash with water and soap and rinse thoroughly.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. In the event of issues, find medical advice.

If swallowed

Rinse out the mouth with clean water. DO NOT INDUCE VOMITING! In the event of issues, find medical advice.

ANTISTATIC SPRAY WAX

Creation date	16th December 2022	Version	3.0
Revision date			

4.2. Most important symptoms and effects, both acute and delayed**If inhaled**

Dizziness, headaches, fatigue Nausea.

If on skin

Repeated exposure may cause skin dryness or cracking.

If in eyes

When intruding eyes, it can evoke irritation.

If swallowed

Irritation, nausea. The central nervous system may be affected.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide, foam, powder.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise.

5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide sufficient ventilation. Do not inhale gases and vapours. Extremely flammable aerosol. Pressurised container: May burst if heated. Remove all ignition sources. Take precautionary measures against static discharge. Do not touch or walk through spilt material. Danger of slipping on spilled product. Use personal protective equipment for work. Prevent contact with skin and eyes. Wash hands and exposed parts of the body thoroughly after handling.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Ventilate the room. Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. After removal of the product, wash the contaminated site with plenty of water.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Use personal protective equipment as per Section 8. Ensure good ventilation/exhaustion at the workplace. Do not inhale gases and vapours. Prevent contact with skin and eyes. Wash hands and exposed parts of the body thoroughly after handling. Do not spray on an open flame or other ignition source. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. No smoking. Take precautionary measures against static discharge. Pressurised container: May burst if heated. Keep away from sources of heating, ignition and direct sunlight. Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Keep away from sources of heating, ignition and direct sunlight.

Storage class

2B - Aerosols

Storage temperature

min 4 °C, max 40 °C

7.3. Specific end use(s)

not available

ANTISTATIC SPRAY WAX

Creation date

16th December 2022

Revision date

Version

3.0

SECTION 8: Exposure controls/personal protection
8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

DNEL

hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	330 mg/m ³	Systemic chronic effects		
Workers	Inhalation	570 mg/m ³	Systemic acute effects		
Workers	Dermal	21 mg/kg bw/day	Systemic chronic effects		
Consumers	Inhalation	71 mg/m ³	Systemic chronic effects		
Consumers	Inhalation	570 mg/m ³	Systemic acute effects		
Consumers	Dermal	12 mg/kg bw/day	Systemic chronic effects		
Consumers	Oral	21 mg/kg bw/day	Systemic chronic effects		

sodium nitrite

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	2 mg/m ³	Systemic chronic effects		
Workers	Inhalation	2 mg/m ³	Systemic acute effects		

PNEC

sodium nitrite

Route of exposure	Value	Value determination	Source
Freshwater environment	0.005 mg/l		
Water (intermittent release)	0.005 mg/l		
Seawater	0.006 mg/l		
Microorganisms in wastewater treatment plants	21 mg/l		
Freshwater sediment	0.019 mg/kg of dry substance of sediment		
Sea sediments	0.022 mg/kg of dry substance of sediment		
Soil (agricultural)	0.001 mg/kg of dry substance of soil		

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Tightly sealed goggles.

Skin protection

Hand protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Material of gloves: Nitrile rubber, NBR. (> 0,46 mm). Neoprene.(>0,54 mm). When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Contaminated skin should be washed thoroughly. Other protection: protective workwear.

ANTISTATIC SPRAY WAX

Creation date	16th December 2022	Version	3.0
Revision date			

Respiratory protection

Provide sufficient ventilation.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	gas
Colour	white
Odour	characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	data not available
Flammability	Extremely flammable aerosol.
Lower and upper explosion limit	data not available
Flash point	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	data not available
Kinematic viscosity	data not available
Solubility in water	miscible
Solubility in fats	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
Density and/or relative density	data not available
Form	aerosol dispenser: spray aerosol
data not available	

9.2. Other information

Evaporation rate	non-applicable
------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

When used in the standard way, there is not any dangerous reaction with other substances.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

not available

10.4. Conditions to avoid

Keep away from sources of heating, ignition and direct sunlight.

10.5. Incompatible materials

Unknown.

10.6. Hazardous decomposition products

Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

ANTISTATIC SPRAY WAX

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	ATE	105882.35 mg/kg			

ANTISTATIC SPRAY WAX

Creation date

16th December 2022

Revision date

Version

3.0

hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	15000 mg/kg		Rat	
Oral	ATE	15000 mg/kg			
Dermal	LD ₅₀	3400 mg/kg		Rat	
Dermal	ATE	3400 mg/kg			

Petroleum gases, liquefied

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Inhalation	LC ₅₀	20.01 mg/l			
Inhalation	ATE	20.01 mg/l			

sodium nitrite

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	180 mg/kg		Rat	
Oral	ATE	180 mg/kg			

Skin corrosion/irritation

Based on available data the classification criteria are not met.

Serious eye damage/irritation

Based on available data the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

Based on available data the classification criteria are not met.

Toxicity for specific target organ - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Route of exposure	Parameter	Value	Result	Species	Sex
Oral	NOAEL	1056 mg/kg		Rat	
Oral	ATE	1056 mg/kg			

Aspiration hazard

Based on available data the classification criteria are not met.

11.2. Information on other hazards

not available

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

Harmful to aquatic life with long lasting effects.

hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Parameter	Value	Exposure time	Species	Environment
LC ₅₀	<30 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	
EC ₅₀	<22 mg/l	48 hour	Aquatic invertebrates (Daphnia magna)	

ANTISTATIC SPRAY WAX

 Creation date 16th December 2022
 Revision date Version 3.0

hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Parameter	Value	Exposure time	Species	Environment
IC ₅₀	4.6-10 mg/l	72 hour	Algae	
EC ₅₀	43.98 mg/l	48 hour	Microorganisms	

sodium nitrite

Parameter	Value	Exposure time	Species	Environment
LC ₅₀	360 mg/l	48 hour	Fishes (Leuciscus idus)	
LC ₅₀	0.54-26.3 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	
EC ₅₀	15.4 mg/l	48 hour	Aquatic invertebrates (Daphnia magna)	
NOEC	9.86 mg/l		Aquatic invertebrates (Daphnia magna)	

Chronic toxicity

hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Parameter	Value	Exposure time	Species	Environment
NOEC	0.097 mg/l	21 day	Aquatic invertebrates (Daphnia magna)	

sodium nitrite

Parameter	Value	Exposure time	Species	Environment
NOEC	9.86 mg/l		Aquatic invertebrates (Daphnia magna)	

12.2. Persistence and degradability

The mixture is biodegradable.

12.3. Bioaccumulative potential

No bioaccumulation potential.

12.4. Mobility in soil

The product is soluble and mobile in water and soil.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

not available

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations
13.1. Waste treatment methods

Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

16 03 05 organic wastes containing hazardous substances *

Packaging waste type code

15 01 11 metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers *

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

ANTISTATIC SPRAY WAX

Creation date	16th December 2022	Version	3.0
Revision date			

SECTION 14: Transport information**14.1. UN number or ID number**

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not relevant

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant


Additional information

Hazard identification No.

UN number

Classification code

Safety signs



5F

2.1

**Road transport - ADR**

Excepted quantities

E0

Tunnel restriction code

(D)

Railway transport - RID**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended. REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents, as amended.

15.2. Chemical safety assessment

not available

SECTION 16: Other information**A list of standard risk phrases used in the safety data sheet**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H272	May intensify fire; oxidiser.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.

ANTISTATIC SPRAY WAX

Creation date	16th December 2022	Version	3.0
Revision date			

H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.
P314	Get medical advice/attention if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P260	Do not breathe spray.
P271	Use only outdoors or in a well-ventilated area.
P501	Dispose of contents/container to in accordance with national regulations.

A list of additional standard phrases used in the safety data sheet

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
DNEL	Derived no-effect level
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
ES	Identification code for each substance listed in EINECS
EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
IC ₅₀	Concentration causing 50% blockade
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
log K _{ow}	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution from Ships
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic

ANTISTATIC SPRAY WAX

Creation date	16th December 2022	Version	3.0
Revision date			

PNEC	Predicted no-effect concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative

Acute Tox.	Acute toxicity
Aerosol	Aerosol
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Ox. Sol.	Oxidising solid
Press. Gas	Gases under pressure
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 3.0 replaces the SDS version from 03 July 2018. Changes were made in sections 11, 12, 13, 15 and 16.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.