

Deep Prewash



Product for machine prewashing of bodyworks – concentrate.



Properties:

- Excellent prewash performance
- Excellent adhesiveness to the washed surface
- High foaming quality
- Phosphate-free

Advantages:

- Pleasant odour
- Saves time of a cleaning cycle

Applications:

RETECH Deep Prewash is a professional, highly efficient foaming alkaline product for machine prewashing of bodyworks designed to remove coarse operational impurities, grease, and dust from the bodywork surface of personal, commercial, public transport, and other vehicles.

It is used especially in automatic brush car washes and washing boxes. When using a foamer it creates a rich, degreasing foam, is easy to rinse and optimally prepares the vehicle for further cleaning.

Warning: The product isn't suitable for materials with surface treatment sensitive to chemical solvents, as it may damage or discolour them. These are typically low-quality metallic plastic parts. Before using on this type of material it is recommended to test the product on a small, concealed area.

Order codes:

Name	Storage code	Package	Volume / Size	Order number
Deep Prewash 5 L	DPW5	Can	5L	1 35881
Deep Prewash 25L	DPW25	Can	25L	1 35882

Instructions for use:

1. Rinse and cool the surface, and remove very coarse dirt before applying the product.
2. Set a 1:40 dilution ratio on the dispenser. Use warm water to increase washing effect.
3. Apply this mix onto the surface using a pressure washer and leave for a short while. Leave for 1-2 minutes if prewashing by hand.
4. Brush the surface with the rinser turned on. Use warm water to increase washing effect. If hand washing, use a soft brush, microfibre gloves, or a car sponge.
5. Rinse the surface with a strong stream of water.

General rules for car bodywork washing:

- Never apply any product on the bodywork in direct sunlight
- Never apply any product directly onto a hot surface, always cool it down with a stream of cold water first
- Never leave the product to dry on the surface.
- Keep in mind that the quality and mineralisation of used water can leave calcic residue on the paint after drying.

ONLY FOR PROFESSIONAL AND INDUSTRIAL USE!**Technical data:**

Consistency:	Liquid
Colour:	Yellow
pH:	12,5-13,5
Density:	1,01-1,02 g/cm ³
Application temperature:	5 °C–30 °C
Recommended dilution:	1:40

Storage:

In a dry place at a temperature +5 °C to +25 °C. Protect from direct sunlight and subzero temperatures.

Health and Safety:

Health and Safety information is available in the Material Safety Data Sheet and on the label.

Declaration:

The information and recommendations in this publication are to the best of our knowledge reliable. However nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Address:

RETECH, s.r.o., Vackova 1541/4; Praha 5 - Stodůlky; Czech Republic
Contact address: 285 02 Suchdol u Kutné Hory cp. 212; tel./fax: +420 327 596 128; e-mail: info@retech.cz