

Industrial Floor Cleaner



Highly efficient industrial floor cleaner /
CONCENTRATE.



Properties:

- Extra effective even on dried up deposits
- Non-foaming formula for industrial cleaning
- Removes fats, grease, tyre marks, aged soiling
- Suitable for all types of industrial floor cleaners

Advantages:

- Very fast cleaning effect
- Saves time of a complete cleaning cycle
- One product for many floor types
- Suitable also for hand washing

Applications:

RETECH Industrial Floor Cleaner is an extra strong non-foaming cleaning product for quick and efficient industrial cleaning from fats, grease, tyre marks, aged soiling and other impurities. Can be used on a wide scale of industrial floor types including acrylate, concrete (polished and unpolished), cement, epoxy, polymer concrete, and armoured floors. **Industrial Floor Cleaner** can be used in various industrial operations such as floors in manufacturing halls, warehouses, logistic centres, workshops, hallways and corridors, basements, and more. In automotive industry, **Industrial Floor Cleaner** is used mostly in service workshops, warehouses, garages and parking lots, body shops, paint shops, and similar places. It is also used to clean ceramic tiles in industrial car washes for personal and commercial vehicles, buses, trains, and other mass transport vehicles.

Order codes:

Name	Storage code	Package	Volume / Size	Order number
Industrial Floor Cleaner 5L	IFC	Can	5 l	1 36419
Industrial Floor Cleaner 20L	IFC20	Can	20 l	1 36420
Industrial Floor Cleaner 200L	IFC200	HD-PE Barrel	200 l	1 36421
Industrial Floor Cleaner 1000L	IFC1000	IBC container	1000 l	1 36422

Instructions for use:

1. Always use protective equipment when handling the product – prevent eye and skin contact!
2. For industrial cleaning dilute with water in ration 1:10 – 1:200 deppend of degree of pollution.
3. Apply the desired mixture using a cleaning machine on the surface and leave to work for 2-5 minutes based on the level of soiling. Make sure the product does not dry up on the floor!
4. Thoroughly brush the surface, wipe with clean water, and properly dry up.

For hand washing of other floor types (PVC, vinyl, etc.) we recommend to dilute the product at a 1:10 to 1:100 ration. The hand washing process is otherwise identical to the industrial one.

ONLY FOR PROFESSIONAL AND INDUSTRIAL USE!**Warning:**

The product is not suitable for polished aluminium, zinc, magnesium, copper, brass and other polished surfaces sensitive to strongly alkaline products. It is recommended to first try the product in a non-visible place before using on the above mentioned surfaces.

Technical data:

Consistency	Liquid
Base	Sodium hydroxide
Colour (visually)	Yellow
Odour	Distinct
pH level	13-14 (non-diluted product)
Density at 20°C	1.05 to 1.10 g/cm ³
Usability time	12 months after opening

Storage:

In a dry place at a temperature +5 °C to +30 °C. Protect from direct sunlight and subzero temperatures.

Healt and Safety:

Please read our Material Safety Data Sheet.

Declaration:

The information and recommendations in this publication are to the best of our knowledge reliable. However nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Address:

RETECH, s.r.o., Vackova 1541/4; Praha 5 - Stodůlky; Czech Republic

Contact address: 285 02 Suchdol u Kutné Hory cp. 212; tel./fax: +420 327 596 128; e-mail: info@retech.cz